


856930

457.5 MHz SAW Filter

Applications

- Smart metering
- Remote meter reading wireless modules
- Licensed band wireless
- General purpose wireless



Product Features

- Usable bandwidth 15 MHz
- Low loss
- Dimensions: 3.80 x 3.80 x 1.27 mm
- Single-ended operation
- No impedance matching required for operation at 50Ω
- Matching can be added for high attenuation performance
- Ceramic Surface Mount Package (SMP)
- Industry standard package
- Hermetic **RoHS** compliant, **Pb-free**

General Description


Wireless RF system filter designed specifically for the smart metering infrastructure market.

Low insertion loss, with the option to match for high attenuation, and single ended Input/Output ports make this an effective choice for wireless system designers.

Suitable for use in remote meter reading applications, especially licensed band applications targeting the water metering market.

Functional Block Diagram

Top view



Pin Configuration

| Pin # | SE | Description |
|---------|----|-------------|
| 2 | | Input |
| 6 | | Output |
| 1,3,5,7 | | Ground |
| 4,8 | | Case Ground |

Ordering Information

| Part No. | Description |
|------------|------------------|
| 856930 | packaged part |
| 856930-EVB | evaluation board |

Please specify the unmatched or matched configuration when ordering an evaluation board.

Standard T/R size = 4000 units/reel.

Specifications - Unmatched

Electrical Specifications ⁽¹⁾

Specified Temperature Range: ⁽²⁾ -40 to +85 °C

| Parameter ⁽³⁾ | Conditions | Min | Typical ⁽⁴⁾ | Max | Units |
|--|----------------|-----|------------------------|-----|--------|
| Center Frequency | | - | 457.5 | - | MHz |
| Maximum Insertion Loss | 450 – 465 MHz | - | 2.2 | 3.0 | dB |
| Amplitude Variation ⁽⁵⁾ | 450 – 465 MHz | - | 1.4 | 2.0 | dB p-p |
| Lower 3.0 dB Bandedge ⁽⁶⁾ | | - | 447.9 | 450 | MHz |
| Upper 3.0 dB Bandedge ⁽⁶⁾ | | 465 | 466.9 | - | MHz |
| Upper 25 dB Bandedge ⁽⁶⁾ | | - | 470.2 | 472 | MHz |
| Upper 34 dB Bandedge ⁽⁶⁾ | | - | 470.5 | 475 | MHz |
| Absolute Attenuation ⁽⁶⁾ | 10 – 420 MHz | 30 | 35 | - | dB |
| | 472 – 475 MHz | 25 | 70 | - | dB |
| | 475 – 480 MHz | 34 | 55 | - | dB |
| | 800 – 1000 MHz | 30 | 36 | - | dB |
| Input/Output Return Loss | 450 – 465 MHz | - | 9 | - | dB |
| Source Impedance (single-ended) ⁽⁷⁾ | | - | 50 | - | Ω |
| Load Impedance (single-ended) ⁽⁷⁾ | | - | 50 | - | Ω |

Notes:

- All specifications are based on the TriQuint schematic for the main reference design shown on page 4
- In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
- Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- Typical values are based on average measurements at room temperature
- Evaluated as the total variation over the specified band
- Relative to zero dB
- This is the optimum impedance in order to achieve the performance shown

Absolute Maximum Ratings

| Parameter | Rating |
|----------------------------|---------------|
| Operating Temperature | -40 to +85 °C |
| Storage Temperature | -40 to +85 °C |
| Input Power ⁽⁸⁾ | +20 dBm |

- Input Power is targeted for an applied CW modulated RF signal at 55 °C for 10,000 hours. Operation of this device outside of the parameter ranges listed above may cause permanent damage.

Specifications - Matched

Electrical Specifications ⁽¹⁾

Specified Temperature Range: ⁽²⁾ -40 to +85 °C

| Parameter ⁽³⁾ | Conditions | Min | Typical ⁽⁴⁾ | Max | Units |
|--|----------------|-----|------------------------|-------|--------|
| Center Frequency | | - | 457.5 | - | MHz |
| Maximum Insertion Loss | 450 – 465 MHz | - | 2.9 | 3.5 | dB |
| Amplitude Variation ⁽⁵⁾ | 450 – 465 MHz | - | 1.4 | 2.2 | dB p-p |
| Lower 3.5 dB Bandedge ⁽⁶⁾ | | - | 448.33 | 450 | MHz |
| Upper 3.5 dB Bandedge ⁽⁶⁾ | | 465 | 466.93 | - | MHz |
| Upper 25 dB Bandedge ⁽⁶⁾ | | - | 470.5 | 472.4 | MHz |
| Upper 34 dB Bandedge ⁽⁶⁾ | | - | 470.81 | 475 | MHz |
| Absolute Attenuation ⁽⁶⁾ | 10 – 300 MHz | 50 | 53 | - | dB |
| | 300 – 420 MHz | 25 | 32 | - | dB |
| | 472.4 – 475MHz | 25 | 65 | - | |
| | 475 – 480 MHz | 34 | 62 | - | dB |
| | 480 – 1000 MHz | 30 | 39 | - | dB |
| Input/Output Return Loss | 450 – 465 MHz | - | 9 | - | dB |
| Source Impedance (single-ended) ⁽⁷⁾ | | - | 50 | - | Ω |
| Load Impedance (single-ended) ⁽⁷⁾ | | - | 50 | - | Ω |

Notes:

- All specifications are based on the TriQuint schematic for the main reference design shown on page 6
- In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
- Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- Typical values are based on average measurements at room temperature
- Evaluated as the total variation over the specified band
- Relative to zero dB
- This is the optimum impedance in order to achieve the performance shown

Absolute Maximum Ratings

| Parameter | Rating |
|----------------------------|---------------|
| Operating Temperature | -40 to +85 °C |
| Storage Temperature | -40 to +85 °C |
| Input Power ⁽⁸⁾ | +20 dBm |


- Input Power is targeted for an applied CW modulated RF signal at 55 °C for 10,000 hours. Operation of this device outside the parameter ranges given above may cause permanent damage.

856930

457.5 MHz SAW Filter

Reference – Unmatched


Schematic



Notes:

1. No impedance matching required
2. Actual matching values may vary due to PCB layout and parasitic


PC Board



Notes:

- Top, middle & bottom layers: 1 oz copper
- Substrates: FR4 dielectric, .031" thick
- Finish plating: Nickel: 3-8 μ m thick, Gold: .03-.2 μ m thick
- Hole plating: Copper min .0008 μ m thick

Mounting Configuration







Notes:

1. All dimensions are in millimeters.
2. This footprint represents a recommendation only.


Bill of Material

| Reference Desg. | Value | Description | Manufacturer | Part Number |
|-----------------|-------|---------------|------------------|---------------|
| SMA | N/A | SMA connector | Radiall USA Inc. | 9602-1111-018 |
| PCB | N/A | 3-layer | multiple | 960700 |


Typical Performance - Unmatched (at room temperature)



Input Smith Chart



Output Smith Chart




856930

457.5 MHz SAW Filter

Reference – Matched


Schematic



Notes:

Actual matching values may vary due to PCB layout and parasitic


PC Board



Notes:

3-layer board - top, middle & bottom layer: 1 oz copper
 Substrates: .031" thick FR4 dielectric.
 Finish plating: Nickel: 3-8µm thick, Gold: .03-.2µm thick
 Hole plating: Copper min .0008µm thick

Mounting Configuration







Notes:

1. All dimensions are in millimeters.
2. This footprint represents a recommendation only.


Bill of Material

| Reference Desg. | Value | Description | Manufacturer | Part Number |
|-----------------|-------|-----------------------|------------------|-------------------|
| L1 | 24nH | Coil Wire-wound, 0402 | MuRata | LQW15AN24NJ00 |
| L2 | 10nH | Coil Wire-wound, 0402 | MuRata | LQW15AN10NJ00 |
| C1 | 12pF | Chip Ceramic, 0402 | MuRata | GRM1555C1H120GZ01 |
| C2 | 8.2pF | Chip Ceramic, 0402 | MuRata | GRM1555C1H8R2FZ01 |
| C3 | 10pF | Chip Ceramic, 0402 | MuRata | GRM1555C1H100KZ01 |
| SMA | N/A | SMA connector | Radiall USA Inc. | 9602-1111-018 |
| PCB | N/A | 3-layer | multiple | 960846 |


Typical Performance - Matched (at room temperature)



Input Smith Chart




Output Smith Chart



Mechanical Information

Package Information, Dimensions and Marking



Package Style: SMP-15
 Dimensions: 3.80 x 3.80 x 1.27 mm


Body: Al_2O_3 ceramic
 Lid: Kovar, Ni plated
 Terminations: Au plating 0.5 - 1.0 μ m, over a 2-6 μ m Ni plating

All dimensions shown are nominal in millimeters
 All tolerances are ± 0.15 mm except overall length and width ± 0.10 mm

The date code consists of day of the current year (Julian, 3 digits), Y = last digit of the year, and M = manufacturing site code

Tape and Reel Information

Standard T/R size = 4000 units/reel. All dimensions are in millimeters



856930

457.5 MHz SAW Filter

Product Compliance Information

ESD Information



Caution! ESD-Sensitive Device

ESD Rating: 1B

Value: Passes ≥ 800 V min.
Test: Human Body Model (HBM)
Standard: JEDEC Standard JESD22-A114

ESD Rating: B

Value: Passes ≥ 300 V min.
Test: Machine Model (MM)
Standard: JEDEC Standard JESD22-A115

MSL Rating

Devices are Hermetic, therefore MSL is not applicable

Solderability

Compatible with the latest version of J-STD-020, lead free solder, 260°C

Refer to [Soldering Profile](#) for recommended guidelines.

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: www.triquint.com
Email: info-sales@tqs.com

Tel: +1.407.886.8860
Fax: +1.407.886.7061

For technical questions and application information:

Email: flapplication.engineering@tqs.com

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru