

Type RN73 Series

Key Features

- High precision - TCR 5ppm/°C and 10ppm/°C
- Tolerance down to 0.01%
- Thin film (nichrome)
- Choice of packages
- Stable high frequency performance
- Temperature range -55°C to +155°C

Applications

- Communications
- Instrumentation
- Industrial controls
- Medical



The RN73 series is a high stability precision chip resistor range offering various power dissipations relating to chip size, TCR's down to 5ppm/°C and resistance tolerances to 0.01%. The resistor is produced with three sputtered layers giving optimum performance. Values are restricted to the E96 and E24 value grids. The RN73 has accurate and uniform physical dimensions to facilitate placement.

Characteristics - Electrical

| | 0402 | | | | | | 0603 | | | | | | 0805 | | | | | |
|--------------------------------|---------------|------|------|------|------|------|---------------|------|------|------|------|------|---------------|------|------|------|------|------|
| Rated Power @ 70°C: | 0.063W | | | | | | 0.063W | | | | | | 0.1W | | | | | |
| Resistance Range (Ohms) | Min: | 49R9 | 49R9 | 49R9 | 49R9 | 49R9 | 24R9 | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 | 24R9 | 24R9 | 24R9 | 4R3 | 24R9 | 4R3 |
| | Max: | 5K0 | 15K | 5K0 | 15K | 5K0 | 15K | 100K | 15K | 332K | 15K | 332K | 30K | 200K | 30K | 511K | 30K | 511K |
| Tolerance (%): | 0.01 | | 0.05 | | 0.1 | | 0.01 | | 0.05 | | 0.1 | | 0.01 | | 0.05 | | 0.1 | |
| Code Letter: | L | | A | | B | | L | | A | | B | | L | | A | | B | |
| Selection Series: | E24 & E96 | | | | | | E24 & E96 | | | | | | E24 & E96 | | | | | |
| Temp. Coefficient (ppm/°C): | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 |
| Code Letter: | A | C | A | C | A | C | A | C | A | C | A | C | A | C | A | C | A | C |
| Limiting Element Voltage: | 25V | | | | | | 50V | | | | | | 100V | | | | | |
| Max. Overload Voltage: | 50V | | | | | | 100V | | | | | | 200V | | | | | |
| Operating Temp. Range: | -55 to +155°C | | | | | | -55 to +155°C | | | | | | -55 to +155°C | | | | | |
| Climatic Category (°C): | 55/125/55 | | | | | | 55/125/55 | | | | | | 55/125/55 | | | | | |
| Insulation Resistance Dry Min: | 1000MΩ | | | | | | 1000MΩ | | | | | | 1000MΩ | | | | | |
| Stability: | 0.5% | | | | | | 0.5% | | | | | | 0.5% | | | | | |

| | 1206 | | | | | | 1210 | | | | | | 2010 | | | | | | |
|--------------------------------|---------------|------|------|------|-----|------|---------------|------|------|------|-----|------|---------------|------|------|------|-----|------|-----|
| Rated Power @ 70°C: | 0.125W | | | | | | 0.2W | | | | | | 0.25W | | | | | | |
| Resistance Range (Ohms) | Min: | 24R9 | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 | 24R9 | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 | 24R9 | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 |
| | Max: | 50K | 562K | 50K | 1M0 | 50K | 1M0 | 50K | 500K | 50K | 1M0 | 50K | 1M0 | 100K | 500K | 100K | 1M0 | 100K | 1M0 |
| Tolerance (%): | 0.01 | | 0.05 | | 0.1 | | 0.01 | | 0.05 | | 0.1 | | 0.01 | | 0.05 | | 0.1 | | |
| Code Letter: | L | | A | | B | | L | | A | | B | | L | | A | | B | | |
| Selection Series: | E24 & E96 | | | | | | E24 & E96 | | | | | | E24 & E96 | | | | | | |
| Temp. Coefficient (ppm/°C): | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | 5 | 10 | |
| Code Letter: | A | C | A | C | A | C | A | C | A | C | A | C | A | C | A | C | A | C | |
| Limiting Element Voltage: | 150V | | | | | | 150V | | | | | | 150V | | | | | | |
| Max. Overload Voltage: | 300V | | | | | | 300V | | | | | | 300V | | | | | | |
| Operating Temp. Range: | -55 to +155°C | | | | | | -55 to +155°C | | | | | | -55 to +155°C | | | | | | |
| Climatic Category (°C): | 55/125/55 | | | | | | 55/125/55 | | | | | | 55/125/55 | | | | | | |
| Insulation Resistance Dry Min: | 1000MΩ | | | | | | 1000MΩ | | | | | | 1000MΩ | | | | | | |
| Stability: | 0.5% | | | | | | 0.5% | | | | | | 0.5% | | | | | | |

Type RN73 Series

| | | 2512 | | | | | |
|---------------------------------------|-------------|---------------|------|------|-----|------|-----|
| Rated Power @ 70°C: | | 0.5W | | | | | |
| Resistance Range (Ohms) | Min: | 24R9 | 24R9 | 24R9 | 4R7 | 24R9 | 4R7 |
| | Max: | 100K | 500K | 100K | 1M0 | 100K | 1M0 |
| Tolerance (%): | | 0.01 | | 0.05 | | 0.1 | |
| Code Letter: | | L | | A | | B | |
| Selection Series: | | E24 & E96 | | | | | |
| Temp. Coefficient (ppm/°C): | | 5 | 10 | 5 | 10 | 5 | 10 |
| Code Letter: | | A | C | A | C | A | C |
| Limiting Element Voltage: | | 150V | | | | | |
| Max. Overload Voltage: | | 300V | | | | | |
| Operating Temp. Range: | | -55 to +155°C | | | | | |
| Climatic Category (°C): | | 55/125/55 | | | | | |
| Insulation Resistance Dry Min: | | 1000MΩ | | | | | |
| Stability: | | 0.5% | | | | | |

Characteristics - Environmental

| | Requirement | | Test Method |
|---|--|--------------|---|
| | Tol. ≤ 0.05% | Tol. > 0.05% | |
| Temperature Coefficient of Resistance (TCR): | As per TCRs specified in value range table on page 1 | | +25/-55/+25/+125/+25°C |
| Short Time Overload: | ΔR ±0.05% | ΔR ±0.2% | RCWV* 2.5 or max. overload voltage for 5 seconds |
| Insulation Resistance: | >1000MΩ | | Apply 100VDC for 1 minute |
| Endurance: | ΔR ±0.05% | ΔR ±0.2% | 70 ±2°C, max. working voltage for 1000hrs with 1.5hrs "ON" and 0.5hrs "OFF" |
| Damp Heat with Load: | ΔR ±0.05% | ΔR ±0.3% | 40 ±2°C, 90 - 95% R.H. max. working voltage hrs with 1.5hrs "ON" and 0.5hrs "OFF" |
| Bending Strength: | ΔR ±0.05% | ΔR ±0.2% | Bending amplitude 3mm for 10 seconds |
| Solderability: | 95% min. coverage | | 245 ±5°C for 3 seconds |
| Resistance to Soldering Heat: | ΔR ±0.05% | ΔR ±0.2% | 260 ±5°C for 10 seconds |
| Dielectric Withstand Voltage: | By type | | Max. overload voltage for 1 minute |
| Thermal Shock: | ΔR ±0.05% | ΔR ±0.25% | -55°C to +150°C, 100 cycles |
| Low Temperature Operation: | ΔR ±0.05% | ΔR ±0.2% | 1 hour, -65°C, followed by 45 minutes of RCWV |
| | ΔR ±0.5% for high power rating | | |

Reference Standards: MIL-STD-202, JIS-C 5201-1

Storage Temperature: 25±3°C; Humidity < 80%RH

Power Derating Curve



For resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with this curve.

Type RN73 Series

Dimensions



| Part Number | L | W | H | D | d | Weight (g) 1000 pieces |
|----------------|-------------|-------------|-------------|-------------|-------------|------------------------|
| RN73 1E (0402) | 1.00+/-0.05 | 0.50+/-0.05 | 0.30+/-0.05 | 0.20+/-0.10 | 0.20+/-0.10 | 0.54 |
| RN73 1J (0603) | 1.55+/-0.10 | 0.80+/-0.10 | 0.45+/-0.10 | 0.30+/-0.20 | 0.30+/-0.20 | 1.83 |
| RN73 2A (0805) | 2.00+/-0.15 | 1.25+/-0.15 | 0.55+/-0.10 | 0.30+/-0.20 | 0.40+/-0.25 | 4.71 |
| RN73 2B (1206) | 3.05+/-0.15 | 1.55+/-0.15 | 0.55+/-0.10 | 0.42+/-0.20 | 0.35+/-0.25 | 9.02 |
| RN73 2E (1210) | 3.10+/-0.15 | 2.40+/-0.15 | 0.55+/-0.10 | 0.40+/-0.20 | 0.55+/-0.25 | 10 |
| RN73 2H (2010) | 4.90+/-0.15 | 2.40+/-0.15 | 0.55+/-0.10 | 0.60+/-0.30 | 0.50+/-0.25 | 23.61 |
| RN73 3A (2512) | 6.30+/-0.15 | 3.10+/-0.15 | 0.55+/-0.10 | 0.60+/-0.30 | 0.50+/-0.25 | 38.08 |

Marking Codes - Case Sizes 0805 to 2512

IEC 4 Digit Marking

| | | | | | |
|---------------|------|-------|------|--------|-------|
| Resistance: | 100Ω | 2.2KΩ | 10KΩ | 49.9KΩ | 100KΩ |
| Marking Code: | 1000 | 2201 | 1002 | 4992 | 1003 |

Case Sizes 0603

E24 3 Digit Marking - Example: 101=100Ω 102=1KΩ

| | | | | | | | | | | | | |
|-----|----|----|----|----|----|----|----|----|----|----|----|----|
| E24 | 10 | 11 | 12 | 13 | 15 | 16 | 18 | 20 | 22 | 24 | 27 | 30 |
| | 33 | 36 | 39 | 43 | 47 | 51 | 56 | 62 | 68 | 75 | 82 | 91 |

E96 3 Digit Marking - Examples: 14C=13K7Ω, 13C=13K3Ω, 68B=4K99Ω, 68X=49.9Ω



0603 E96 Marking Code Table

| Code | E96 | Code | E96 | Code | E96 | Code | E96 | | | | |
|------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|------------------|------------------|
| 01 | 100 | 25 | 178 | 49 | 316 | 73 | 562 | | | | |
| 02 | 102 | 26 | 182 | 50 | 324 | 74 | 576 | | | | |
| 03 | 105 | 27 | 187 | 51 | 332 | 75 | 590 | | | | |
| 04 | 107 | 28 | 191 | 52 | 340 | 76 | 604 | | | | |
| 05 | 110 | 29 | 196 | 53 | 348 | 77 | 619 | | | | |
| 06 | 113 | 30 | 200 | 54 | 357 | 78 | 634 | | | | |
| 07 | 115 | 31 | 205 | 55 | 365 | 79 | 649 | | | | |
| 08 | 118 | 32 | 210 | 56 | 374 | 80 | 665 | | | | |
| 09 | 121 | 33 | 215 | 57 | 383 | 81 | 681 | | | | |
| 10 | 124 | 34 | 221 | 58 | 392 | 82 | 698 | | | | |
| 11 | 127 | 35 | 226 | 59 | 402 | 83 | 715 | | | | |
| 12 | 130 | 36 | 232 | 60 | 412 | 84 | 732 | | | | |
| 13 | 133 | 37 | 237 | 61 | 422 | 85 | 750 | | | | |
| 14 | 137 | 38 | 243 | 62 | 432 | 86 | 768 | | | | |
| 15 | 140 | 39 | 249 | 63 | 442 | 87 | 787 | | | | |
| 16 | 143 | 40 | 255 | 64 | 453 | 88 | 806 | | | | |
| 17 | 147 | 41 | 261 | 65 | 464 | 89 | 825 | | | | |
| 18 | 150 | 42 | 267 | 66 | 475 | 90 | 845 | | | | |
| 19 | 154 | 43 | 274 | 67 | 487 | 91 | 866 | | | | |
| 20 | 158 | 44 | 280 | 68 | 499 | 92 | 887 | | | | |
| 21 | 162 | 45 | 287 | 69 | 511 | 93 | 909 | | | | |
| 22 | 165 | 46 | 294 | 70 | 523 | 94 | 931 | | | | |
| 23 | 169 | 47 | 301 | 71 | 536 | 95 | 953 | | | | |
| 24 | 174 | 48 | 309 | 72 | 549 | 96 | 976 | | | | |
| Code | A | B | C | D | E | F | G | H | X | Y | Z |
| Multiplier | 10 ⁰ | 10 ¹ | 10 ² | 10 ³ | 10 ⁴ | 10 ⁵ | 10 ⁶ | 10 ⁷ | 10 ⁻¹ | 10 ⁻² | 10 ⁻³ |

Type RN73 Series

Recommend Land Pattern



| Type | A | B | C |
|----------------|-----|------|-----------|
| RN73 1E (0402) | 0.5 | 0.5 | 0.60 ±0.2 |
| RN73 1J (0603) | 0.8 | 1.0 | 0.90 ±0.2 |
| RN73 2A (0805) | 1.0 | 1.0 | 1.35 ±0.2 |
| RN73 2B (1206) | 2.0 | 1.15 | 1.70 ±0.2 |
| RN73 2E (1210) | 2.0 | 1.15 | 2.50 ±0.2 |
| RN73 2H (2010) | 3.6 | 1.4 | 2.50 ±0.2 |
| RN73 3A (2512) | 4.9 | 1.6 | 3.10 ±0.2 |

Packaging Quantity & Reel Specifications



| Type | øA | øB | øC | W | T | Paper Tape (EA) | Embossed Plastic Tape (EA) |
|----------------|------------|-----------|------------|-----------|-----------|--------------------|----------------------------|
| RN73 1E (0402) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0 | 11.5 ±1.0 | *250 / 1000 / 5000 | - |
| RN73 1J (0603) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0 | 11.5 ±1.0 | *250 / 1000 / 5000 | - |
| RN73 2A (0805) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0 | 11.5 ±1.0 | *250 / 1000 / 5000 | - |
| RN73 2B (1206) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0 | 11.5 ±1.0 | *250 / 1000 / 5000 | - |
| RN73 2E (1210) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 9.5 ±1.0 | 11.5 ±1.0 | *250 / 1000 / 5000 | - |
| RN73 2H (2010) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 13.5 ±1.0 | 15.5 ±1.0 | - | 4000 |
| RN73 3A (2512) | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ± 0.7 | 13.5 ±1.0 | 15.5 ±1.0 | - | 4000 |

* 250 piece packs supplied in sealed bags of cut tape length

Type RN73 Series

Paper Tape Specification



| Type | A | B | W | E | F | P ₀ | P ₁ | P ₂ | øD ₀ | T |
|----------------|------------|------------|------------|------------|-----------|----------------|----------------|----------------|-----------------|------------|
| RN73 1E (0402) | 0.70 ±0.05 | 1.16 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 2.00 ±0.05 | 1.55 ±0.05 | 0.40 ±0.03 |
| RN73 1J (0603) | 1.10 ±0.05 | 1.90 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 4.00 ±0.10 | 2.00 ±0.05 | 1.55 ±0.05 | 0.60 ±0.03 |
| RN73 2A (0805) | 1.60 ±0.05 | 2.37 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 4.00 ±0.10 | 2.00 ±0.05 | 1.55 ±0.05 | 0.75 ±0.05 |
| RN73 2B (1206) | 2.00 ±0.05 | 3.55 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 4.00 ±0.10 | 2.00 ±0.05 | 1.55 ±0.05 | 0.75 ±0.05 |
| RN73 2E (1210) | 2.75 ±0.05 | 3.40 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 1.60 ±0.10 | 0.75 ±0.05 |

Embossed Plastic Tape Specifications



| Type | A | B | W | E | F | P ₀ | P ₁ | P ₂ | øD ₀ | T |
|----------------|------------|------------|------------|------------|-----------|----------------|----------------|----------------|-----------------|------------|
| RN73 2H (2010) | 2.85 ±0.10 | 5.45 ±0.10 | 12.0 ±0.10 | 1.75 ±0.10 | 5.5 ±0.05 | 4.00 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 1.50 +0.10 | 1.00 ±0.20 |
| RN73 3A (2512) | 3.40 ±0.10 | 6.65 ±0.10 | 12.0 ±0.10 | 1.75 ±0.10 | 5.5 ±0.05 | 4.00 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 1.50 +0.10 | 1.00 ±0.20 |

How to Order

| RN73 | C | 2A | 100K | B | TDF |
|--|---|---|---|---|--|
| Common Part | Temp. Coefficient | Package Size | Resistor Value | Tolerance | Packaging |
| RN73 - High precision resistors (RoHS compliant) | A - ±5ppm/°C * C - ±10ppm/°C * Preferred stock item | 1E - 0402 * 1J - 0603 * 2A - 0805 2B - 1206 2E - 1210 2H - 2010 3A - 2512 * Preferred stock item | 100R (100 ohms) 1K0 (1000 ohms) 100K (100,000 ohms) | A - ±0.05% * B - ±0.1% L - ±0.01% * Preferred stock item | TG - 250 Cut tape length (1E, 1J, 2A, 2B) TDF - 1000 REEL (1E, 1J, 2A, 2B) TD - 5000 REEL (1E, 1J, 2A, 2B, 2E) TDG - 250 REEL (1E, 1J, 2A only) TE - 4000 REEL (2H, 3A only) |

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru