

# Type WMC Polyester Film/Foil Capacitors

## Axial Lead, Miniature Size for Automatic Insertion



Type WMC axial-leaded polyester film/foil capacitors are ideal for automatic insertion in printed circuit boards. It is an ultraminiature version of Type WMF and the sections of these non-inductive capacitors are constructed with extended foil, polyester film, with tinned copper-clad steel leads.

### Highlights

- Miniature Size
- Available on tape and reel
- Film/foil construction, non-inductive design
- High  $dV/dt$  ratings
- Good for high pulse applications


### Specifications



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

|                               |                                                                                                                                      |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>Capacitance Range:</b>     | .001 $\mu$ F to .47 $\mu$ F                                                                                                          |
| <b>Voltage Range:</b>         | 80 to 400 Vdc                                                                                                                        |
| <b>Capacitance Tolerance:</b> | $\pm 10\%$ standard, $\pm 5\%$ optional                                                                                              |
| <b>Temperature Range:</b>     | $-55$ to $+125$ $^{\circ}$ C<br>(Full-rated voltage at $85$ $^{\circ}$ C—Derate linearly to 50%-rated voltage at $125$ $^{\circ}$ C) |
| <b>Dielectric Strength:</b>   | 250% of rated voltage for 1 minute                                                                                                   |
| <b>Dissipation Factor:</b>    | .75% Max. ( $25$ $^{\circ}$ C, 1 kHz)                                                                                                |
| <b>Insulation Resistance:</b> | 30,000 $M\Omega \times \mu$ F, 100,000 $M\Omega$ Min.                                                                                |
| <b>Life Test:</b>             | 250 hours at $85$ $^{\circ}$ C at 125% rated voltage                                                                                 |

### Outline Drawing



#### Lead Diameters:

No. 24 AWG to .282" (6.35mm) diameter

No. 22 AWG .283" (6.38mm) diameter and up

NOTE: Other capacitance values, sizes and performance specifications are available. Contact us.

### Pulse Ratings

| Pulse Capability |                                          |           |           |       |       |
|------------------|------------------------------------------|-----------|-----------|-------|-------|
| Rated Voltage    | Body Length                              |           |           |       |       |
|                  | $\leq .437$                              | .531-.593 | .656-.718 | 0.906 | 1.218 |
|                  | $dV/dt$ — volts per microsecond, maximum |           |           |       |       |
| 80               | 5000                                     | 2100      | 1500      | 900   | 690   |
| 200              | 10800                                    | 5000      | 3000      | 1700  | 1260  |
| 400              | 30700                                    | 14500     | 9600      | 3600  | 2600  |

### Ratings

| Cap<br>( $\mu$ F) | Catalog<br>Part Number | D<br>Inches (mm) | L<br>Inches (mm) | d<br>Inches (mm) |
|-------------------|------------------------|------------------|------------------|------------------|
| 80 Vdc            |                        |                  |                  |                  |
| 0.0010            | WMC08D1K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0012            | WMC08D12K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0015            | WMC08D15K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0018            | WMC08D18K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0022            | WMC08D22K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0027            | WMC08D27K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |

| Cap<br>( $\mu$ F) | Catalog<br>Part Number | D<br>Inches (mm) | L<br>Inches (mm) | d<br>Inches (mm) |
|-------------------|------------------------|------------------|------------------|------------------|
| 80 Vdc            |                        |                  |                  |                  |
| 0.0033            | WMC08D33K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0039            | WMC08D39K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0047            | WMC08D47K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0056            | WMC08D56K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0068            | WMC08D68K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0082            | WMC08D82K-F            | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |

# Type WMC Polyester Film/Foil Capacitors

| Cap<br>(μF)        | Catalog<br>Part Number | D<br>Inches (mm) | L<br>Inches (mm) | d<br>Inches (mm) |
|--------------------|------------------------|------------------|------------------|------------------|
| <b>80 Vdc</b>      |                        |                  |                  |                  |
| 0.010              | WMC08S1K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.012              | WMC08S12K-F            | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.015              | WMC08S15K-F            | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.018              | WMC08S18K-F            | .185 (4.7)       | .531 (13.5)      | .020 (.5)        |
| 0.022              | WMC08S22K-F            | .185 (4.7)       | .531 (13.5)      | .020 (.5)        |
| 0.027              | WMC08S27K-F            | .229 (5.8)       | .468 (11.9)      | .020 (.5)        |
| 0.033              | WMC08S33K-F            | .229 (5.8)       | .468 (11.9)      | .020 (.5)        |
| 0.039              | WMC08S39K-F            | .229 (5.8)       | .593 (15.1)      | .020 (.5)        |
| 0.047              | WMC08S47K-F            | .229 (5.8)       | .593 (15.1)      | .020 (.5)        |
| 0.056              | WMC08S56K-F            | .250 (6.3)       | .593 (15.1)      | .020 (.5)        |
| 0.068              | WMC08S68K-F            | .250 (6.3)       | .593 (15.1)      | .020 (.5)        |
| 0.082              | WMC08S82K-F            | .343 (8.7)       | .531 (13.5)      | .024 (.6)        |
| 0.10               | WMC08P1K-F             | .343 (8.7)       | .531 (13.5)      | .024 (.6)        |
| 0.12               | WMC08P12K-F            | .343 (8.7)       | .656 (16.7)      | .024 (.6)        |
| 0.15               | WMC08P15K-F            | .343 (8.7)       | .656 (16.7)      | .024 (.6)        |
| 0.18               | WMC08P18K-F            | .382 (9.7)       | .656 (16.7)      | .024 (.6)        |
| 0.22               | WMC08P22K-F            | .382 (9.7)       | .656 (16.7)      | .024 (.6)        |
| 0.27               | WMC08P27K-F            | .382 (9.7)       | .905 (23.0)      | .024 (.6)        |
| 0.33               | WMC08P33K-F            | .382 (9.7)       | .905 (23.0)      | .024 (.6)        |
| 0.39               | WMC08P39K-F            | .382 (9.7)       | 1.218 (30.9)     | .024 (.6)        |
| 0.47               | WMC08P47K-F            | .382 (9.7)       | 1.218 (30.9)     | .024 (.6)        |
| <b>200/250 Vdc</b> |                        |                  |                  |                  |
| 0.0010             | WMC2D1K-F              | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0012             | WMC2D12K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0015             | WMC2D15K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0018             | WMC2D18K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0022             | WMC2D22K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0027             | WMC2D27K-F             | .185 (4.7)       | .406 (10.3)      | .020 (.5)        |
| 0.0033             | WMC2D33K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0039             | WMC2D39K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0047             | WMC2D47K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0056             | WMC2D56K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0068             | WMC2D68K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0082             | WMC2D82K-F             | .185 (4.7)       | .531 (13.5)      | .020 (.5)        |
| 0.010              | WMC2S1K-F              | .185 (4.7)       | .531 (13.5)      | .020 (.5)        |
| 0.012              | WMC2S12K-F             | .229 (5.8)       | .468 (11.9)      | .020 (.5)        |
| 0.015              | WMC2S15K-F             | .229 (5.8)       | .468 (11.9)      | .020 (.5)        |
| 0.018              | WMC2S18K-F             | .229 (5.8)       | .656 (16.7)      | .020 (.5)        |

| Cap<br>(μF)        | Catalog<br>Part Number | D<br>Inches (mm) | L<br>Inches (mm) | d<br>Inches (mm) |
|--------------------|------------------------|------------------|------------------|------------------|
| <b>200/250 Vdc</b> |                        |                  |                  |                  |
| 0.022              | WMC2S22K-F             | .229 (5.8)       | .656 (16.7)      | .020 (.5)        |
| 0.027              | WMC2S27K-F             | .250 (6.3)       | .656 (16.7)      | .020 (.5)        |
| 0.033              | WMC2S33K-F             | .250 (6.3)       | .656 (16.7)      | .020 (.5)        |
| 0.039              | WMC2S39K-F             | .343 (8.7)       | .531 (13.5)      | .024 (.6)        |
| 0.047              | WMC2S47K-F             | .343 (8.7)       | .531 (13.5)      | .024 (.6)        |
| 0.056              | WMC2S56K-F             | .343 (8.7)       | .656 (16.7)      | .024 (.6)        |
| 0.068              | WMC2S68K-F             | .343 (8.7)       | .656 (16.7)      | .024 (.6)        |
| 0.082              | WMC2S82K-F             | .382 (9.7)       | .656 (16.7)      | .024 (.6)        |
| 0.10               | WMC2P1K-F              | .382 (9.7)       | .656 (16.7)      | .024 (.6)        |
| 0.12               | WMC2P12K-F             | .382 (9.7)       | .906 (23.0)      | .024 (.6)        |
| 0.15               | WMC2P15K-F             | .382 (9.7)       | .906 (23.0)      | .024 (.6)        |
| 0.18               | WMC2P18K-F             | .382 (9.7)       | 1.218 (30.9)     | .024 (.6)        |
| 0.22               | WMC2P22K-F             | .382 (9.7)       | 1.218 (30.9)     | .024 (.6)        |
| <b>400 Vdc</b>     |                        |                  |                  |                  |
| 0.0010             | WMC4D1K-F              | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0012             | WMC4D12K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0015             | WMC4D15K-F             | .185 (4.7)       | .468 (11.9)      | .020 (.5)        |
| 0.0018             | WMC4D18K-F             | .185 (4.7)       | .531 (13.5)      | .020 (.5)        |
| 0.0022             | WMC4D22K-F             | .185 (4.7)       | .531 (13.5)      | .020 (.5)        |
| 0.0027             | WMC4D27K-F             | .229 (5.8)       | .531 (13.5)      | .020 (.5)        |
| 0.0033             | WMC4D33K-F             | .229 (5.8)       | .531 (13.5)      | .020 (.5)        |
| 0.0039             | WMC4D39K-F             | .229 (5.8)       | .531 (13.5)      | .020 (.5)        |
| 0.0047             | WMC4D47K-F             | .229 (5.8)       | .531 (13.5)      | .020 (.5)        |
| 0.0056             | WMC4D56K-F             | .250 (6.3)       | .656 (16.7)      | .020 (.5)        |
| 0.0068             | WMC4D68K-F             | .250 (6.3)       | .656 (16.7)      | .020 (.5)        |
| 0.0082             | WMC4D82K-F             | .250 (6.3)       | .656 (16.7)      | .020 (.5)        |
| 0.010              | WMC4S1K-F              | .250 (6.3)       | .656 (16.7)      | .020 (.5)        |
| 0.012              | WMC4S12K-F             | .343 (8.7)       | .593 (15.1)      | .024 (.6)        |
| 0.015              | WMC4S15K-F             | .343 (8.7)       | .593 (15.1)      | .024 (.6)        |
| 0.018              | WMC4S18K-F             | .343 (8.7)       | .718 (18.2)      | .024 (.6)        |
| 0.022              | WMC4S22K-F             | .343 (8.7)       | .718 (18.2)      | .024 (.6)        |
| 0.027              | WMC4S27K-F             | .382 (9.7)       | .718 (18.2)      | .024 (.6)        |
| 0.033              | WMC4S33K-F             | .382 (9.7)       | .718 (18.2)      | .024 (.6)        |
| 0.039              | WMC4S39K-F             | .382 (9.7)       | .906 (23.0)      | .024 (.6)        |
| 0.047              | WMC4S47K-F             | .382 (9.7)       | .906 (23.0)      | .024 (.6)        |
| 0.056              | WMC4S56K-F             | .382 (9.7)       | 1.218 (30.9)     | .024 (.6)        |
| 0.068              | WMC4S68K-F             | .382 (9.7)       | 1.218 (30.9)     | .024 (.6)        |

**Notice and Disclaimer:** All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)