



### Main

|                               |                                                 |
|-------------------------------|-------------------------------------------------|
| Range of product              | OsiSense XX                                     |
| Sensor type                   | Ultrasonic sensor                               |
| Series name                   | General purpose                                 |
| Sensor name                   | XX2                                             |
| Sensor design                 | Cylindrical M30                                 |
| Detection system              | Diffuse                                         |
| [Sn] nominal sensing distance | 6.56 ft (2 m) adjustable with teach push-button |
| Material                      | Plastic                                         |
| Type of output signal         | Discrete                                        |
| Discrete output function      | 2 NO                                            |
| Wiring technique              | 4-wire                                          |
| Discrete output type          | NPN                                             |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection   |
| Electrical connection         | Male connector M12 4 pins                       |
| Product specific application  | For 2 levels monitoring                         |
| [Sd] sensing range            | 0.39...6.56 ft (0.12...2 m)                     |
| Beam angle                    | 10 °                                            |
| IP degree of protection       | IP67 conforming to IEC 60529                    |

### Complementary

|                                                   |                                                                                                                                       |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Enclosure material                                | ULTEM                                                                                                                                 |
| Front material                                    | Silicone                                                                                                                              |
| Thread type                                       | M30 x 1.5                                                                                                                             |
| Supply voltage limits                             | 10...28 V DC                                                                                                                          |
| Function available                                | Without synchronisation mode                                                                                                          |
| [Sa] assured operating distance                   | 0.39...6.56 ft (0.12...2 m) (teach mode)                                                                                              |
| Maximum differential travel                       | 0.1 in (2.5 mm)                                                                                                                       |
| Blind zone                                        | 0...4.72 in (0...120 mm)                                                                                                              |
| Transmission frequency                            | 200 kHz                                                                                                                               |
| Repeat accuracy                                   | 0.9 %                                                                                                                                 |
| Deviation angle from 90° of object to be detected | -10...10 °                                                                                                                            |
| Minimum size of detected object                   | Cylinder diameter 1.6 mm at 0.635 m                                                                                                   |
| Status LED                                        | 1 LED (green/red (flashing)) output state<br>1 LED (green/red (flashing)) setting-up assistance<br>1 LED (yellow) distance indication |
| Current consumption                               | 100 mA                                                                                                                                |
| Maximum switching current                         | 100 mA with overload and short-circuit protection                                                                                     |
| Voltage drop                                      | < 1 V                                                                                                                                 |
| Delay first up                                    | 1000 ms                                                                                                                               |
| Delay response                                    | 150 ms                                                                                                                                |
| Delay recovery                                    | 1000 ms                                                                                                                               |
| Marking                                           | CE                                                                                                                                    |
| Threaded length                                   | 1.77 in (45 mm)                                                                                                                       |
| Height                                            | 1.38 in (35 mm)                                                                                                                       |
| Width                                             | 1.38 in (35 mm)                                                                                                                       |
| Depth                                             | 3.35 in (85 mm)                                                                                                                       |
| Product weight                                    | 0.2 lb(US) (0.091 kg)                                                                                                                 |

Environment

|                                       |                                                        |
|---------------------------------------|--------------------------------------------------------|
| standards                             | IEC 60947-5-2                                          |
| product certifications                | CCSAus<br>UL                                           |
| ambient air temperature for operation | 32...122 °F (0...50 °C)                                |
| ambient air temperature for storage   | 14...176 °F (-10...80 °C)                              |
| vibration resistance                  | +/-1 mm conforming to IEC 60068-2-6 10...55 Hz         |
| shock resistance                      | 30 gn in all 3 axes 11 ms conforming to IEC 60068-2-27 |
| resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2               |
| resistance to electromagnetic fields  | 9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3 |
| resistance to fast transients         | 1 kV level 3 conforming to IEC 61000-4-4               |


Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                  | Not Green Premium product                                                                                                  |
| Compliant - since 0836 - Schneider Electric declaration of conformity                                                      | Compliant - since 0836 - Schneider Electric declaration of conformity                                                      |
| Reference contains SVHC above the threshold - go to CaP for more details                                                   | Reference contains SVHC above the threshold                                                                                |
| Available                                                                                                                  | Available                                                                                                                  |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

Contractual warranty


|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Dimensions




Minimum Mounting Distances

Side by side



e : respect the distances indicated on the detection curves


Face to face



e > 4 x Sn


Wiring Diagram

NO + NO outputs, NPN




- (1) (+) Brown
  - (2) NO output (White)
  - (3) (-) Blue
  - (4) NO output (Black)
- BN** Brown  
**WH** White  
**BU** Blue  
**BK** Black

## Curves



- (1) Parallel movement
- (2) Distance
- (3) Blind zone for diffuse sensors.

## Operating Curves



- (1) Adjustable detection zone
- (2) Output pin 4 BK
- (3) Output pin 2 WH

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)