

12 GHZ HAND FORMABLE .086 COAX CABLES

50 Ohm DC-12 GHz Hand Formable Coaxial Cables

Roffs

Features:

Center Conductor: Silver-plated copper clad steel wire

Outer Braid: Tin-soaked copper braid, 100% coverage
Insulation: PTFE (Polytetrafluoroethylene) dielectric


Cable Outer Dia.:0.086" (2.2mm)Connectors:Gold plated brassCenter Pin:Gold plated brassOperating Temperature:-40°C to +85°C

Minimum Bend Radius: 0.24" (6mm) single bend

0.99" (25mm) multiple bends

Electrically Matched Pairs Available

PN: CCSMA-MM-086-3 INSERTION LOSS



Electrical Specifications:

Impedance: 50 Ohms
Frequency: DC to 12 GHz

Insertion Loss: <0.82 dB/ft at 12 GHz VSWR: <1.3, DC to 12 GHz

Nominal Capacitance: 28.6 pF/ft Velocity of Propagation: 70% RF Shielding: <-130 dB

*connector loss not included (refer to actual cable plot (see below))

*connector loss not included (refer to actual cable plot (see below))

0.30 Typ. at 2 GHz
0.46 Typ. at 4 GHz
0.70 Typ. at 8 GHz
0.76 Typ. at 10 GHz
0.82 Typ. at 12 GHz

 Avg. Power in (Watts):
 900 @ 100 MHz

 *as specified at 40°C
 200 @ 1 GHz

 50 @ 10 GHz

50 @ 10 GHz

Applications: Jumpers
Instrume
High Fre

Instrumentation
High Frequency Interconnects

SMA/SMA[Straight/Straight]

Part Number	Description	Length
CCSMA-MM-086-3	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	3"
CCSMA-MM-086-4	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	4"
CCSMA-MM-086-5	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	5"
CCSMA-MM-086-6	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	6"
CCSMA-MM-086-7	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	7"
CCSMA-MM-086-8	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	8"
CCSMA-MM-086-10	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	10"
CCSMA-MM-086-12	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	12"
CCSMA-MM-086-18	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	18"
CCSMA-MM-086-24	.086 Hand Formable Coax Cable, SMA Male/Male, Straight/Straight	24"





OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru