

# Ceramic Resonators (CERALOCK®)

Ceramic resonators (CERALOCK®) are made of high stability piezoelectric ceramics that function as a mechanical resonator. At present, CERALOCK® find a broad range of applications such as automotive electronics, communications, personal computing, and medical/healthcare equipment.



« Search Conditions »

cstn(Starting with ...)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE10M0G520000R0<br><small>Under development</small>                        | 10.000MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE10M0G52A000R0<br><small>Under development</small>                        | 10.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE10M0G52Z000R0<br><small>Under development</small>                        | 10.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE10M0G550000R0<br><small>In Production</small> <small>Recommended</small> | 10.000MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE10M0G55A000R0<br><small>In Production</small> <small>Recommended</small> | 10.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE10M0G55Z000R0<br><small>In Production</small> <small>Recommended</small> | 10.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |

**Attention**

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE10M0GH5C000R0<br><span>In Production</span> <span>Recommended</span> | 10.000MHz | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE10M0GH5L000R0<br><span>In Production</span> <span>Recommended</span> | 10.000MHz | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE11M0G520000R0<br><span>Under development</span>                      | 11.000MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE11M2G550000R0<br><span>In Production</span> <span>Recommended</span> | 11.289MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M0G520000R0<br><span>Under development</span>                      | 12.000MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M0G52A000R0<br><span>Under development</span>                      | 12.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE12M0G52Z000R0<br><span>Under development</span>                      | 12.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE12M0G550000R0<br><span>In Production</span> <span>Recommended</span> | 12.000MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M0G55A000R0<br><span>In Production</span> <span>Recommended</span> | 12.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE12M0G55Z000R0<br><span>In Production</span> <span>Recommended</span> | 12.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE12M0GH5C000R0<br><span>In Production</span> <span>Recommended</span> | 12.000MHz | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE12M0GH5L000R0<br><span>In Production</span> <span>Recommended</span> | 12.000MHz | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M2G520000R0<br><span>Under development</span>                      | 12.288MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M2G550000R0<br><span>In Production</span> <span>Recommended</span> | 12.288MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M2G55A000R0<br><span>In Production</span> <span>Recommended</span> | 12.288MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |

**Attention**

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE12M2GH5L000R0<br><small>In Production</small> <small>Recommended</small> | 12.288MHz | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M5G520000R0<br><small>Under development</small>                        | 12.500MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M5G550000R0<br><small>In Production</small> <small>Recommended</small> | 12.500MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE12M5G55A000R0<br><small>In Production</small> <small>Recommended</small> | 12.500MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE12M5G55Z000R0<br><small>In Production</small> <small>Recommended</small> | 12.500MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE13M0G520000R0<br><small>Under development</small>                        | 13.000MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE13M0G55A000R0<br><small>In Production</small> <small>Recommended</small> | 13.000MHz | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE13M5G520000R0<br><small>Under development</small>                        | 13.500MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE13M5G550000R0<br><small>In Production</small> <small>Recommended</small> | 13.500MHz | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE14M0V510000R0<br><small>Under development</small>                        | 14.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE14M0V530000R0<br><small>In Production</small> <small>Recommended</small> | 14.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE14M0V53C000R0<br><small>In Production</small> <small>Recommended</small> | 14.000MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE14M3V530000R0<br><small>In Production</small> <small>Recommended</small> | 14.318MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE14M7V510000R0<br><small>Under development</small>                        | 14.746MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE14M7V530000R0<br><small>In Production</small> <small>Recommended</small> | 14.746MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |

**Attention**

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE14M7V53C000R0<br><span>In Production</span> <span>Recommended</span> | 14.746MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE15M0V530000R0<br><span>In Production</span> <span>Recommended</span> | 15.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE15M0V53C000R0<br><span>In Production</span> <span>Recommended</span> | 15.000MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE16M0V510000R0<br><span>Under development</span>                      | 16.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M0V51C000R0<br><span>Under development</span>                      | 16.000MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE16M0V51Z000R0<br><span>Under development</span>                      | 16.000MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE16M0V530000R0<br><span>In Production</span> <span>Recommended</span> | 16.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M0V53C000R0<br><span>In Production</span> <span>Recommended</span> | 16.000MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE16M0V53Z000R0<br><span>In Production</span> <span>Recommended</span> | 16.000MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE16M0VH3C000R0<br><span>In Production</span> <span>Recommended</span> | 16.000MHz | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE16M0VH3L000R0<br><span>In Production</span> <span>Recommended</span> | 16.000MHz | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M3V530000R0<br><span>In Production</span> <span>Recommended</span> | 16.384MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M5V530000R0<br><span>In Production</span> <span>Recommended</span> | 16.500MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M6V530000R0<br><span>In Production</span> <span>Recommended</span> | 16.670MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M6V53C000R0<br><span>In Production</span> <span>Recommended</span> | 16.670MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |

**Attention**

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE16M6V53Z000R0<br><span>In Production</span> <span>Recommended</span> | 16.670MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE16M8V530000R0<br><span>In Production</span> <span>Recommended</span> | 16.800MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M9V530000R0<br><span>In Production</span> <span>Recommended</span> | 16.934MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE16M9V53C000R0<br><span>In Production</span> <span>Recommended</span> | 16.934MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE16M9V53Z000R0<br><span>In Production</span> <span>Recommended</span> | 16.934MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE17M0V530000R0<br><span>In Production</span> <span>Recommended</span> | 17.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE17M2V530000R0<br><span>In Production</span> <span>Recommended</span> | 17.200MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE18M0V510000R0<br><span>Under development</span>                      | 18.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE18M0V530000R0<br><span>In Production</span> <span>Recommended</span> | 18.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE18M0VH3C000R0<br><span>In Production</span> <span>Recommended</span> | 18.000MHz | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE18M4V530000R0<br><span>In Production</span> <span>Recommended</span> | 18.432MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE18M4V53C000R0<br><span>In Production</span> <span>Recommended</span> | 18.432MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE18M4V53Z000R0<br><span>In Production</span> <span>Recommended</span> | 18.432MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE18M7V530000R0<br><span>In Production</span> <span>Recommended</span> | 18.750MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE19M2V530000R0<br><span>In Production</span> <span>Recommended</span> | 19.200MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |

### Attention

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE19M2VH3L000R0<br><span>In Production</span> <span>Recommended</span> | 19.200MHz | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE19M6V510000R0<br><span>Under development</span>                      | 19.660MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE19M6V530000R0<br><span>In Production</span> <span>Recommended</span> | 19.660MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE19M8V530000R0<br><span>In Production</span> <span>Recommended</span> | 19.800MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE20M0V510000R0<br><span>Under development</span>                      | 20.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE20M0V51C000R0<br><span>Under development</span>                      | 20.000MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE20M0V51Z000R0<br><span>Under development</span>                      | 20.000MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE20M0V530000R0<br><span>In Production</span> <span>Recommended</span> | 20.000MHz | ±0.50%              | ±0.30%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE20M0V53C000R0<br><span>In Production</span> <span>Recommended</span> | 20.000MHz | ±0.50%              | ±0.15%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE20M0V53Z000R0<br><span>In Production</span> <span>Recommended</span> | 20.000MHz | ±0.50%              | ±0.30%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE20M0VH3C000R0<br><span>In Production</span> <span>Recommended</span> | 20.000MHz | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE20M0VH3L000R0<br><span>In Production</span> <span>Recommended</span> | 20.000MHz | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M00G520000R0<br><span>Under development</span>                      | 8.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M00G52A000R0<br><span>Under development</span>                      | 8.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE8M00G52Z000R0<br><span>Under development</span>                      | 8.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |

### Attention

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number   | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|---|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE8M00G55000R0<br><span>In Production</span> <span>Recommended</span>  | 8.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M00G55A000R0<br><span>In Production</span> <span>Recommended</span> | 8.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE8M00G55Z000R0<br><span>In Production</span> <span>Recommended</span> | 8.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Consumer/Industrial | SMD   |
| CSTNE8M00GH5C000R0<br><span>In Production</span> <span>Recommended</span> | 8.000MHz  | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE8M00GH5L000R0<br><span>In Production</span> <span>Recommended</span> | 8.000MHz  | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M19G55000R0<br><span>In Production</span> <span>Recommended</span>  | 8.192MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M38G52000R0<br><span>Under development</span>                       | 8.388MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M38G52A000R0<br><span>Under development</span>                      | 8.388MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE8M38G55000R0<br><span>In Production</span> <span>Recommended</span>  | 8.388MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE8M38G55A000R0<br><span>In Production</span> <span>Recommended</span> | 8.388MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNE8M50G55000R0<br><span>In Production</span> <span>Recommended</span>  | 8.500MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE9M00G52000R0<br><span>Under development</span>                       | 9.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE9M00G55000R0<br><span>In Production</span> <span>Recommended</span>  | 9.000MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE9M21G52000R0<br><span>Under development</span>                       | 9.210MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE9M60GH5L000R0<br><span>In Production</span> <span>Recommended</span> | 9.600MHz  | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |

### Attention

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# Ceramic Resonators (CERALOCK®)

| Part Number  | Frequency | Frequency Tolerance | Frequency Shift by Temperature | Operating Temperature Range | Other Applications  | Shape |
|--|-----------|---------------------|--------------------------------|-----------------------------|---------------------|-------|
| CSTNE9M83G52000R0<br><small>Under development</small>          | 9.830MHz  | ±0.50%              | ±0.20%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE9M83GH5L000R0<br><small>In Production Recommended</small> | 9.830MHz  | ±0.07%              | ±0.11%                         | -40°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNE9M84G52A000R0<br><small>Under development</small>         | 9.843MHz  | ±0.50%              | ±0.20%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNR4M00GH5C000R0<br><small>In Production Recommended</small> | 4.000MHz  | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNR4M00GH5L000R0<br><small>In Production Recommended</small> | 4.000MHz  | ±0.07%              | ±0.11%                         | -20°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNR4M91GH5L000R0<br><small>In Production Recommended</small> | 4.915MHz  | ±0.07%              | ±0.11%                         | -20°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNR5M00GH5C000R0<br><small>In Production Recommended</small> | 5.000MHz  | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNR5M00GH5L000R0<br><small>In Production Recommended</small> | 5.000MHz  | ±0.07%              | ±0.11%                         | -20°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNR6M00GH5C000R0<br><small>In Production Recommended</small> | 6.000MHz  | ±0.07%              | ±0.13%                         | -40°C to 125°C              | Automotive          | SMD   |
| CSTNR6M00GH5L000R0<br><small>In Production Recommended</small> | 6.000MHz  | ±0.07%              | ±0.11%                         | -20°C to 85°C               | Consumer/Industrial | SMD   |
| CSTNR7M37GH5L000R0<br><small>In Production Recommended</small> | 7.370MHz  | ±0.07%              | ±0.11%                         | -20°C to 85°C               | Consumer/Industrial | SMD   |

**Attention**

1. This catalog is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)