

THIS DRAWING IS UNPUBLISHED.







RELEASED FOR PUBLICATION

© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DWDIST
—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	ECR-12-012115	26OCT12	EL	WK



RECOMMENDED PCB LAYOUT (THICKNESS: 1.6mm)
DIMENSION TOLERANCE: 1 PLC: ±0.1 2PLC: ±0.05

NOTE:

- MATERIAL:
HOUSING: PA46 WITH 30% GF, UL94 V-0, BLACK COLOR.
CONTACTS: PHOSPHOR BRONZE.
SHIELD: BRASS.
- FINISH:
CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA, GOLD FLASH ON SOLDER TAIL, WITH ENTIRE CONTACT UNDERPLATED 1.27μm [50μ"] MIN. NICKEL.
SHIELD: 0.51μm [20μ"] MIN. NICKEL PLATED.
- WAVE SOLDER CAPABLE TO 265°C PER 109-202, CONDITION B.

4. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	6P2C	REEL	1.27μm [50μ"]	2-1734723-8
			0.762μm [30μ"]	2-1734723-7
			0.381μm [15μ"]	2-1734723-6
			0.152μm [6μ"]	2-1734723-5
OBSOLETE	6P2C	TRAY	1.27μm [50μ"]	2-1734723-4
			0.762μm [30μ"]	2-1734723-3
			0.381μm [15μ"]	2-1734723-2
			0.152μm [6μ"]	2-1734723-1
OBSOLETE	6P6C	REEL	1.27μm [50μ"]	1734723-8
			0.762μm [30μ"]	1734723-7
			0.381μm [15μ"]	1734723-6
			0.152μm [6μ"]	1734723-5
OBSOLETE	6P6C	TRAY	1.27μm [50μ"]	1734723-4
			0.762μm [30μ"]	1734723-3
			0.381μm [15μ"]	1734723-2
			0.152μm [6μ"]	1734723-1
	RJ11	PACKAGE	MIN. GOLD THICKNESS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	A. WU	10MAR2008
CHK	S. HOU	10MAR2008
APVD	W. KODAMA	10MAR2008
PRODUCT SPEC	108-57527	
APPLICATION SPEC	—	
WEIGHT	3 GRAMS	
CUSTOMER DRAWING		



TE Connectivity

MODULAR JACK, RJ11,
SINGLE, DIP TYPE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	—	1734723	—
SCALE	—	SHEET 1 OF 5	REV A2

THIS DRAWING IS UNPUBLISHED.







RELEASED FOR PUBLICATION

© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DWDIST
—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			




RECOMMENDED PCB LAYOUT (THICKNESS: 1.6mm)
DIMENSION TOLERANCE: 1 PLC: ±0.1 2PLC: ±0.05

NOTE:

- MATERIAL:
HOUSING: PA46 WITH 30% GF, UL94 V-0, BLACK COLOR.
CONTACTS: PHOSPHOR BRONZE.
SHIELD: BRASS.
- FINISH:
CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA, GOLD FLASH ON SOLDER TAIL, WITH ENTIRE CONTACT UNDERPLATED 1.27μm [50μ"] MIN. NICKEL.
- WAVE SOLDER CAPABLE TO 265°C PER 109-202, CONDITION B.

4. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	6P6C	REEL	1.27μm [50μ"]	1-1734723-8
			0.762μm [30μ"]	1-1734723-7
			0.381μm [15μ"]	1-1734723-6
			0.152μm [6μ"]	1-1734723-5
OBSOLETE	6P6C	TRAY	1.27μm [50μ"]	1-1734723-4
			0.762μm [30μ"]	1-1734723-3
			0.381μm [15μ"]	1-1734723-2
			0.152μm [6μ"]	1-1734723-1
	RJ11	PACKAGE	MIN. GOLD THICKNESS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. WU 10MAR2008	 TE Connectivity	
DIMENSIONS: MM		CHK S. HOU 10MAR2008		
		APVD W. KODAMA 10MAR2008		
		PRODUCT SPEC 108-57527		
MATERIAL SEE NOTE		APPLICATION SPEC —	NAME MODULAR JACK, RJ11, SINGLE, DIP TYPE	
FINISH SEE NOTE		WEIGHT 2.5 GRAMS	SIZE A3	RESTRICTED TO —
		CUSTOMER DRAWING	SCALE —	SHEET 2 OF 5
			REV A2	

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION



COPYRIGHT

BY TYCO ELECTRONICS CORPORATION.

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

DW

—

P

LTR




DESCRIPTION

DATE




DWN

APVD

SEE SHEET 1.



LOGO

RECOMMENDED PCB LAYOUT (THICKNESS: 1.6mm)
DIMENSION TOLERANCE: 1 PLC: ±0.1 2PLC: ±0.05

NOTE:

- MATERIAL:
HOUSING: PA46 WITH 30% GF, UL94 V-0, BLACK COLOR.
CONTACTS: PHOSPHOR BRONZE.
SHIELD: BRASS.
- FINISH:
CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA, GOLD FLASH ON SOLDER TAIL, WITH ENTIRE CONTACT UNDERPLATED 1.27μm [50μ"] MIN. NICKEL.
SHIELD: 0.51μm [20μ"] MIN. NICKEL PLATED.
- WAVE SOLDER CAPABLE TO 265°C PER TE TEST SPEC. 109-202, CONDITION B.

OBSOLETE	6P2C	REEL	1.27μm [50μ"]	4-1734723-8
			0.762μm [30μ"]	4-1734723-7
			0.381μm [15μ"]	4-1734723-6
			0.152μm [6μ"]	4-1734723-5
OBSOLETE		TRAY	1.27μm [50μ"]	4-1734723-4
			0.762μm [30μ"]	4-1734723-3
			0.381μm [15μ"]	4-1734723-2
			0.152μm [6μ"]	4-1734723-1
	RJ11	PACKAGE	MIN. GOLD THICKNESS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN A. WU 10MAR2008

CHK S. HOU 10MAR2008

APVD W. KODAMA 10MAR2008

PRODUCT SPEC

108-57527

APPLICATION SPEC

—

WEIGHT 3 GRAMS

CUSTOMER DRAWING



TE Connectivity

NAME

MODULAR JACK, RJ11,
SINGLE, DIP TYPE


SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 — C=1734723 —

SCALE — SHEET 3 OF 5 REV A2

DIMENSIONS:

MM



MATERIAL

SEE NOTE

TOLERANCES UNLESS

OTHERWISE SPECIFIED:

0 PLC	± 0.50
1 PLC	± 0.30
2 PLC	± 0.20
3 PLC	± 0.10
4 PLC	± 0.10
ANGLES	± —

FINISH

SEE NOTE


4

3

2

1

LOC	DIST	REVISIONS					
DW	—	P	LTR	DESCRIPTION	DATE	DWN	APVD
				SEE SHEET 1.			



13.2 Kg	3960	120	1734723-1
GROSS WEIGHT	TOTAL	PCS/TRAY	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. WU 10MAR2008	TE Connectivity	
DIMENSIONS: MM		CHK S. HOU 10MAR2008		
		APVD W. KODAMA 10MAR2008		
		PRODUCT SPEC		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	NAME MODULAR JACK, RJ11, SINGLE, DIP TYPE	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		WEIGHT		
MATERIAL		FINISH	SIZE A3	CAGE CODE -
			DRAWING NO C=1734723	RESTRICTED TO -
CUSTOMER DRAWING			SCALE -	SHEET 4 of 5
			REV A2	

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-,-

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DWDIST
—

REVISIONS

P

LTR


DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1.



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN A. WU 10MAR2008

CHK S. HOU 10MAR2008

APVD W. KODAMA 10MAR2008

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

STE

TE Connectivity

MODULAR JACK, RJ11,
SINGLE, DIP TYPE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

—

C=1734723

—

SCALE

SHEET

5 of 5

REV

A2

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru