

# Cree® PLCC6 3 in 1 SMD LED CLX6F-PKW



#### **PRODUCT DESCRIPTION**

These SMD LEDs are packaged in an industry standard PLCC6 package. These high reliability and high brightness LEDs are designed to work in a wide range of environmental condition and are ideally suited for use in illumination applications.

Its wide viewing angle makes these LEDs ideally suited for channel letter, or general backlighting and illumination applications. The flat top emitting surface makes it easy for these LEDs to mate with light pipes.

#### **FEATURES**

- Size (mm):3.5 x 3.4 x 2.8
- Luminous Intensity (mcd)
  PC Amber (6300-11300)
- Moisture Sensitivity Level: 5a
- Lead-Free
- RoHS Compliant

#### **APPLICATIONS**

- Architecture Lighting
- Channel Letter
- Backlight



# ABSOLUTE MAXIMUM RATINGS $(T_A = 25^{\circ}C)$

Items	Symbol	Absolute Maximum Rating Uni	
Forward Current Note 1	$I_{_{\rm F}}$	3 x 70	mA
Peak Forward Current Note 2	$I_{\sf FP}$	3 x 200	mA
Reverse Voltage	$V_R$	5	V
Power Dissipation	P <sub>D</sub>	3 x 280	mW
Operation Temperature	$T_{opr}$	-40 ~ +85	°C
Storage Temperature	$T_{stg}$	-40 ~ +100	°C
Junction Temperature	T,	110	°C
Junction/ambient 1 chip on	R <sub>THJA</sub>	220	°C/W
Junction/solder point 1 chip on	R <sub>THJS</sub>	140	°C/W
Electrostatic Discharge Classification(MIL-STD-883E)	ESD	1000 V	

**Note:** 1. Single-color light.

2. Pulse width  $\leq 0.1$  msec, duty  $\leq 1/10$ .

# TYPICAL ELECTRICAL & OPTICAL CHARACTERISTICS $(T_A = 25^{\circ}C)$

Characteristics	Condition	Symbol	Values	Unit
Spectral bandwidth at 50% $I_{\text{REL}}$ max	$I_F = 3 \times 35 \text{ mA}$	Δλ	81	nm
Forward Voltage	$I_F = 3 \times 35 \text{ mA}$	$V_{F(avg)}$	3.3	V
		$V_{F(max)}$	4.0	V
Luminous Intensity	$I_F = 3 \times 35 \text{ mA}$	$I_{V(min)}$	6300	mcd
		$I_{V(avg)}$	9000	mcd
Luminous Flux(Reference)	$I_{F} = 3 \times 35 \text{ mA}$	$\Phi_{V(avg)}$	23	lm
Reverse Current (max)	$V_R = 5 V$	$I_R$	10	μΑ

Note: Continuous reverse voltage can cause LED damage.



## INTENSITY BIN LIMIT ( $I_F = 3 \times 35 \text{ mA}$ )

PC Amber

Bin Code	Min.(mcd)	Max.(mcd)	
1k1m	6300	8000	
Χ	7100	9000	
1n1p	8000	10100	
Υ	9000	11300	

ullet Tolerance of measurement of luminous intensity is  $\pm 10\%$ .


## COLOR BIN LIMIT ( $I_F = 3 \times 35 \text{ mA}$ )

PC Amber

Bin Code	x	у
V0	0.5622	0.4372
	0.5843	0.4152
	0.5705	0.4111
	0.5499	0.4249

• Tolerance of measurement of the color coordinates is  $\pm 0.02$ .

#### **CIE CHROMATICITY DIAGRAM**





#### **ORDER CODE TABLE\***

Kit Number	Color	Luminous Intensity (mcd)		Dominant Wavelength (nm)	Package
			Max.		
CLX6F-PKW-C1k1mYV0V03	PC Amber	6300	11300	V0	Reel

#### Notes:


- 1. The above kit numbers represent the order codes which include multiple intensity-bin and color-bin codes. Only one intensity-bin code and one color-bin code will be shipped on each reel. Single intensity-bin code and single color-bin code will be orderable in certain quantities. For example, intensity bin from 1k1m Y means intensity bin from (1k1m or X or 1n1p or Y) will be shipped by Cree.
- 2. Please refer to the "Cree LED Lamp Reliability Test Standards" document #1 for reliability test conditions.
- 3. Please refer to the "Cree LED Lamp Soldering & Handling" document #2 for information about how to use this LED product safely.


<sup>#1:</sup> Refer to http://www.cree.com/led-components/media/documents/LED\_Lamp\_Reliability\_Test\_Standard.pdf


<sup>#2:</sup> Refer to http://www.cree.com/led-components/media/documents/sh-HB.pdf



#### **GRAPHS**












#### **GRAPHS**








The above data are collected from statistical figures that do not necessarily correspond to the actual parameters of each single LED. Hence, these data will be changed without further notice.



#### **MECHANICAL DIMENSIONS**

All dimensions are in mm.



#### **NOTES**

#### RoHS Compliance

The levels of environmentally sensitive, persistent biologically toxic (PBT), persistent organic pollutants (POP), or otherwise restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS), as amended through April 21, 2006.

#### Vision Advisory Claim


Users should be cautioned not to stare at the light of this LED product. The bright light can damage the eye.



#### KIT NUMBER SYSTEM

Cree LED lamps are tested and sorted into performance bins. A bin is specified by ranges of color, forward voltage, and brightness. Sorted LEDs are packaged for shipping in various convenient options. Please refer to the "Cree LED Lamp Packaging Standard" document for more information about shipping and packaging options.


Cree LEDs are sold by order codes in combinations of bins called kits. Order codes are configured in the following manner:





#### **REFLOW SOLDERING**

- The CLX6F-PKW is rated as a MSL 5a product.
- The recommended floor life out of bag is 24hrs.
- The temperature profile is as below.



#### Use only with CLX6F-PKW


Solder
Average ramp-up rate = 4°C/s max
Preheat temperature = 150°C ~200°C
Preheat time = 120s max
Ramp-down rate = 6°C/s max
Peak temperature = 250°C max
Time within 5°C of actual Peak Temperature = 10s max
Duration above 217°C is 60s max

 $Refer\ to\ "http://www.cree.com/led-components/media/documents/sh-HB.pdf"\ for\ soldering\ \&\ handling\ details.$ 



### **NOTES**


- The packaging sizes of these SMD products are very small and the resin is still soft after solidification. Users are required to handle with care. Never touch the resin surface of SMD products.
- To avoid damaging the product's surface and interior device, it is recommended to choose a special nozzle to pick up the SMD products during the process of SMT production. If handling is necessary, take special care when picking up these products. The following method is necessary:





#### **PACKAGING**

- The boxes are not water resistant and they must be kept away from water and moisture.
- The LEDs are packed in cardboard boxes after packaging in normal or anti-electrostatic bags.
- Cardboard boxes will be used to protect the LEDs from mechanical shocks during transportation.
- The reel pack is applied in SMD LED.
- Max 2800 pcs per reel.





OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

#### Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru