74LVT244A-Q100; 74LVTH244A-Q100

3.3 V octal buffer/line driver; 3-state

Rev. 1 — 22 April 2013

Product data sheet

1. General description

The 74LVT244A-Q100; 74LVTH244A-Q100 is a high-performance BiCMOS product designed for V_{CC} operation at 3.3 V.

This device is an $\underline{\text{octal buffer}}$ that is ideal for driving bus lines. The device features two output enables $(1\overline{\text{OE}}, 2\overline{\text{OE}})$, each controlling four of the 3-state outputs.

This product has been qualified to the Automotive Electronics Council (AEC) standard Q100 (Grade 3) and is suitable for use in automotive applications.

2. Features and benefits

- Automotive product qualification in accordance with AEC-Q100 (Grade 3)
 - ◆ Specified from -40 °C to +85 °C
- Octal bus interface
- 3-state buffers
- Output capability: +64 mA and -32 mA
- TTL input and output switching levels
- Input and output interface capability to systems at 5 V supply
- Bus hold data inputs eliminate need for external pull-up resistors to hold unused inputs
- Live insertion and extraction permitted
- Power-up 3-state
- No bus current loading when output is tied to 5 V bus
- Latch-up protection
 - ◆ JESD78 Class II exceeds 500 mA
- ESD protection:
 - MIL-STD-883, method 3015 exceeds 2000 V
 - ◆ HBM JESD22-A114F exceeds 2000 V
 - ♦ MM JESD22-A115-A exceeds 200 V (C = 200 pF, R = 0 Ω)




3. Ordering information

Table 1. Ordering information


Type number	Package								
	Temperature range	Name	Description	Version					
74LVT244AD-Q100	–40 °C to +85 °C	SO20	plastic small outline package; 20 leads;	SOT163-1					
74LVTH244AD-Q100			body width 7.5 mm						
74LVT244APW-Q100	–40 °C to +85 °C	TSSOP20	plastic thin shrink small outline package;	SOT360-1					
74LVTH244APW-Q100			20 leads; body width 4.4 mm						
74LVT244ABQ-Q100	–40 °C to +85 °C	DHVQFN20	plastic dual in-line compatible thermal enhanced	SOT764-1					
74LVTH244ABQ-Q100			very thin quad flat package; no leads; 20 terminals; body $2.5 \times 4.5 \times 0.85$ mm						

4. Functional diagram



5. Pinning information

5.1 Pinning



5.2 Pin description

Table 2. Pin description

Symbol	Pin	Description
1 OE , 2 OE	1, 19	output enable input (active low)
1A0, 1A1, 1A2, 1A3	2, 4, 6, 8	data input
2Y0, 2Y1, 2Y2, 2Y3	9, 7, 5, 3	data output
GND	10	ground (0 V)
2A0, 2A1, 2A2, 2A3	11, 13, 15, 17	data input
1Y0, 1Y1, 1Y2, 1Y3,	18, 16, 14, 12	data output
V _{CC}	20	supply voltage

6. Functional description

6.1 Function table

Table 3. Function table [1]

Control	Input	Output
nOE	nAn	nYn
L	L	L
	Н	Н
Н	X	Z

^[1] H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

7. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

		0, 1, ,		10	,
Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		-0.5	+4.6	V
V _I	input voltage		[<u>1]</u> -0.5	+7.0	V
V _O	output voltage	output in OFF-state or HIGH-state	<u>[1]</u> –0.5	+7.0	V
I _{IK}	input clamping current	V _I < 0 V	-	-50	mA
I _{OK}	output clamping current	V _O < 0 V	-	-50	mA
Io	output current	output in LOW-state	-	128	mA
		output in HIGH-state	-	-64	mA
T _{stg}	storage temperature		–65	+150	°C
Tj	junction temperature		[2] _	150	°C
P _{tot}	total power dissipation	$T_{amb} = -40 \text{ to } +85 ^{\circ}\text{C}$	[3]	500	mW

^[1] The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.

8. Recommended operating conditions

Table 5. Operating conditions

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
V_{CC}	supply voltage		2.7	-	3.6	V
V_{I}	input voltage		0	-	5.5	V
I _{OH}	HIGH-level output current		-	-	-32	mA

74LVT_LVTH244A_Q100

^[2] The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.

^[3] For SO20 package: above 70 °C derate linearly with 8 mW/K.
For TSSOP20 package: above 60 °C derate linearly with 5.5 mW/K.
For DHVQFN20 package: above 60 °C derate linearly with 4.5 mW/K.

 Table 5.
 Operating conditions ...continued

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
I_{OL}	LOW-level output current	none	-	-	32	mA
		current duty cycle \leq 50 %; $f_i \geq$ 1 kHz	-	-	64	mA
T _{amb}	ambient temperature	in free-air	-40	-	+85	°C
Δt/ΔV	input transition rise and fall rate	outputs enabled	-	-	10	ns/V

9. Static characteristics

Table 6. Static characteristics

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
T _{amb} = -	40 °C to +85 °C [1]					
V_{IK}	input clamping voltage	$V_{CC} = 2.7 \text{ V}; I_{IK} = -18 \text{ mA}$	-1.2	-0.9	-	V
V_{IH}	HIGH-level input voltage		2.0	-	-	V
V_{IL}	LOW-level input voltage		-	-	0.8	V
V_{OH}	HIGH-level output voltage	V_{CC} = 2.7 V to 3.6 V; I_{OH} = $-100~\mu A$	$V_{CC}-0.2$	$V_{CC}-0.1$	-	V
		V_{CC} = 2.7 V to 3.6 V; I_{OH} = -8 mA	2.4	2.5	-	V
		$V_{CC} = 3.0 \text{ V}; I_{OH} = -32 \text{ mA}$	2.0	2.2	-	V
V_{OL}	LOW-level output voltage	V_{CC} = 2.7 V; I_{OL} = 100 μA	-	0.1	0.2	V
		$V_{CC} = 2.7 \text{ V}; I_{OL} = 24 \text{ mA}$	-	0.3	0.5	V
		$V_{CC} = 3.0 \text{ V}; I_{OL} = 16 \text{ mA}$	-	0.25	0.4	V
		$V_{CC} = 3.0 \text{ V}; I_{OL} = 32 \text{ mA}$	-	0.3	0.5	V
		$V_{CC} = 3.0 \text{ V}; I_{OL} = 64 \text{ mA}$	-	0.4	0.55	V
I _I	input leakage current	all input pins				
		$V_{CC} = 0 \text{ V or } 3.6 \text{ V}; V_I = 5.5 \text{ V}$	-	0.1	10	μΑ
		control pins				
		$V_{CC} = 3.6 \text{ V}; V_I = V_{CC} \text{ or GND}$	-	±0.1	±1	μΑ
		data pins	[2]			
		$V_{CC} = 3.6 \text{ V}; V_I = V_{CC}$	-	0.1	1	μΑ
		$V_{CC} = 3.6 \text{ V}; V_I = 0 \text{ V}$	– 5	-1	_	μΑ
I _{OFF}	power-off leakage current	$V_{CC} = 0 \text{ V}$; $V_I \text{ or } V_O = 0 \text{ V to } 4.5 \text{ V}$	-	1	±100	μΑ
I _{BHL}	bus hold LOW current	$V_{CC} = 3 \text{ V}; V_{I} = 0.8 \text{ V}$	[<u>3]</u> 75	150	-	μΑ
I _{BHH}	bus hold HIGH current	$V_{CC} = 3 \text{ V}; V_{I} = 2.0 \text{ V}$	_	-150	-75	μΑ
I _{BHLO}	bus hold LOW overdrive current	nAn input; $V_{CC} = 0 \text{ V to } 3.6 \text{ V}; V_I = 3.6 \text{ V}$	500	-	-	μΑ
I _{BHHO}	bus hold HIGH overdrive current	nAn input; $V_{CC} = 0 \text{ V to } 3.6 \text{ V}; V_I = 3.6 \text{ V}$	-	-	-500	μА
I _{LO}	output leakage current	nYn output in HIGH-state when $V_O > V_{CC}$; $V_O = 5.5$ V; $V_{CC} = 3.0$ V	-	60	125	μА
I _{O(pu/pd)}	power-up/power-down output current	$V_{CC} \le 1.2 \text{ V}; V_O = 0.5 \text{ V} \text{ to } V_{CC};$ $V_I = \text{GND or } V_{CC}; \text{ nOE} = \text{don't care}$	<u>[4]</u> _	±1	±100	μА

Table 6. Static characteristics ... continued

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions		Min	Тур	Max	Unit
I_{OZ}	OFF-state output current	V_{CC} = 3.6 V; V_I = V_{IH} or V_{IL}					
		$V_{O} = 3.0 \text{ V}$		-	1	5	μΑ
		$V_{O} = 0.5 \text{ V}$		-5	-1	-	μΑ
I _{CC}	supply current	V_{CC} = 3.6 V; V_I = GND or V_{CC} ; I_O = 0 A					
		output HIGH		-	0.13	0.19	mΑ
		output LOW		-	3	12	mΑ
		outputs disabled	<u>[5]</u>	-	0.13	0.19	mΑ
ΔI_{CC}	additional supply current	per input pin; V_{CC} = 3.0 V to 3.6 V; one input at V_{CC} – 0.6 V and other inputs at V_{CC} or GND	<u>[6]</u>	-	0.1	0.2	mA
C _I	input capacitance	$V_I = 0 \text{ V or } 3.0 \text{ V}$		-	4	-	pF
Co	output capacitance	outputs disabled; $V_0 = 0 \text{ V or } 3.0 \text{ V}$		-	8	-	pF

^[1] All typical values are at $T_{amb} = 25$ °C.

10. Dynamic characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 7.

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
$T_{amb} = -40$	°C to +85 °C [1]					
t _{PLH}	LOW to HIGH	nAn to nYn; see Figure 5				
	propagation delay	V _{CC} = 2.7 V	-	-	5.0	ns
		V _{CC} = 3.0 V to 3.6 V	1	2.5	4.1	ns
t _{PHL}	HIGH to LOW	nAn to nYn; see Figure 5				
	propagation delay	V _{CC} = 2.7 V	-	-	5.1	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	1	2.6	4.1	ns
t _{PZH}	OFF-state to HIGH propagation delay	see Figure 6				
		V _{CC} = 2.7 V	-	-	6.3	ns
		V _{CC} = 3.0 V to 3.6 V	1	3.2	5.2	ns
t _{PZL}	OFF-state to LOW	see Figure 6				
	propagation delay	V _{CC} = 2.7 V	-	-	6.7	ns
		V _{CC} = 3.0 V to 3.6 V	1.1	3.1	5.2	ns
t _{PHZ}	HIGH to OFF-state	see Figure 6				
	propagation delay	V _{CC} = 2.7 V	-	-	6.3	ns
		V _{CC} = 3.0 V to 3.6 V	1.9	3.3	5.6	ns
74LVT_LVTH244A_Q100		All information provided in this document is subject to	legal disclaimers.	6	Nexperia B.V. 2017	7. All rights reserv

^[2] Unused pins at V_{CC} or GND.

^[3] This is the bus hold overdrive current required to force the input to the opposite logic state.

^[4] This parameter is valid for any V_{CC} between 0 V and 1.2 V with a transition time of up to 10 ms. From V_{CC} = 1.2 V to V_{CC} = 3.3 V \pm 0.3 V a transition time of 100 μ s is permitted. This parameter is valid for T_{amb} = 25 °C only.

^[5] I_{CC} is measured with outputs pulled to V_{CC} or GND.

^[6] This is the increase in supply current for each input at the specified voltage level other than V_{CC} or GND.


 Table 7.
 Dynamic characteristics ...continued

Voltages are referenced to GND (ground = 0 V); for test circuit see Figure 7.

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
t _{PLZ}	LOW to OFF-state propagation delay	see Figure 6				
		V _{CC} = 2.7 V	-	-	5.6	ns
		V _{CC} = 3.0 V to 3.6 V	1.8	3.3	5.1	ns

^[1] All typical values are at $V_{CC} = 3.3 \text{ V}$ and $T_{amb} = 25 \,^{\circ}\text{C}$.


11. Waveforms



Measurement points are given in Table 8.

 $\ensuremath{V_{OL}}$ and $\ensuremath{V_{OH}}$ are typical voltage output levels that occur with the output load.

Fig 5. Propagation delay input (nAn) to output (nYn) propagation delays



Measurement points are given in Table 8.


 V_{OL} and V_{OH} are typical voltage output levels that occur with the output load.

Fig 6. 3-state output enable and disable times

Table 8. Measurement points

Input	Output		
V_{M}	V _M	V _X	V _Y
1.5 V	1.5 V	V _{OL} + 0.3 V	$V_{OH} - 0.3 V$

74LVT_LVTH244A_Q100



Test data is given in Table 9.

Definitions test circuit:

R_L = Load resistance.

 C_L = Load capacitance including jig and probe capacitance.

 R_T = Termination resistance should be equal to output impedance Z_o of the pulse generator.

 V_{EXT} = Test voltage for switching times.

Fig 7. Test circuit for measuring switching times


Table 9. Test data

Input			Load		V _{EXT}			
		CL	R_L	t _{PHZ} , t _{PZH}	t_{PLZ} , t_{PZL}	t _{PLH} , t _{PHL}		
2.7 V	\leq 10 MHz	500 ns	≤ 2.5 ns	50 pF	500Ω	GND	6 V	open

12. Package outline

SO20: plastic small outline package; 20 leads; body width 7.5 mm

SOT163-1



Note

1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.

OUTLINE	REFERENCES				EUROPEAN	ICCUE DATE
VERSION	IEC	JEDEC	JEITA		PROJECTION	ISSUE DATE
SOT163-1	075E04	MS-013				99-12-27 03-02-19

Fig 8. Package outline SOT163-1 (SO20)


74LVT_LVTH244A_Q100

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserve

TSSOP20: plastic thin shrink small outline package; 20 leads; body width 4.4 mm

SOT360-1



- 1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
- 2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.

OUTLINE	REFERENCES			EUROPEAN	IOOUE DATE	
VERSION	IEC	JEDEC	JEITA		PROJECTION	ISSUE DATE
SOT360-1		MO-153				99-12-27 03-02-19

Fig 9. Package outline SOT360-1 (TSSOP20)

74LVT_LVTH244A_Q100

All information provided in this document is subject to legal disclaimers.

Nexperia B.V. 2017. All rights reserved

DHVQFN20: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 20 terminals; body 2.5 x 4.5 x 0.85 mm SOT764-1




Fig 10. Package outline SOT764-1 (DHVQFN20)

74LVT_LVTH244A_Q100

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

13. Abbreviations

Table 10. Abbreviations

Acronym	Description
BiCMOS	Blpolar Complementary Metal Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
НВМ	Human Body Model
MM	Machine Model
MIL	Military
TTL	Transistor-Transistor Logic

14. Revision history

Table 11. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
74LVT_LVTH244A_Q100 v.1	20130422	Product data sheet	-	-

15. Legal information

15.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions"
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

15.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

15.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use in automotive applications — This Nexperia product has been qualified for use in automotive applications. Unless otherwise agreed in writing, the product is not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

74LVT_LVTH244A_Q100

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

16. Contact information

For more information, please visit: http://www.nexperia.com

For sales office addresses, please send an email to: salesaddresses@nexperia.com

74LVT244A-Q100; 74LVTH244A-Q100

Nexperia

3.3 V octal buffer/line driver; 3-state

17. Contents

1	General description
2	Features and benefits
3	Ordering information
4	Functional diagram 2
5	Pinning information
5.1	Pinning
5.2	Pin description
6	Functional description 4
6.1	Function table 4
7	Limiting values 4
8	Recommended operating conditions 4
9	Static characteristics 5
10	Dynamic characteristics 6
11	Waveforms
12	Package outline 9
13	Abbreviations
14	Revision history
15	Legal information
15.1	Data sheet status
15.2	Definitions
15.3	Disclaimers
15.4	Trademarks14
16	Contact information 14
17	Contents 15



OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru