


## AX103267 Faceplates and Panels - FiberExpress Ultra Rack-mount 4U Patch Panel, 19



For more Information  
please call

1-800-Belden1

**General Description:**

FiberExpress Ultra Rack-mount 4U Patch Panel, 19", Black.

**Usage (Overall)**

|                               |                                                                                                 |
|-------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Suitable Applications:</b> | FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers |
| <b>Related Parts:</b>         | FiberExpress Ultra Frames, Cassettes, Bezels                                                    |

**Physical Characteristics (Connectivity)****Capacity**

|                       |                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>Max. Capacity:</b> | 12 Frames; 144 Fibers (SC, SCD, ST, FC); 288 Fibers (LCD, MT-RJ). Eight 8-inch FiberExpress Ultra splice tray kits (AX103912) |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------|

**Access**

|                          |                 |
|--------------------------|-----------------|
| <b>Front Connection:</b> | 1 inch Pullout  |
| <b>Termination Area:</b> | Front Swing Out |

**Dimensions**

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 7.000        | 19.000      | 20.900      |

**Materials**

Materials:

| Description | Material |
|-------------|----------|
| Panel       | Steel    |
| Door        | Lexan    |

**Color**

|               |       |
|---------------|-------|
| <b>Color:</b> | Black |
|---------------|-------|

**Weight**

|                |             |
|----------------|-------------|
| <b>Weight:</b> | 34.300 lbs. |
|----------------|-------------|

**Included Parts**

|                        |                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <b>Included Parts:</b> | 4 Screws (10x32); 4 Screws (12x24); 20 Tie Wraps; 4 Radius Controller; 12 Kurly Locks; 2 Velcro Straps; Identification Label |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|

**Packaging**

|                   |                                           |
|-------------------|-------------------------------------------|
| <b>Packaging:</b> | Individually packaged in a cardboard box. |
|-------------------|-------------------------------------------|

**Mechanical Characteristics (Connectivity)**

|                                     |                |
|-------------------------------------|----------------|
| <b>Storage Temperature Range:</b>   | -40°C To +70°C |
| <b>Operating Temperature Range:</b> | -10°C To +60°C |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                              |            |
|----------------------------------------------|------------|
| <b>EU Directive 2002/95/EC (RoHS):</b>       | Yes        |
| <b>EU RoHS Compliance Date (mm/dd/yyyy):</b> | 03/03/2008 |
| <b>MIL Order #39 (China RoHS):</b>           | EUP 50     |

**Suitability**

|                              |     |
|------------------------------|-----|
| <b>Suitability - Indoor:</b> | Yes |
|------------------------------|-----|

**Transmission Characteristics (Connectivity)****Notes (Overall)**

**Notes:** For more information, please refer to the following New Product Bulletins: NP284 Rack- & Wall-mount Patch Panels. For proper installation refer to Installation Guide PX104709 included with the product or visit our web site at <http://www.belden.com>

AX103267 Faceplates and Panels - FiberExpress Ultra Rack-mount 4U Patch Panel, 19

Product Family

Part Numbers:

| Description                                | Item Number |
|--------------------------------------------|-------------|
| FiberExpress Ultra Rack Mount PP 1U, Black | AX103143    |
| FiberExpress Ultra Rack Mount PP 4U, Black | AX103267    |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0    Revision Date: 05-31-2009

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)