



Precision, Low-Voltage Analog Switches

General Description

The MAX381/MAX383/MAX385 are precision, low-voltage analog switches. The single-pole single-throw MAX381 and double-pole single-throw MAX385 dual switches are normally open. The single-pole double-throw MAX383 has two normally open and two normally closed poles. All three parts offer low on-resistance (less than 35Ω), guaranteed to match to within 2Ω between channels and to remain flat over the specified analog signal range (4Ω max). They also offer low leakage (less than 250pA at $+25^\circ\text{C}$ and less than 2.5nA at $+85^\circ\text{C}$) and fast switching (turn-on time less than 175ns and turn-off time less than 100ns).

The MAX381/MAX383/MAX385 are fabricated with Maxim's low-voltage silicon-gate process for high system accuracy. Design improvements guarantee extremely low charge injection ($<5\text{pC}$) and low power consumption ($<10\mu\text{W}$).

These monolithic switches operate with a single positive supply ($+3\text{V}$ to $+15\text{V}$) or with split supplies ($\pm 3\text{V}$ to $\pm 8\text{V}$) while retaining CMOS-logic input compatibility and fast switching. CMOS inputs provide reduced input loading.

Applications

Sample-and-Hold Circuits	Military Radios
Test Equipment	Communication Systems
Heads-Up Displays	Battery-Operated Systems
Audio Signal Routing	PBX, PABX
Guidance and Control Systems	

Features

- ♦ Single-Supply Operation ($+3\text{V}$ to $+15\text{V}$)
Bipolar-Supply Operation ($\pm 3\text{V}$ to $\pm 8\text{V}$)
- ♦ Pin-Compatible with DG401/DG403/DG405
- ♦ Low On-Resistance, 20Ω Typical (35Ω Max)
- ♦ Guaranteed Matched On-Resistance Between Channels, $<2\Omega$
- ♦ Guaranteed Flat On-Resistance over Specified Analog Signal Range, $<4\Omega$
- ♦ Guaranteed Charge Injection, $<5\text{pC}$
- ♦ Guaranteed Off-Channel Leakage, $<2.5\text{nA}$ at $+85^\circ\text{C}$
- ♦ TTL/CMOS-Logic Compatible with 3V , 5V , $\pm 3\text{V}$, and $\pm 5\text{V}$ Supplies
- ♦ Rail-to-Rail Analog Signal Handling Capability

Ordering Information


PART	TEMP. RANGE	PIN-PACKAGE
MAX381CPE	0°C to $+70^\circ\text{C}$	16 Plastic DIP
MAX381CSE	0°C to $+70^\circ\text{C}$	16 Narrow SO
MAX381C/D	0°C to $+70^\circ\text{C}$	Dice*
MAX381EPE	-40°C to $+85^\circ\text{C}$	16 Plastic DIP
MAX381ESE	-40°C to $+85^\circ\text{C}$	16 Narrow SO
MAX381EJE	-40°C to $+85^\circ\text{C}$	16 CERDIP**
MAX381MJE	-55°C to $+125^\circ\text{C}$	16 CERDIP**

Ordering Information continued on last page.

* Dice are tested at $T_A = +25^\circ\text{C}$ only.

** Contact factory for package availability.

Pin Configurations/Block Diagrams/Truth Tables



Precision, Low-Voltage Analog Switches

ABSOLUTE MAXIMUM RATINGS

Voltage Referenced to GND

V+-0.3V to +17V

V-+0.3V to -17V

V+ to V--0.3V to +17V

COM_, NO_, NC_, IN_(V- - 2V) to (V+ + 2V) or 30mA,
whichever occurs first

Continuous Current, any pin30mA

Peak Current, any pin
(pulsed at 1ms, 10% duty cycle max)100mA

Continuous Power Dissipation (T_A = +70°C)

Plastic DIP (derate 10.53mW/°C above +70°C)842mW

Narrow SO (derate 8.70mW/°C above +70°C)696mW

CERDIP (derate 10.00mW/°C above +70°C)800mW

Operating Temperature Ranges

MAX38_C_E0°C to +70°C

MAX38_E_E-40°C to +85°C

MAX38_MJE-55°C to +125°C

Storage Temperature Range-65°C to +150°C

Lead Temperature (soldering, 10sec)+300°C

Note 1: Signals on NC, NO, COM, or IN exceeding V+ or V- are clamped by internal diodes. Limit forward diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—Dual Supplies

(V+ = +5V ±10%, V- = -5V ±10%, GND = 0V, V_{INH} = 2.4V, V_{INL} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP. RANGE	MIN	TYP (Note 2)	MAX	UNITS
SWITCH							
Analog Signal Range	V _{COM} , V _{NO} , V _{NC}	(Note 3)		V-		V+	V
On-Resistance	R _{ON}	V+ = 4.5V, V- = -4.5V, V _{NC} or V _{NO} = ±3.5V, I _{COM} = -10mA, V _{INH} = 2.4V, V _{INL} = 0.8V	T _A = +25°C	C, E	20	35	Ω
				M	20	30	
			T _A = T _{MIN} to T _{MAX}	C, E, M		45	
On-Resistance Match Between Channels (Note 4)	ΔR _{ON}	V _{NC} or V _{NO} = ±3V, I _{COM} = -10mA, V+ = 5V, V- = -5V	T _A = +25°C	C, E, M	0.5	2	Ω
			T _A = T _{MIN} to T _{MAX}	C, E, M		4	
On-Resistance Flatness (Note 4)	R _{FLAT(ON)}	V _{NC} or V _{NO} = 3V, 0V, -3V; I _{COM} = -10mA, V+ = 5V, V- = -5V	T _A = +25°C	C, E, M		4	Ω
			T _A = T _{MIN} to T _{MAX}	C, E, M		6	
NC or NO Off Leakage Current (Note 5)	I _{NC(OFF)} or I _{NO(OFF)}	V _{COM} = ±4.5V, V _{NC} or V _{NO} = ∓4.5V, V+ = 5.5V, V- = -5.5V	T _A = +25°C	C, E	-0.2	-0.01	nA
				M	-0.1	-0.01	
			T _A = T _{MIN} to T _{MAX}	C, E	-2.5		
				M	-5.0		
COM Off Leakage Current (Note 5)	I _{COM(OFF)}	V _{COM} = ±4.5V, V _{NC} or V _{NO} = ∓4.5V, V+ = 5.5V, V- = -5.5V	T _A = +25°C	C, E	-0.2	-0.01	nA
				M	-0.1	-0.01	
			T _A = T _{MIN} to T _{MAX}	C, E	-2.5		
				M	-5.0		
COM On Leakage Current (Note 5)	I _{COM(ON)}	V _{COM} = ±4.5V, V _{NC} or V _{NO} = ±4.5V, V+ = 5.5V, V- = -5.5V	T _A = +25°C	C, E	-0.4	-0.04	nA
				M	-0.2	-0.04	
			T _A = T _{MIN} to T _{MAX}	C, E	-5.0		
				M	-20.0		

Precision, Low-Voltage Analog Switches

MAX381/MAX383/MAX385

ELECTRICAL CHARACTERISTICS—Dual Supplies (continued)

(V+ = +5V ±10%, V- = -5V ±10%, GND = 0V, VINH = 2.4V, VINL = 0.8V, TA = TMIN to TMAX, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP (Note 2)	MAX	UNITS	
DIGITAL LOGIC INPUT								
Input Current with Input Voltage High	I _{INH}	V _{IN} = 2.4V, all others = 0.8V		-1.0	0.005	1.0	μA	
Input Current with Input Voltage Low	I _{INL}	V _{IN} = 0.8V, all others = 2.4V		-1.0	0.005	1.0	μA	
Logic High Input Voltage	V _{AH}		T _A = T _{MIN} to T _{MAX}	2.4			V	
Logic Low Input Voltage	V _{AL}		T _A = T _{MIN} to T _{MAX}			0.8	V	
DYNAMIC								
Turn-On Time	t _{ON}	V _{COM} = 3V, Figure 2	T _A = +25°C	100		175	ns	
			T _A = T _{MIN} to T _{MAX}	225				
Turn-Off Time	t _{OFF}	V _{COM} = 3V, Figure 2	T _A = +25°C	60		100	ns	
			T _A = T _{MIN} to T _{MAX}	150				
Break-Before-Make Time Delay (Note 3)	t _D	MAX383 only, Figure 3	T _A = +25°C	10		20	ns	
Charge Injection (Note 3)	V _{CTE}	C _L = 1.0nF, V _{GEN} = 0V, R _{GEN} = 0Ω, Figure 4	T _A = +25°C			2	5	pC
Off Isolation (Note 6)	V _{ISO}	R _L = 100Ω, C _L = 5pF, f = 1MHz, Figure 5	T _A = +25°C			72		dB
Crosstalk (Note 7)	V _{CT}	R _L = 50Ω, C _L = 5pF, f = 1MHz, Figure 6	T _A = +25°C			90		dB
Off Capacitance	C _{OFF}	f = 1MHz, Figure 7	T _A = +25°C			12		pF
COM Off Capacitance	C _{COM(OFF)}	f = 1MHz, Figure 7	T _A = +25°C			12		pF
Channel On Capacitance	C _{COM(ON)}	f = 1MHz, Figure 8	T _A = +25°C			39		pF
SUPPLY								
Power-Supply Range				±3			±8	V
Positive Supply Current	I ⁺	All channels on or off, V ⁺ = 5.5V, V ⁻ = -5.5V, V _{IN} = 0V or V ⁺		-1.0	0.06	1.0		μA
Negative Supply Current	I ⁻	All channels on or off, V ⁺ = 5.5V, V ⁻ = -5.5V, V _{IN} = 0V or V ⁺		-1.0	-0.01	1.0		μA

Note 2: The algebraic convention, where the most negative value is a minimum and the most positive value a maximum, is used in this data sheet.

Note 3: Guaranteed by design.

Note 4: $\Delta R_{ON} = \Delta R_{ON(max)} - \Delta R_{ON(min)}$. On-resistance match between channels and flatness are guaranteed only with specified voltages. Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured over the specified analog signal range.

Note 5: Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at room temperature.

Note 6: See Figure 4. Off isolation = $20\log_{10} V_{COM}/V_{NC}$ or V_{NO} . VCOM = output, VNC or NO = input to off switch.

Note 7: Between any two switches. See Figure 5.

Note 8: Leakage testing at single supply is guaranteed by testing with dual supplies.

Precision, Low-Voltage Analog Switches

ELECTRICAL CHARACTERISTICS—Single +5V Supply

(V+ = +5V ±10%, V- = 0V, GND = 0V, VINH = 2.4V, VINL = 0.8V, TA = TMIN to TMAX, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		TEMP. RANGE	MIN	TYP (Note 2)	MAX	UNITS	
SWITCH									
Analog Signal Range	V _{COM} , V _{NO} , V _{NC}	(Note 3)			0V		V+	V	
On-Resistance	R _{ON}	V+ = 5.0V, V- = 0V, V _{NC} or V _{NO} = 3.5V, I _{COM} = 1.0mA, V _{INH} = 2.4V, V _{INL} = 0.8V	T _A = +25°C	C, E	25		65	Ω	
				M		60			
			T _A = T _{MIN} to T _{MAX}	C, E, M		75			
On-Resistance Match Between Channels (Note 4)	ΔR _{ON}	V _{NC} or V _{NO} = 3V, I _{COM} = 1.0mA, V+ = 5V	T _A = +25°C	C, E, M	0.5		2	Ω	
			T _A = T _{MIN} to T _{MAX}	C, E, M		4			
On-Resistance Flatness (Note 4)	R _{FLAT(ON)}	V _{NC} or V _{NO} = 3V, 2V, 1V; I _{COM} = 1.0mA; V+ = 5V; V- = 0V	T _A = +25°C	C, E, M			6	Ω	
			T _A = T _{MIN} to T _{MAX}	C, E, M		8			
NC or NO Off Leakage Current (Note 8)	I _{NC(OFF)} or I _{NO(OFF)}	V _{COM} = 0V, V _{NC} or V _{NO} = 4.5V, V+ = 5.5V, V- = 0V	T _A = +25°C	C, E	-0.2	-0.01	0.2	nA	
				M	-0.1	-0.01	0.1		
				T _A = T _{MIN} to T _{MAX}	C, E	-2.5			2.5
				M	-5.0		5.0		
COM Off Leakage Current (Note 8)	I _{COM(OFF)}	V _{COM} = 4.5V, V _{NC} or V _{NO} = 0V, V+ = 5.5V, V- = 0V	T _A = +25°C	C, E	-0.2	-0.01	0.2	nA	
				M	-0.1	-0.01	0.1		
				T _A = T _{MIN} to T _{MAX}	C, E	-2.5			2.5
				M	-5.0		5.0		
COM On Leakage Current (Note 8)	I _{COM(ON)}	V _{COM} = 4.5V, V _{NC} or V _{NO} = 4.5V, V+ = 5.5V, V- = 0V	T _A = +25°C	C, E	-0.4	-0.04	0.4	nA	
				M	-0.2	-0.04	0.2		
				T _A = T _{MIN} to T _{MAX}	C, E	-5.0			5.0
				M	-20.0		20.0		
DIGITAL LOGIC INPUT									
Input Current with Input Voltage High	I _{INH}	V _{IN} = 2.4V, all others = 0.8V			-1.0	0.005	1.0	μA	
Input Current with Input Voltage Low	I _{INL}	V _{IN} = 0.8V, all others = 2.4V			-1.0	0.005	1.0	μA	

Precision, Low-Voltage Analog Switches

MAX381/MAX383/MAX385

ELECTRICAL CHARACTERISTICS—Single +5V Supply (continued)

(V+ = +5V ±10%, V- = 0V, GND = 0V, VINH = 2.4V, VINL = 0.8V, TA = TMIN to TMAX, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP (Note 2)	MAX	UNITS
DYNAMIC						
Turn-On Time	tON	VCOM = 3V, Figure 2	TA = +25°C	160	250	ns
			TA = TMIN to TMAX		300	
Turn-Off Time	tOFF	VCOM = 3V, Figure 2	TA = +25°C	60	125	ns
			TA = TMIN to TMAX		175	
Break-Before-Make Time Delay (Note 3)	tD	MAX383 only	TA = +25°C	10	20	ns
Charge Injection (Note 3)	VCTE	CL = 1.0nF, VGEN = 0V, RGEN = 0Ω	TA = +25°C	2	5	pC
SUPPLY						
Power-Supply Range	V+		2.7		16	V
Positive Supply Current	I+	All channels on or off, VIN = 0V or V+, V+ = 5.5V, V- = 0V	-1.0	0.01	1.0	μA
Negative Supply Current	I-	All channels on or off, VIN = 0V or V+, V+ = 5.5V, V- = 0V	-1.0	-0.01	1.0	μA

ELECTRICAL CHARACTERISTICS—Single +3.3V Supply

(V+ = 3.0V to 3.6V, GND = 0V, VINH = 2.4V, VINL = 0.8V, TA = TMIN to TMAX, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP. RANGE	MIN	TYP (Note 2)	MAX	UNITS
SWITCH							
Analog Signal Range	VCOM, VNO, VNC	(Note 3)		0V		V+	V
On-Resistance	RON	V+ = 3V, V- = 0V, VNC or VNO = 1.5V, ICOM = 1.0mA, VINH = 2.4V, VINL = 0.8V	TA = +25°C	C, E	75	185	Ω
				M		175	
NC or NO Off Leakage Current (Note 8)	INC(OFF) or INO(OFF)	VCOM = 0V, VNC or VNO = 3V, V+ = 3.6V, V- = 0V	TA = +25°C	C, E	-0.2	-0.01	nA
				M	-0.1	-0.01	
			TA = TMIN to TMAX	C, E	-2.5		
				M	-5.0	5.0	
COM Off Leakage Current (Note 8)	ICOM(OFF)	VCOM = 3V, VNC or VNO = 0V, V+ = 3.6V, V- = 0V	TA = +25°C	C, E	-0.2	-0.01	nA
				M	-0.1	-0.01	
			TA = TMIN to TMAX	C, E	-2.5		
				M	-5.0	5.0	
COM On Leakage Current (Note 8)	ICOM(ON)	VCOM = 3V, VNC or VNO = 3V, V+ = 3.6V, V- = 0V	TA = +25°C	C, E	-0.4	-0.04	nA
				M	-0.2	-0.04	
			TA = TMIN to TMAX	C, E	-5.0		
				M	-20.0	20.0	

Precision, Low-Voltage Analog Switches




ELECTRICAL CHARACTERISTICS—Single +3.3V Supply (continued)

($V^+ = 3.0\text{V}$ to 3.6V , $\text{GND} = 0\text{V}$, $V_{\text{INH}} = 2.4\text{V}$, $V_{\text{INL}} = 0.8\text{V}$, $T_A = T_{\text{MIN}}$ to T_{MAX} , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP (Note 2)	MAX	UNITS
DIGITAL LOGIC INPUT						
Input Current with Input Voltage High	I_{INH}	$V_{\text{IN}} = 2.4\text{V}$, all others = 0.8V	-1.0	0.005	1.0	μA
Input Current with Input Voltage Low	I_{INL}	$V_{\text{IN}} = 0.8\text{V}$, all others = 2.4V	-1.0	0.005	1.0	μA
DYNAMIC						
Turn-On Time (Note 3)	t_{ON}	$V_{\text{COM}} = 1.5\text{V}$, Figure 2 $T_A = +25^\circ\text{C}$			400	ns
Turn-Off Time (Note 3)	t_{OFF}	$V_{\text{COM}} = 1.5\text{V}$, Figure 2 $T_A = +25^\circ\text{C}$			150	ns
Break-Before-Make Time Delay (Note 3)	t_{D}	MAX383 only $T_A = +25^\circ\text{C}$	10	20		ns
Charge Injection (Note 3)	V_{CTE}	$C_L = 1.0\text{nF}$, $V_{\text{GEN}} = 0\text{V}$, $R_{\text{GEN}} = 0\Omega$ $T_A = +25^\circ\text{C}$		1	5	pC
SUPPLY						
Power-Supply Range	V^+		2.7		16	V
Positive Supply Current	I^+	All channels on or off, $V_{\text{IN}} = 0\text{V}$ or V^+ , $V^+ = 3.6\text{V}$, $V^- = 0\text{V}$	-1.0	0.01	1.0	μA
Negative Supply Current	I^-	All channels on or off, $V_{\text{IN}} = 0\text{V}$ or V^+ , $V^+ = 3.6\text{V}$, $V^- = 0\text{V}$	-1.0	-0.01	1.0	μA

Typical Operating Characteristics








($T_A = +25^\circ\text{C}$, unless otherwise noted.)



Precision, Low-Voltage Analog Switches

Typical Operating Characteristics (continued)

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



MAX381/MAX383/MAX385

Precision, Low-Voltage Analog Switches

Pin Description

PIN			NAME	FUNCTION
MAX381	MAX383	MAX385		
1, 8	1, 3, 6, 8	1, 3, 6, 8	COM_	Analog Switch Common Terminal
2–7, 12	2, 7, 12	2, 7, 12	N.C.	Not Internally Connected
9, 16	9, 16	4, 5, 9, 16	NO_	Analog Switch Normally Open Terminal
—	4, 5	—	NC_	Analog Switch Normally Closed Terminal
10, 15	10, 15	10, 15	IN_*	Logic Level Input (Normally Low)
11	11	11	V+	Analog Signal and Logic Positive Supply Input
13	13	13	GND	Logic Negative Supply Input (Ground)
14	14	14	V-	Analog Signal Negative Supply Input

* IN1 controls COM1 and COM3; IN2 controls COM2 and COM4.

Applications Information

Operation with Supply Voltages Other than $\pm 5V$

The MAX381/MAX383/MAX385 switches operate with $\pm 3.0V$ to $\pm 8V$ bipolar supplies and a $+3V$ to $+15V$ single supply. In either case, analog signals ranging from $V+$ to $V-$ can be switched. The *Typical Operating Characteristics* graphs show the typical on-resistance variation with analog signal and supply voltage. The usual on-resistance temperature coefficient is $0.5\%/^{\circ}C$ (typ).

Overvoltage Protection

Proper power-supply sequencing is recommended for all CMOS devices. Do not exceed the absolute maximum ratings, because stresses beyond the listed ratings can cause permanent damage to the devices. Always sequence $V+$ on first, then $V-$, followed by the logic inputs, NO, or COM. If power-supply sequencing is not possible, add two small signal diodes ($D1$, $D2$) in series with supply pins for overvoltage protection (Figure 1). Adding diodes reduces the analog signal range to one diode drop below $V+$ and one diode drop above $V-$, but does not affect the devices' low switch resistance and low leakage characteristics. Device operation is unchanged, and the difference between $V+$ and $V-$ should not exceed $17V$. These protection diodes are not recommended when using a single $3V$ supply.




Figure 1. Overvoltage Protection Using Two External Blocking Diodes

Precision, Low-Voltage Analog Switches

Test Circuits/Timing Diagrams




Figure 2. Switching-Time Test Circuit




Figure 3. Break-Before-Make Test Circuit (MAX383 only)




Figure 4. Charge-Injection Test Circuit

Precision, Low-Voltage Analog Switches

Test Circuits/Timing Diagrams (continued)




Figure 5. Off Isolation




Figure 6. Crosstalk Test Circuit




Figure 7. Channel-Off Capacitance




Figure 8. Channel-On Capacitance

Precision, Low-Voltage Analog Switches


Ordering Information (continued)

PART	TEMP. RANGE	PIN-PACKAGE
MAX383CPE	0°C to +70°C	16 Plastic DIP
MAX383CSE	0°C to +70°C	16 Narrow SO
MAX383C/D	0°C to +70°C	Dice*
MAX383EPE	-40°C to +85°C	16 Plastic DIP
MAX383ESE	-40°C to +85°C	16 Narrow SO
MAX383EJE	-40°C to +85°C	16 CERDIP**
MAX383MJE	-55°C to +125°C	16 CERDIP**
MAX385CPE	0°C to +70°C	16 Plastic DIP
MAX385CSE	0°C to +70°C	16 Narrow SO
MAX385C/D	0°C to +70°C	Dice*
MAX385EPE	-40°C to +85°C	16 Plastic DIP
MAX385ESE	-40°C to +85°C	16 Narrow SO
MAX385EJE	-40°C to +85°C	16 CERDIP**
MAX385MJE	-55°C to +125°C	16 CERDIP**

* Dice are tested at $T_A = +25^\circ\text{C}$ only.

** Contact factory for package availability.

Chip Topography





MAX381/MAX383/MAX385

TRANSISTOR COUNT: 57
SUBSTRATE CONNECTED TO V+

Precision, Low-Voltage Analog Switches

Package Information



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru