

› Plug-In Timer 8 pins

- › Multifunction or monofunction
- › Compact body for space saving
- › Wide time range (from 0.5 seconds to 10 days delay)
- › Universal power supply (12-240 V \sim)
- › 1 or 2 relay outputs (SPDT / Changeover)
- › Protective cover
- › LED status indicator
- › 3-wire PNP sensor compatible
- › 8-pins connections



OU1R10MV1
Multifunction U -
Monofunction Ad - N



OA2R10MV1
Monofunction A



OC1R10MV1
Monofunction C



OL1R10MV1
Monofunction L - Li

| Product selection | | | |
|---|----------|--------------------|------------------|
| Function | Output | Supply Voltage | Part Number |
| Multifunction U: (A, At, B, C, H, Ht, D, Di, Ac, Bw) Ad - N | 1 relay | 12 to 240 V \sim | OU1R10MV1 |
| A | 2 relays | 12 to 240 V \sim | OA2R10MV1 |
| C | 1 relay | 12 to 240 V \sim | OC1R10MV1 |
| L - Li | 1 relay | 12 to 240 V \sim | OL1R10MV1 |

PART NUMBERING SYSTEM

Type

- O:** Plug-in 8-Pins
- P:** Plug-in 11-Pins

Output Quantity

- 1:** 1 Output
- 2:** 2 Outputs

Output Power

- 10:** 10 A

O

A

1

R

10

MV1

Function

- A:** ON-Delay
- C:** OFF-Delay
- L:** Repeat Cycle
- U:** Multifunction U

Output Type

- R:** Relay

Power Supply

- MV1:** 12-240V AC/DC

You have a project? Contact us on www.crouzet.com

Description:

Syr-line, the new specialized range at Crouzet, aimed to satisfy the most unique requirements of your applications by innovating in design, engineering and development.

The Plug in Analog Timers, a new family of 8 timers with multifunction or monofunction, universal power supply, wide time range, with all the classic functions.

For more information about Crouzet's Syr-line range, please visit www.crouzet.com.

| | OU1R10MV1 | OA2R10MV1 | OC1R10MV1 | OL1R10MV1 |
|---|--|--|--|-----------|
| Power Supply | | | | |
| Rated supply voltage Un | 12 to 240 V \sim | | | |
| Voltage supply tolerance | -15 %, +10 % | | | |
| AC supply voltage frequency | 50 / 60 Hz \pm 5% | | | |
| Galvanic isolation of supply / inputs | No | | | |
| Power consumption @ Un | Approx. 3 VA (VAC) 1.5 W (VDC) | | | |
| Immunity to power micro cuts | 10 ms | | | |
| Timing Control | | | | |
| Specified time ranges (7) (IEC 1812-1) | 0.5..10 s, 0.05..1 min, 0.5..10 min, 0.05.. 1h, 0.5..10 h, 0.05..1 day, 0.5..10 days | | | |
| Minimum control pulse duration (IEC 1812-1) | 40 ms 100 ms with load | | | |
| Recovery time (after by de-energisation) (IEC 1812-1) | 120 ms | | | |
| Repeatability (IEC 1812-1) | $\leq \pm 0.5$ % | | | |
| Setting Accuracy (IEC 1812-1) | $\leq \pm 10$ % | | | |
| Temperature drift | $\leq \pm 0.05$ % / $^{\circ}$ C | | | |
| Voltage drift | $\leq \pm 0.2$ % / V | | | |
| Relay output | | | | |
| Contact arrangement | 1 CO (SPDT) (ChangeOver -Single Pole Double Throw-) | 2 CO (SPDT) (ChangeOver -Single Pole Double Throw-) | 1 CO (SPDT) (ChangeOver -Single Pole Double Throw-) | |
| Maximum switching voltage | 250 V \sim / 10 A resistive / 125 V --- / 0.3 A resistive | | | |
| Switching current rate (resistive) | NO / NC: 10 A 250 V \sim / 10 A 30 V --- @ 40 $^{\circ}$ C NO / NC: 8 A 250 V \sim / 8 A 30 V --- @ 60 $^{\circ}$ C | NO / NC: 10 A 250 V \sim / 10 A 30 V --- @ 25 $^{\circ}$ C NO / NC: 5 A 250 V \sim / 5 A 30 V --- @ 60 $^{\circ}$ C | NO / NC: 10 A 250 V \sim / 10 A 30 V --- @ 40 $^{\circ}$ C NO / NC: 8 A 250 V \sim / 8 A 30 V --- @ 60 $^{\circ}$ C | |
| Minimum switching contact | 10 mA / 5 V --- | | | |
| Maximum switching power (resistive) | 2500 VA / 300 W | | | |
| Electrical life | 10 ⁵ cycles min at 250 V \sim / 10 A resistive(NO only) | | | |
| Maximum rate (at max switching power) | 360 cycles /hour | | | |
| Mechanical life | 10 x 10 ⁶ cycles | | | |
| Rated impulse voltage | 4 kV (1.2/50 μ s) | | | |
| Dielectric strength between coil / contacts (IEC 60664-1) | 2.5 kV / 1 min / 1 mA / 50 Hz | | | |
| Dielectric strength between open contacts | 1 kV / 1 min / 1 mA / 50 Hz | | | |
| Insulation | | | | |
| Rated Insulation voltage (IEC 60664-1) | 250 V | | | |
| Insulation coordination (IEC 60664-1) | Overvoltage category III; pollution degree 2; up to 2 000 m above sea level | | | |
| Rated impulse voltage (IEC 60664-1) | 4 kV (1.2/50 μ s) | | | |
| Clearance / Creepage distances (IEC 60664-1) | 3 mm / 3.2 mm | | | |
| Dielectric strength (EN-61812-1) | 2.5 kV / 1 min / 1 mA / 50 Hz | | | |
| Insulation Resistance (NFC 93 050) | > 500 MOhms / 250 V --- / 1 min | | | |
| General specifications | | | | |
| Status indication (LED) | Un: green LED blinks when count, flash when waiting Y1, continuous ON when supplied R: yellow LED blink when only R2 is ON (instantaneous), continuous ON when the 2 relays are ON. | | | |
| Casing | 35 mm | | | |
| Mounting | Mounting base-mounted on socket | | | |
| Housing material (UL94) | Enclosure plastic type V0 | | | |
| Degree of protection (IEC 60529) | IP40 | | | |

| | OU1R10MV1 | OA2R10MV1 | OC1R10MV1 | OL1R10MV1 |
|---|--|-----------|-----------|-----------|
| Operating temperature (IEC 60068-2) | -20 °C to +60 °C | | | |
| Storage temperature (IEC 60068-2) | -40 °C to +70 °C | | | |
| Humidity (IEC 60068-2-30) | 93 % without condensation | | | |
| Vibration resistance (IEC 60068-2-6) | ± 0.15mm from 10 Hz...60 Hz 2g from 60 Hz..150 Hz | | | |
| Shock resistance (IEC60068-2-27) | 10 gn - 11ms ; 3 x 6 axis (Output non-energized) 5 gn - 1 ms ; 3 x 6 axis (Output energized) | | | |
| Drop to concrete floor (IEC 60068-2-32) | High: 0.75 m | | | |
| Weight | 90 g 110 g with packaging | | | |

Standards

| | |
|---|---|
| CEE Directive (2014/30/EU 2014/35/EU) | EMC Low voltage |
| Approvals / Marking | CE cULus Listed Industrial Control Equipment |
| Security standard (IEC 60664-1) | Insulation coordination for equipment within low-voltage systems |
| Conformity with environmental directives (2015/863/UE 1907/2006 2012/19/UE) | RoHS Reach WEEE |
| Product standard (IEC 61812-1 UL 60947-4-1) | Specified time relays for industrial use Industrial Control Equipment (NRNT- Industrial Control Switches) Refer to UL840 InsulationCoordinationfor Electrical Equipment |
| Electromagnetic compatibility (IEC 61000-6-2 IEC 61000-6-3 IEC 61000-6-4) | Generic standards Immunity for industrial environment Emission residential environment Emission industrial environment |
| Immunity to electrostatic discharges (IEC61000-4-2) | Level III Air ± 8 KV / Contact ± 6 KV |
| Immunity to radiated, radio-frequency, electromagnetic field (IEC61000-4-3) | Level III 10V/m (80 MHz to 1 GHz) 80% AM (1 kHz) 3 V/m (1.4 to 2 GHz) 80% AM (1KHz) 1 V/m (2 to 2.7 GHz) 80% AM (1KHz) |
| Immunity to rapid transient bursts (IEC 61000-4-4) | direct ±4kV 5/50 Tr/Th ns 5 KHz & 100KHz Capacitive coupling clamp ± 2 KV 5/50 Tr/Th ns 5 KHz & 100 KHz |
| Immunity to shock waves on power supply (IEC 61000-4-5) | Level III: line-to-earth ±2kV / line-to-line ±1kV |
| Immunity to radiofrequency in common mode (IEC 61000-4-6) | Level III: 10 Vrms (0.15 to 80 MHz) 80 % AM (1 kHz) |
| Immunity to voltage dips and breaks (IEC 61000-4-11) | 0 % residual voltage during 1 cycle (Crit. B) 40 % residual voltage / 10 cycles 50Hz / 12 cycles 60Hz (Crit. C) 70 % residual voltage / 25 cycles 50Hz / 30 cycles 60Hz (Crit. C) Short interruptions: 0 % residual voltage / 250 cycles 50Hz / 300 cycles 60Hz (Crit. C) |
| AC/DC main port emissions (IEC 61000-6-3 IEC 61000-6-4) | CISPR 16-2-1 (7.4.1), CISPR 16-1-2 (4.3) 0.15 MHz – 0.5 MHz, 66 dB(µV) – 56 dB(µV) quasi-peak, 56 dB(µV) – 46 dB(µV) average 0.5 MHz – 5 MHz, 56 dB(µV) quasi-peak, 46 dB(µV) average 5 MHz – 30 MHz, 60 dB(µV) quasi-peak, 50 dB(µV) average CISPR 14-1 0.15 MHz – 30 MHz CISPR 16-2-1 (7.4.1), CISPR 16-1-2 (4.3) 0.15 MHz – 0.5 MHz, 79 dB(µV) quasi-peak, 66 dB(µV) average 0.5 MHz – 30 MHz, 73 dB(µV) quasi-peak, 60 dB(µV) average |
| Radiated emissions (IEC 61000-6-3 IEC 61000-6-4) | CISPR 16-2-3 30 MHz – 230 MHz, 30 dB(µV/m) Quasi-peak at 10 m 230 MHz – 1 000 MHz, 37 dB(µV/m) Quasi-peak at 10 m Or: 30 MHz – 230 MHz, 40 dB(µV/m) Quasi-peak at 3 m in a semi-anechoic chamber 230 MHz – 1 000 MHz, 47 dB(µV/m) Quasi-peak at 3 m in a semi-anechoic chamber |

OU1R10MV1

OA2R10MV1


OC1R10MV1

OL1R10MV1


Function Diagrams

Basic Time Chart


Function A - On-Delay (Delay on make)




Function Ac - On/Off Delay (Delay on make/break)




Function Ad - Delay on Start




Function At - Summation time relay




Function B - One-Shot




Function Bw




Function C - Off-Delay (Delay on break)



Function D - Symmetrical flashing (OFF Start)




Function Di - Symmetrical flashing (ON Start)




Function H - Interval



Function Ht - Interval summation time relay




Function L - Recycler (OFF Start)



Function Li - Recycler (ON Start)




Function N - Watchdog




| | | | |
|-----------|-----------|-----------|-----------|
| OU1R10MV1 | OA2R10MV1 | OC1R10MV1 | OL1R10MV1 |
|-----------|-----------|-----------|-----------|

Connections


OU1R10MV1 - OC1R10MV1



OA2R10MV1




OL1R10MV1



| | | | |
|-----------|-----------|-----------|-----------|
| OU1R10MV1 | OA2R10MV1 | OC1R10MV1 | OL1R10MV1 |
|-----------|-----------|-----------|-----------|

Outline dimensions (mm)



| | | | |
|-----------|-----------|-----------|-----------|
| OU1R10MV1 | OA2R10MV1 | OC1R10MV1 | OL1R10MV1 |
|-----------|-----------|-----------|-----------|

Socket

RECOMENDED SOCKET

8 Pins for DIN Rail or Panel Mount (P/N: 25 622 130)



Warning:

The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Crouzet Automatismes SAS and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru