

# Ultra-high Voltage Ceramic Capacitors

Molded type with metal terminals

For high voltage power supply/laser

UHV(Edc: 20 to 50kV) series

FHV(Edc: 15 to 50kV) series

Issue date: September 2006

- All specifications are subject to change without notice.
  - Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.
-

# Ultra-high Voltage Ceramic Capacitors

## Molded Type with Metal Terminals UHV, FHV Series

Conformity to RoHS Directive

**CLASS 2 HIGH DIELECTRIC****DC. 20 TO 50kV: UHV-1A TO 12A, 221A TO 253A TYPES****DC. 15 TO 50kV: FHV-1AN TO 12AN, 153AN TYPES**

TDK UHV and FHV series high voltage ceramic capacitors feature low dissipation and excellent voltage-capacitance characteristics using patented strontium titanate for dielectric material. They are epoxy-encapsulated to meet requirement of high voltage applications.

**FEATURES**

- Small size.
- Low dissipation factor.
- Excellent voltage-capacitance characteristics.
- Screw terminals for easy mounting.
- FHV series: High capacitance and low temperature characteristics of capacitance.

**APPLICATIONS**

High voltage power supplies, laser equipment.

**INITIAL CHARACTERISTICS**

| Series                                  | UHV   | FHV   |
|---|---|---|
| Operating temperature range             | -30 to +85°C  | -30 to +85°C  |
| Rated voltage                           | DC. 20 to 50kV  | DC. 15 to 50kV  |
| Insulation resistance                   | 100,000MΩ min.  | 100,000MΩ min.  |
| Nominal capacitance range               | 100 to 4,000pF  | 700 to 7,000pF  |
| Capacitance tolerance                   | ±10%  | ±10%  |
| Dissipation factor(tanδ)                | 0.2% max.   | 0.2% max.   |
| Capacitance temperature characteristics | Z5T:+22, -33%[+10 to +85°C, 25°C ]                      | Y5S:±22%[-30 to +85°C, 25°C ]                           |
| AC Corona starting voltage              | 3PC* max. at 50% of rated voltage min.(50Hz rms)        | 3PC* max. at 50% of rated voltage min.(50Hz rms)        |
| Withstanding voltage                    | No breakdown at 1.5 times of rated voltage, 60s(in oil) | No breakdown at 1.5 times of rated voltage, 60s(in oil) |

\* PC: Pico coulomb

**SHAPES AND DIMENSIONS****UHV-1A to 12A****UHV-221A to 253A**

Dimensions in mm

**FHV-1AN to 12AN****MARKING**

| Item  | Marking example |
|---|-----------------|
| 1. Part No.                                   |                 |
| 2. Nominal capacitance and tolerance code     | 1 → UHV-5A      |
| 3. Rated voltage                              | 2 → 172K        |
| 4. Manufacturer's name (TDK or TDK logo mark) | 3 → 30kV        |
| 5. Lot No.                                    | 4 → TDK         |
|   | 5 → 1234        |

**MARKING**

| Item  | Marking example |
|---|-----------------|
| 1. Part No.                                   |                 |
| 2. Nominal capacitance and tolerance code     | 1 → FHV-5A      |
| 3. Rated voltage                              | 2 → 172K        |
| 4. Manufacturer's name (TDK or TDK logo mark) | 3 → 30kV        |
| 5. Lot No.                                    | 4 → TDK         |
|   | 5 → 1234        |

• Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

• All specifications are subject to change without notice.

## ELECTRICAL CHARACTERISTICS/DIMENSIONS

### TYPICAL CAPACITANCE CHARACTERISTICS

#### UHV SERIES(DC. 20 to 50kV, TC:Z5T)

| Rated voltage<br>Edc(kV) | Part No. | Rated capacitance<br>(pF)±10% | Dimensions (mm) |        |    | Female thread |
|--------------------------|----------|-------------------------------|-----------------|--------|----|---------------|
|                          |          |                               | øD              | T      | L  |               |
| 20                       | UHV-221A | 200                           | 20              | 19     | 23 | ISO M4        |
|                          | UHV-222A | 400                           | 25              |        |    |               |
|                          | UHV-223A | 700                           | 30              |        |    |               |
|                          | UHV-224A | 1,000                         | 34              |        |    | ISO M5        |
|                          | UHV-1A   | 1,400                         | 38              |        |    |               |
|                          | UHV-2A   | 2,500                         | 48              |        |    |               |
|                          | UHV-3A   | 4,000                         | 60              |        |    |               |
| 30                       | UHV-231A | 200                           | 25              | 22     | 26 | ISO M4        |
|                          | UHV-232A | 400                           | 30              |        |    |               |
|                          | UHV-233A | 700                           | 34              |        |    |               |
|                          | UHV-4A   | 940                           | 38              |        |    | ISO M5        |
|                          | UHV-5A   | 1,700                         | 48              |        |    |               |
|                          | UHV-6A   | 2,700                         | 60              |        |    |               |
|                          | 40       | UHV-241A                      | 100             |        |    |               |
| UHV-242A                 |          | 200                           | 25              |        |    |               |
| UHV-243A                 |          | 400                           | 34              |        |    |               |
| UHV-7A                   |          | 700                           | 38              | ISO M5 |    |               |
| UHV-8A                   |          | 1,300                         | 48              |        |    |               |
| UHV-9A                   | 2,000    | 60                            |                 |        |    |               |
| 50                       | UHV-251A | 100                           | 20              | 31     | 35 | ISO M4        |
|                          | UHV-252A | 200                           | 30              |        |    |               |
|                          | UHV-253A | 400                           | 34              |        |    |               |
|                          | UHV-10A  | 560                           | 38              |        |    | ISO M5        |
|                          | UHV-11A  | 1,000                         | 48              |        |    |               |
| UHV-12A                  | 1,700    | 60                            |                 |        |    |               |

#### FHV SERIES(DC. 15 to 50kV, TC:Y5S)

| Rated voltage<br>Edc(kV) | Part No.  | Rated capacitance<br>(pF)±10% | Dimensions (mm) |      |      | Female thread |
|--------------------------|-----------|-------------------------------|-----------------|------|------|---------------|
|                          |           |                               | øD              | T    | L    |               |
| 15                       | FHV-153AN | 7,000                         | 60              | 16.5 | 20.5 | ISO M5        |
|                          | FHV-1AN   | 1,700                         | 38              | 18.5 | 22.5 |               |
| 20                       | FHV-2AN   | 3,000                         | 48              |      |      |               |
|                          | FHV-3AN   | 5,200                         | 60              |      |      |               |
|                          | FHV-4AN   | 1,200                         | 38              |      |      |               |
| 30                       | FHV-5AN   | 2,100                         | 48              | 22   | 26   | ISO M5        |
|                          | FHV-6AN   | 3,500                         | 60              |      |      |               |
|                          | FHV-7AN   | 850                           | 38              |      |      |               |
| 40                       | FHV-8AN   | 1,500                         | 48              | 26   | 30   | ISO M5        |
|                          | FHV-9AN   | 2,600                         | 60              |      |      |               |
|                          | FHV-10AN  | 700                           | 38              |      |      |               |
| 50                       | FHV-11AN  | 1,300                         | 48              | 29   | 33   | ISO M5        |
|                          | FHV-12AN  | 2,100                         | 60              |      |      |               |

### TYPICAL CAPACITANCE CHARACTERISTICS

#### CAPACITANCE vs. TEMPERATURE CHARACTERISTICS

##### UHV SERIES(DC. 20 to 50kV, TC:Z5T)



##### FHV SERIES(DC. 15 to 50kV, TC:Y5S)



## CAPACITANCE vs. DC BIAS CHARACTERISTICS

### UHV SERIES(DC. 20 to 50kV, TC:Z5T)



### FHV SERIES(DC. 15 to 50kV, TC:Y5S)



## PRECAUTIONS

### (1) During transportation and storage

- Do not transport or store where the capacitor will be exposed to high temperature or high humidity.
- Do not expose to poisonous gases such as H<sub>2</sub>SO<sub>4</sub>, HCl, or HNO<sub>3</sub>.
- Avoid excessive impact such as that caused by falling.

### (2) During operation

- Avoid contact with electrolytes such as perspiration. Do not touch with bare hands.
- Avoid excessive impact such as that caused by falling.
- Do not apply solder to stud terminals.
- Do not re-machine the terminals.

### (3) Usage

- When the capacitor is used for high-speed pulses such as with a laser, make sure that the impressed voltage (peak-to-peak voltage) is within the capacitor's rated specifications.
- Make sure that the capacitor is not exposed to radiant heat from chambers or transformers.

• For more information about products with other capacitance or other data, please contact us.

• All specifications are subject to change without notice.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)