



For more Information  
please call

1-800-Belden1



### General Description:

Security, Pro Audio & Intercom Cable, Plenum-CMP, 2-22 AWG stranded bare copper pairs with FEP insulation, Individually Beldfoil® shielded and PVDF jacket with ripcord

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
2	22	7x30	BC - Bare Copper	.029

Total Number of Conductors: 4

#### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (in.)	Dia. (in.)
Teflon®	FEP - Fluorinated Ethylene Propylene	.010	.049

#### Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

#### Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVDF - Fluorocopolymer	.015

Outer Jacket Ripcord: Yes

#### Overall Cable

Overall Nominal Diameter: 0.214 in.

#### Pair

Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & White

Pair Lay Length & Direction:

Lay Length (in.)	Twists (twist/ft)
1.375	6.900

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +150°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 23.700 lbs/1000 ft.

Max. Recommended Pulling Tension: 47.400 lbs.

Min. Bend Radius/Minor Axis: 2.100 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
NEC Articles:	800
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

50

### Nom. Inductance:

Inductance (µH/ft)

.18

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

27.5

### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

49.5

### Nominal Velocity of Propagation:

VP (%)

69

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

16.4

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 15.300 Ohm/1000 ft

### Max. Operating Voltage - UL:

Voltage

300 V RMS

### Max. Recommended Current:

Current

2.2 Amps per conductor @ 25°C

## Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6541PA 008U1000	1,000 FT	26.000 LB	GRAY		2 FSPR #22 FEP SLF
6541PA 0081000	1,000 FT	27.000 LB	GRAY	C	2 FSPR #22 FEP SLF

### Notes:

C = CRATE REEL PUT-UP.

## 6541PA Multi-Conductor - Pro Audio and Intercom Systems

Revision Number: 1    Revision Date: 03-13-2013

© 2014 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)