

**Description**

- The IQXT-316-3 uses ASIC technology and is designed to meet the short and medium term stability requirements of packet network synchronisation for Small Cells.
- Model IQXT-316-3
- Model Issue number 1

**Frequency Parameters**

- Frequency 30.720MHz
- Frequency Tolerance  $\pm 1.00$ ppm
- Tolerance Condition @ 25°C  $\pm 1^\circ\text{C}$  & VC=1.5V
- Frequency Stability Max  $\pm 0.25$ ppm
- Operating Temperature Range -5.00 to 85.00°C
- In-service Short-term Frequency Stability (over any 24-hr timeslot @ fixed supply voltage and load):
  - 50 to 70°C:  $\pm 80$ ppb max
  - 15 to 85°C:  $\pm 100$ ppb max
  - 5 to 85°C:  $\pm 250$ ppb max
- Ageing (@ 25°C):
  - $\pm 20$ ppb max/day
  - $\pm 200$ ppb max/month
  - $\pm 1$ ppm max/year
  - $\pm 2$ ppm max over 3yrs
- Temperature Rate of Change (maximum rate of change of temperature condition for guaranteed stability specifications):  $1^\circ\text{C}/\text{min}$  max
- Acceleration Sensitivity (gamma vector of all 3 axes from 30 to 1500Hz): Typically 2ppb/G max
- Supply Voltage Variation ( $\pm 2\%$  change @ 25°C, measurement referenced to frequency observed @ nominal Vs):  $\pm 10$ ppb typ
- Load Variation ( $\pm 1$ pF change @ 25°C, measurement referenced to frequency observed @ nominal load):  $\pm 10$ ppb typ
- Reflow Variation (pre to post reflow  $\Delta F$ , measured after 1hr recovery @ 25°C):  $\pm 1$ ppm max
- Note: The characteristics of the oscillator may be temporarily affected by the processes of assembly and soldering. The in-service short term frequency stability specification applies after 48hrs continuous operation and after the first excursion over the temperature range. Nominal conditions apply unless otherwise stated.

**Electrical Parameters**

- Supply Voltage 3.3V  $\pm 5\%$
- Current Draw 7.000mA
- Absolute Maximum Ratings:
  - Supply Voltage (Vs): -0.5V to 7V
  - Control Voltage (VC): -0.5V to 9V
  - All other inputs: -0.5V to Vs+0.5V
  - Power Dissipation: 100mW max
  - Junction Temperature: 150°C max
- Note: Operating beyond these limits may result in change or permanent damage to the oscillator.


**Outline (mm)**

**Sales Office Contact Details:**

UK: +44 (0)1460 270200  
Germany: 0800 1808 443

France: 0800 901 383  
USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

**Frequency Adjustment**

- Pulling  $\pm 7\text{ppm min to } \pm 12\text{ppm max}$
- Control Voltage  $1.5\text{V } \pm 1.0\text{V}$
- Input Impedance  $100\text{k}\Omega \text{ min}$
- Linearity (deviation from straight line curve fit):  $1\% \text{ max}$
- Frequency Tuning Slope: Positive
- Modulation Bandwidth:  $1\text{Hz min}$
- Note: Pulling referenced to frequency @  $V_C=1.5\text{V}$

**Output Details**

- Output Compatibility HCMOS
- Drive Capability  $15\text{pF}$
- Rise and Fall Time  $8.0\text{ns max}$
- Duty Cycle  $45/55\%$
- Output Voltage Levels:  
Output Low (VoL):  $10\%V_s \text{ max}$   
Output High (VoH):  $90\%V_s \text{ min}$
- Start Up Time (amplitude within 90% of specified output level):  
 $15\text{ms max}$
- Temperature Sensor Output (pad 3):  
Vtemp (@  $25^\circ\text{C}$ ):  $1.76\text{V typ}$   
Slope Option:  $-2.1\text{mV}/^\circ\text{C typ}$   
Resistive Load:  $100\text{k}\Omega \text{ min}$   
Capacitive Load:  $30\text{pF max}$   
Output Impedance (@  $25^\circ\text{C}$ ):  $1\text{k}\Omega \text{ typ}$   
Sensor Linearity:  $1.5\% \text{ typ}$

**Output Control**

- Tri-State Mode:  
Logic '0' ( $20\%V_s \text{ max}$ ) to pad 6 disables the oscillator output, the output goes to a high impedance state.  
Logic '1' ( $60\%V_s \text{ min}$ ) or no connection to pad 6 enables the oscillator output.  
Note: The tri-state control (enable) input pad has an internal  $100\text{k}\Omega$  pull up resistor which allows it to be left unconnected if not used. When in tri-state mode, the output stage is disabled, but the oscillator and compensation circuit are still active (Current Consumption:  $2\text{mA typ}$ ).
- Output Enable Time:  $100\mu\text{s max}$

**Noise Parameters**

- Phase Noise @  $25^\circ\text{C}$  (typ):  
 $-65\text{dBc}/\text{Hz @ } 1\text{Hz}$   
 $-95\text{dBc}/\text{Hz @ } 10\text{Hz}$   
 $-125\text{dBc}/\text{Hz @ } 100\text{Hz}$   
 $-143\text{dBc}/\text{Hz @ } 1\text{kHz}$   
 $-149\text{dBc}/\text{Hz @ } 10\text{kHz}$   
 $-152\text{dBc}/\text{Hz @ } 100\text{kHz}$   
 $-155\text{dBc}/\text{Hz @ } 1\text{MHz}$
- Phase Jitter (12kHz to 5MHz):  $300\text{fs RMS typ}$

**Sales Office Contact Details:**

UK: +44 (0)1460 270200  
Germany: 0800 1808 443

France: 0800 901 383  
USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

**Environmental Parameters**

- Low Temperature Storage: IEC 60068-2-01, Test Ab: 1000hrs @ -55°C.
- High Temperature Storage: IEC 60068-2-02, Test Bb: 1000hrs @ 150°C.
- Mechanical Shock: JESD22-B104: 1500G, 0.5ms duration, 5 pulses in each of 6 directions.
- Vibration: JESD22-B103: 20G peak acceleration for 4hrs in each of the 3 orientations, tested from 60-2000Hz, 12hrs total.
- High Temperature Operating Life (HTOL): JESD22-A108: 1008hrs @ 125°C.
- Thermal Cycling: JESD22-A104: 500 temperature cycles, -55 to 125°C.
- Solderability: JESD22-B102, Method 1, Condition E: 260°C for 5secs (preconditioning: 150°C, 16hrs).
- Resistance to Soldering Heat: IPC/JEDEC J-STD-020: 3 reflow cycles (peak temperature 260°C).
- Humidity: JESD22-A101: After 1008hrs @ 85°C ±2°C, 85% RH non-condensing (preconditioning: 3 reflow cycles @ peak temperature 260°C).
- Ageing: MIL-PRF-55310: 1008hrs @ 85°C (preconditioning: 3 reflow cycles @ peak temperature 260°C).

**Manufacturing Details**

- Maximum Process Temperature: 260°C (30secs max)

**Compliance**

- RoHS Status (2011/65/EU)      Compliant
- REACH Status                      Compliant
- MSL Rating (JDEC-STD-033):    1

**Packaging Details**

- Pack Style: Reel      Tape & reel in accordance with EIA-481-D  
Pack Size: 500
- *Alternative packing option available*

**Sales Office Contact Details:**

UK: +44 (0)1460 270200

Germany: 0800 1808 443

France: 0800 901 383

USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)