

## Main

Enclosure type	Corrosion resistance enclosure indoor/outdoor Dust and oil resistant weatherproof enclosure indoor/outdoor
----------------	---

## Complementary

Line Rated Current	10 A
Cable entry	1 entry for 1/2" - 14 NPT
Controlled fluid	Selected corrosive liquids Selected corrosive gases
Fluid connection type	0.25 inch 18 NPTF
Local display	Without
Locking options description	Without keylocks
Material	Zinc plated steel flange
Materials in contact with fluid	Viton fluorocarbon diaphragm
Maximum pressure	10000 psig
Operating rate	<= 120 cyc/mn
Permissible voltage	<= 600 V
Pilot light	24 V DC red LED
Pressure actuator	Piston
Range on decreasing pressure	20...1000 psi
Repeat accuracy	+/- 0.1...1 %
Scale type	Fixed differential
Stage of operation	Stage 1
Switch function	SPDT isolated
Switching threshold drift	+/- 1 % adjustable range over 1000000 operations
Temperature of controlled fluid	-15...250 °F
Tolerance	+/- 9 %
Type of setting	Fixed

## Environment

ambient air temperature for operation	-10...185 °F
approximate fixed differential	59 psi
NEMA degree of protection	NEMA 4/4X/13
product certifications	CE CSA UL listed CSA LR25490 class 3211 03
shock resistance	50 gn
standards	UL 508 IEC 60957-5-1

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.

---

For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov) For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)