

Product Description


The QPD2194 is a discrete GaN on SiC HEMT which operates from 1.8-2.2 GHz. The device is a single stage pre-matched power amplifier transistor.

The QPD2194 can be used in Doherty architecture for the final stage of a base station power amplifier for macrocell high efficiency systems.

QPD2194 can deliver P_{SAT} of 371 W at +48 V operation.

Lead-free and ROHS compliant.

Functional Block Diagram



2 Lead NI400 Package

Product Features

- Operating Frequency Range: 1.8-2.2 GHz
- Operating Drain Voltage: +48 V
- Maximum Output Power (P_{SAT}): 371 W
- Maximum Drain Efficiency: 78.8%
- Efficiency-Tuned P3dB Gain: 18.0 dB
- 2-lead, earless, ceramic flange NI400 package

Applications

- W-CDMA / LTE
- Macrocell Base Station, B3-B1
- Active Antenna

Ordering Information

| Part No. | ECCN | Description |
|----------------|-------|---------------------------|
| QPD2194S2 | EAR99 | Box (2 Samples Each) |
| QPD2194SQ | EAR99 | Tray (25 Samples) |
| QPD2194SR | EAR99 | Reel (100 Samples) |
| QPD2194PCB4B01 | EAR99 | 1805-2170 MHz Eval. Board |

Absolute Maximum Ratings

| Parameter | Value / Range |
|---|---------------|
| Gate Current (I_G) | -48 to 48 mA |
| Drain Voltage (V_D) | +55 V |
| Peak RF Input Power | 44 dBm |
| VSWR Mismatch, P1dB Pulse (10 % duty cycle, 100 μ width), T = 25 °C | 10:1 |

Operation of this device outside the parameter ranges given above may cause permanent damage.

Recommended Operating

| Parameter | Min | Typ | Max | Units |
|--------------------------------|-----|------|-----|-------|
| Gate Voltage (V_G) | | -2.7 | | V |
| Drain Voltage (V_D) | | 48 | | V |
| Quiescent Current (I_{DQ}) | | 600 | | mA |

Electrical performance is measured under conditions noted in the electrical specifications table. Specifications are not guaranteed over all recommended operating conditions.

RF Characterization

| Parameter | Conditions | Min | Typ | Max | Units |
|-------------------|------------|------|------|------|-------|
| Frequency Range | | 1805 | - | 2170 | MHz |
| Quiescent Current | | | 600 | | mA |
| Linear Gain | | | 19.1 | | dB |
| P3dB | | | 55.0 | | dBm |
| Drain Efficiency | P3dB | | 60.0 | | % |

Test conditions unless otherwise noted: $V_D = +48$ V, $I_{DQ} = 600$ mA, T = 25 °C, Pulsed CW (10% duty cycle, 100 μ s width) on Class AB single-ended EVB at 1880 MHz


Thermal and Reliability Information

| Parameter | Test Conditions | Value | Units |
|--|---|-------|--------------------|
| Thermal Resistance, Peak IR Surface Temperature at Average Power (θ_{JC}) | $T_{CASE} = 85^\circ\text{C}$, $T_{CH} = 131^\circ\text{C}$, CW: $P_{DISS} = 60$ W, $P_{OUT} = 90$ W | 0.77 | $^\circ\text{C/W}$ |

Notes:

1. Thermal resistance measured to package backside.
2. Based on expected carrier amplifier efficiency of Doherty.
3. P_{OUT} assumes 20% peaking amplifier contribution of total average Doherty rated power.
4. Refer to the following document: [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#).







QPD2194PCB4B01 Layout



QPD2194PCB4B01 Bill of Materials



| Reference Des. | Value | Description | Manuf. | Part Number |
|-------------------|--------|---|-----------|--------------------|
| C1, C2, C3, C4 | 33 pF | Capacitor, 33 pF, 5%, 250 V | ATC | ATC800A330JT |
| C5 | 1.2 oF | Capacitor, 1.2 pF, ±0.1 pF, 250 V | ATC | ATC800A1R2BT250X |
| C6 | 1.9 pF | Capacitor, 1.9 pF, ±0.1 pF, 250 V | ATC | ATC800A1R9BT250X |
| C7 | 2.2 pF | Capacitor, 2.2 pF, ±0.1 pF, 250 V | ATC | ATC800A2R2BT250X |
| C8 | 0.8 pF | Capacitor, 0.8 pF, ±0.1 pF, 250 V | ATC | ATC800A0R8BT250X |
| C9, C10, C11, C15 | 4.7 µF | Capacitor, 4.7 µF, 10%, 100 V, X7R | Murata | GRM55ER72A475KA01L |
| C12 | 1 µF | Capacitor, 1 µF, 10%, 100 V, X7R | Murata | GRM32NR72A104KA01L |
| C13 | 100 µF | Capacitor, 100 µF, ±20%, 50 V, electrolytic | Panasonic | EEE-1HA101UAP |
| C14 | 220 µF | Capacitor, 220 µF, 20%, 100 V, electrolytic | Cornell | AFK227M2AR44T-F |
| R1 | 10 Ω | Resistor, 10 Ω, 1%, 1/4 W, 1206 | Panasonic | ERJ-8ENF10R0V |

QPD2194PCB4B01 Performance Plots



Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 600\text{ mA}$, $T = 25^\circ\text{C}$, on Class AB single-ended EVB.

QPD2194PCB4B01 Performance Plots



Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 600\text{ mA}$, $T = 25^\circ\text{C}$, on Class AB single-ended EVB.

Power-Tuned Load Pull Performance

| Frequency (MHz) | Source Impedance | Load Impedance | Gain @ P3dB (dB) | P3dB (dBm) | Drain Efficiency (%) |
|-----------------|------------------|----------------|------------------|------------|----------------------|
| 1800 | 6.21 – j1.70 | 6.15 – j5.81 | 15.1 | 55.4 | 54.0 |
| 1840 | 2.31 – j5.94 | 6.15 – j5.82 | 15.9 | 55.7 | 57.0 |
| 1880 | 4.21 – j2.56 | 6.00 – j4.30 | 16.4 | 55.7 | 62.5 |
| 2110 | 4.06 – j5.02 | 6.52 – j2.92 | 16.4 | 55.6 | 66.6 |
| 2140 | 4.24 – j5.12 | 8.50 – j2.10 | 15.7 | 55.6 | 59.4 |
| 2170 | 1.55 – j2.71 | 8.00 – j2.10 | 16.1 | 55.6 | 62.2 |

Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 600\text{ mA}$, $T = 25^\circ\text{C}$, Pulsed (10% duty cycle, 100 μs width)


Efficiency-Tuned Load Pull Performance

| Frequency (MHz) | Source Impedance | Load Impedance | Gain @ P3dB (dB) | P3dB (dBm) | Drain Efficiency (%) |
|-----------------|------------------|----------------|------------------|------------|----------------------|
| 1800 | 6.21 – j1.70 | 2.50 – j1.70 | 16.8 | 53.6 | 70.9 |
| 1840 | 2.31 – j5.94 | 2.92 – j2.22 | 17.6 | 54.3 | 73.3 |
| 1880 | 4.21 – j2.56 | 2.53 – j2.80 | 18.0 | 54.1 | 78.8 |
| 2110 | 4.06 – j5.02 | 2.14 – j3.38 | 17.6 | 52.6 | 78.4 |
| 2140 | 4.24 – j5.12 | 3.30 – j3.90 | 17.5 | 53.8 | 75.7 |
| 2170 | 1.55 – j2.71 | 2.23 – j4.27 | 18.0 | 52.2 | 77.7 |


Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 600\text{ mA}$, $T = 25^\circ\text{C}$, Pulsed (10% duty cycle, 100 μs width)

Load Pull Plots


Load Pull at 1.8 GHz



Load Pull at 1.84 GHz




Load Pull at 1.88 GHz




Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 600\text{ mA}$, $T = 25^\circ\text{C}$, Pulsed (10% duty cycle, 100 μs width)

Load Pull Plots


Load Pull at 2.11 GHz



Load Pull at 2.14 GHz




Load Pull at 2.17 GHz



Test conditions unless otherwise noted: $V_D = +48\text{ V}$, $I_{DQ} = 600\text{ mA}$, $T = 25^\circ\text{C}$, Pulsed (10% duty cycle, 100 μs width)

Pin Configuration




Pin Description

| Pin No. | Label | Description |
|---------------------|------------|-----------------------|
| 1 | RF IN, VG | RF Input, Gate Bias |
| 2 | RF OUT, VD | RF Output, Drain Bias |
| 3 (Backside Paddle) | RF/DC GND | RF/DC Ground |

Package Marking and Dimensions


Marking: Qorvo Logo
 Part Number – QPD2194
 Date Code – YYWW
 Production Lot Number – MXXX
 Serial Number – ZZZ



Notes: Unless Otherwise Specified;

1. Material:
 - Package Base: Ceramic/Metal
 - Package Lid: Ceramic
2. Package exposed metallization is NiAu plated. Au thickness is minimum 60 μm .
3. Part is epoxy sealed.
4. Part meets industry NI400 footprint.
5. Body dimensions do not include lid shift or epoxy run out, which can be up to 0.020 per side.
6. Dimensions are in inches. General tolerance is ± 0.005 .


Tape and Reel Information – Carrier and Cover Tape Dimensions



| Feature | Measure | Symbol | Size (in) | Size (mm) |
|---------------------|--|--------|-----------|-----------|
| Cavity | Length | A0 | 0.417 | 10.60 |
| | Width | B0 | 0.419 | 10.65 |
| | Depth | K0 | 0.181 | 4.60 |
| | Pitch | P1 | 0.630 | 16 |
| Centerline Distance | Cavity to Perforation – Length Direction | P2 | 0.079 | 2.00 |
| | Cavity to Perforation – Width Direction | F | 0.559 | 14.20 |
| Cover Tape | Width | C | 1.004 | 25.50 |
| Carrier Tape | Width | W | 1.260 | 32 |


Tape and Reel Information – Reel Dimensions

Standard T/R size = 100 pieces on a 13" reel.



| Feature | Measure | Symbol | Size (in) | Size (mm) |
|---------|----------------------|--------|-----------|-----------|
| Flange | Diameter | A | 12.992 | 330.0 |
| | Thickness | W2 | 1.504 | 38.2 |
| | Space Between Flange | W1 | 1.291 | 32.8 |
| Hub | Outer Diameter | N | 4.016 | 102.0 |
| | Arbor Hole Diameter | C | 0.512 | 13.0 |
| | Key Slit Width | B | 0.079 | 2.0 |
| | Key Slit Diameter | D | 0.787 | 20.0 |

Tape and Reel Information – Tape Length and Label Placement



Notes:

1. Empty part cavities at the trailing and leading ends are sealed with cover tape. See EIA 481-1-A.
2. Labels are placed on the flange opposite the sprockets in the carrier tape.

Handling Precautions

| Parameter | Rating | Standard |
|----------------------------------|----------|---------------------------------|
| ESD – Human Body Model (HBM) | Class 1B | ANSI/ESDA/JEDEC Standard JS-001 |
| ESD – Charged Device Model (CDM) | Class C3 | ANSI/ESDA/JEDEC Standard JS-002 |
| MSL – 260°C Convection Reflow | Level 3 | IPC/JEDEC Standard J-STD-020 |



Solderability

Compatible with lead-free (260°C maximum reflow temperature) soldering processes. The use of no-clean solder to avoid washing after soldering is recommended. Contact plating is NiAu. Au thickness is minimum 60 µin.

RoHS Compliance

This product is compliant with the 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment), as amended by Directive 2015/863/EU. This product also has the following attributes:

- Lead Free
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about Qorvo:

Web: www.qorvo.com **Tel:** +1.972.994.8465
Email: info-sales@qorvo.com **Fax:** +1.972.994.8504

For technical questions and application information:

Email: BTSApplications@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2018 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru