

## UFE / UFR Series

### Up to 6000 Watts

**Total Power:** Up to 6000 W  
**Input Voltage:** 85 - 264 Vac  
**# of Outputs:** Single + Aux  
**Output:** 24 V & 48 V



### Special Features

- Rack mounted chassis (1U, 19")
- 3 hot pluggable rectifiers per 1U chassis, up to 4 kW redundant or 6 kW available power (180 - 264 Vac input)
- Up to 2.6 kW redundant or 3.9 kW available per shelf at 90 - 132 Vac input
- Stackable to 6U high to provide up to 36 kW available power
- Class B conducted EMI EN55022 (See Note 1)
- Automatic fan speed control with fault reporting
- Auxiliary standby output, 11 V at approximately 2.8 W
- High density up to 22 W/in<sup>3</sup>
- High efficiency up to 91%
- Floating as well as isolated main output voltage allows positive or negative polarity operation
- EU directive 2002/95/EC compliant for RoHS
- 2 year warranty
- PMBus compliant

### Safety

- VDE EN/IEC60950-1
- UL/cUL60950-1

## Electrical Specifications

| Output   |  |  |
|--|--|--|
| Output Power:  | Main output<br>Auxiliary output                      | See Table 1<br>11 V ±15%, 2.875 W  |
| Line regulation:   | Low line to high line                                | ±0.15% max.  |
| Load regulation (active share mode):                               | Full load to min. load                               | ±0.15% max.  |
| Turn-on delay:   | (See Note 4)   | 5.0 s max.   |
| Ambient temp. coefficient:   | At full load, min. Vin                               | ± 0.005%/°C  |
| Voltage adjustability:<br>Adjustable PMBus command<br>(See Note 6) | 48 Vout<br>24 Vout                                   | 42-57 Vdc<br>21-28.5 Vdc   |
| Output setpoint accuracy:  |  | ± 0.5%   |
| Default output voltage:<br>setting 25 °C                           | 48 Vout (active default)<br>24 Vout (active default) | 48 V ± 0.5% @ 41 A<br>27 V ± 0.5% @ 48 A   |
| Voltage droop:<br>(operation set PMBus command)                    | 24 Vout<br>48 Vout                                   | 40.3 mV/A ± 3.0% from<br>10 A up to power limit<br>80.6 mV/A ± 3.0% from<br>10 A up to power limit |
| Total error band:  | -40 °C to +70 °C, FL range                           | ±1.0% max.   |
| Overshoot/undershoot:  | Main output @ turn-on/off                            | 0%/0%  |
| Ripple and noise (20 MHz):   | Main output, -5 °C and above<br>Auxiliary output     | 500 mV pk-pk, 150 mV rms<br>400 mV pk-pk, 150 mV rms   |
| Dynamic regulation (except droop mode):                            | Peak dev., 25% load step Recovery<br>time            | 2.5% max.<br>1 ms max.   |
| Current sharing (See Note 3):                                      | (I1-I2) / ILIMIT x 100                               | 15% max.   |

All specifications are typical at nominal input, full load at 25 °C ambient unless otherwise stated.



| Input                                 |                     |  |
|---------------------------------------|---------------------|--|
| Input voltage range:<br>(See note 2)  |                     | 88 - 264 Vac<br>176 - 264 Vac            |
| Input frequency range:                |                     | 47 - 63 Hz                               |
| Input current:                        |                     | 15 A max.                                |
| Ground leakage current:               | AC to safety ground | 2 mA max.                                |
| Input fuse (internal)                 | Both lines fused    | 30 A                                     |
| Power factor:                         | 50 to 100% load     | 0.98                                     |
| Undervoltage lockout:<br>(power up)   | High line range     | 176 Vac max.                             |
|                                       | Wide line range     | 88 Vac. max                              |
| Undervoltage lockout:<br>(power down) | High line range     | 162 Vac min.<br>LED warning @ 176 V max. |
|                                       | Wide line range     | 76 Vac min.<br>LED warning @ 88 V max.   |

**Notes**

- Final EMI performance is system/shelf dependent.
- Auto ranging sets power limit based on input voltage at turn on.
- The difference in output current among any two rectifiers operating in parallel does not exceed a value equal to 15% of the rated current limit. This specification applies for operation with any output current from no load to 110% of maximum.
- Maximum 15 minute warm up time at light loads below -15 °C. See Application Note 212 for cold start timing data.
- For operation above 1,524 m (5,000 ft), maximum operation temperature is derated by 2 °C per 305 m (1,000 ft).
- Output voltage can be modified on the fly between 21-28.5 V (24 V model) or 42-57 V (48 V model) PMBus command.
- PM BUs communication. Pin names in parenthesis refer to the PMBus version names. UFE2000-96S48PJ and UFE130096S24PJ use PMBus.

| General Specifications   |                                     |                                    |
|--------------------------|-------------------------------------|------------------------------------|
| Electrical insulation:   | Input/output                        | 3000 Vac / 4242 Vdc                |
|                          | Input/chassis                       | 1500 Vac / 2121 Vdc                |
| Switching frequency:     | Fixed                               | 450 kHz                            |
| Approvals and standards: |                                     | VDE EN/IEC60950-1<br>UL/CUL60950-1 |
| Weight:                  |                                     | 5.5 lbs                            |
| Hold-up time:            | 48 Vout at rated output power       | 20 ms min.                         |
|                          | 24 Vout at rated output power       | 20 ms min.                         |
| MTBF (@25 °C):           | Telcordia SR-332 Issue 1            | 279,069 hours                      |
| Acoustical noise:        | Over all conditions                 | 71 dB max.                         |
|                          | 25 °C ambient at rated output power | 58 dB typ.                         |

| EMC                  |                      |                                    |
|----------------------|----------------------|------------------------------------|
| Conducted emissions: | EN55022, FCC part 15 | Class B (when installed in system) |
| Immunity:            |                      |                                    |
| Harmonic current:    | EN61000-3-2          | Compliant                          |
| ESD air/contact:     | EN61000-4-2          | Level 3                            |
| Surge:               | EN61000-4-5          |                                    |
| Fast transients:     | EN61000-4-4          | Level 3                            |
| Flicker:             | EN61000-3-3          | Compliant                          |
| Magnetic field:      | EN61000-4-8          | Compliant                          |
| Radiated immunity:   | EN61000-4-3          | Level 3                            |
| Conducted immunity:  | EN61000-4-6          | Level 3                            |

**Ordering Information**

| Rated Output Power | Output Voltage Vout |        | Output Current (Min) | Power Limit +15% / -0% Vout (min) | Line Range at Turn On (Auto Ranging) | Operating Line Range | Current Limit (Vout) < Vout (min) | Model Numbers (7) | Order Number |
|--------------------|---------------------|--------|----------------------|-----------------------------------|--------------------------------------|----------------------|-----------------------------------|-------------------|--------------|
|                    | Min                 | Max    |                      |                                   |                                      |                      |                                   |                   |              |
| 24 Vout Models     |                     |        |                      |                                   |                                      |                      |                                   |                   |              |
| 1300 W             | 21 v                | 28.5 V | 0 A                  | 1300 W                            | 90-264 Vac                           | 65 A                 | 65 A                              | UFE1300-96S24C1J  | UFE1300-5    |
| 48 Vout Models     |                     |        |                      |                                   |                                      |                      |                                   |                   |              |
| 1300 W             | 42 V                | 57 V   | 0 A                  | 1300 W                            | 90-264 Vac                           | 33 A                 | 33 A                              | UFE2000-96S48PJ   | UFE2000-9    |
| 2000 W             | 42 V                | 57 V   | 0 A                  | 2000 W                            | 180-264 Vac                          | 52 A                 | 52 A                              |                   |              |
| 1300 W             | 42 V                | 57 V   | 0 A                  | 1300 W                            | 90-264 Vac                           | 33 A                 | 33 A                              | UFE2000-96S48PDJ  | UFE2000-9-D  |
| 2000 W             | 42 V                | 57 V   | 0 A                  | 2000 W                            | 180-264 Vac                          | 52 A                 | 52 A                              |                   |              |
| 1300 W             | 42 V                | 57 V   | 0 A                  | 1300 W                            | 90-264 Vac                           | 33 A                 | 33 A                              | UFE2000-96S48PHDJ | UFE2000-9-HD |
| 2000 W             | 42 V                | 57 V   | 0 A                  | 2000 W                            | 180-264 Vac                          | 52 A                 | 52 A                              |                   |              |

**Rack Ordering Information**

| Rack Model Number | Hot Plug Interface | Number of Power Modules per Pack |
|-------------------|--------------------|----------------------------------|
| UFR6000-00J       | Yes                | 3                                |
| UFR6000-01J       | Yes                | 2 + 1 (Split Rack)               |
| UFR6000PJ         | Blank Panel        | 3                                |

## Environmental Specifications


|   |   |   |
|---|---|---|
| Thermal performance:<br>(See Notes 4 and derating curves) | Operating<br>Non-operating<br>Cold Start                          | -33 °C to +70 °C<br>-40 °C to +100 °C<br>-40 °C |
| Relative humidity:<br>non-condensing                      | Operating<br>Non-operating  | Up to 80%<br>Up to 95%                          |
| Altitude:<br>(See Note 5)                                 | Operating<br>Non-operating  | 10,000 feet max.<br>35,000 feet max.            |
| Vibration:  | Operating<br>Non-operating  | 1.0 G peak<br>1.5 G peak                        |
| Shock:  | Operating<br>Non-operating  | 10 G peak / 11 ms<br>40 G peak / 11 ms          |
| <b>Protection</b>   |   |   |
| Power limit:<br>Vo > Vout min                             |   | ± Rated power +15%/-0%                          |
| Current limit:  | Constant current limiting - brickwall<br>Vo <sup>2</sup> Vout min | ± limit, ± 8%                                   |
| Short-circuit:  | Hiccup mode at<br>Vo < 40 Vdc<br>Vo < 20 Vdc                      | 200 ms on / 1/8 s off                           |
| Overvoltage:  | Output shutdown<br>Latching after 1 retry                         | 60 V max.<br>32 V max.                          |
| Thermal:  | Self protecting   | Non-latching                                    |
| OR-ing fault<br>(See Note 7)                              | Tested via I <sup>2</sup> C or PMBus                              | LED alarm (by read) in case of OR-ing fault     |
| <b>Communication Monitoring Readout Accuracy</b>          |   |   |
| Current:  | Valid from 15% to max. load                                       | ± 15%   |
| Voltage:  | Measured before output OR-ing                                     | ± 5%  |
| Temperature:  | Measured Internal output OR-ing                                   | ± 5 °C  |
| Hours counter:  |   | ± 36 s/hours approx.                            |

## Part Number System with Options

| Product Family            | Rated Output Power                     | Input Range                  | Standard Compliance      | Type of Output | Output Voltage         | Communications Type  | Option Code   | Special Modification | RoHS Compliance <sup>(9)</sup>   |
|---------------------------|--|------------------------------|--------------------------|----------------|------------------------|--|---|----------------------|----------------------------------|
| <b>UFE</b>                | <b>2000</b>                            | <b>9</b>                     | <b>6</b>                 | <b>S</b>       | <b>48</b>              | <b>P</b>   | <b>D</b>  | <b>XX</b>            | <b>J</b>                         |
| UFE = Universal Front-End | 1300 = 1300 Watts<br>2000 = 2000 Watts | 9 = Universal Input with PFC | 6 = UL/CSA/VDE Class A/B | S = Single     | 48 = 48 V<br>24 = 24 V | C1 = I <sup>2</sup> C serial communication<br>P = PMBus serial communication | None = Active Ishare<br>D = Droop Ishare<br>HD = PS Enable HI/Droop |                      | J = Pb free (RoHS 6/6 compliant) |

# Mechanical Drawing


Rev.06.14.11\_47  
UFE / UFR Series  
4 of 6



| Power Supply Connector | Mating Connector    |
|------------------------|---------------------|
| Molex: 87663-4006      | Molex: 87664-2004   |
| Tyco: 2-1450330-8      | Tyco: 1450370-5     |
| FCI Berg: 51939-180    | FCI Berg: 51915-070 |


| Power Supply Connector Pinout |           |        |   |         |                                      |
|-------------------------------|-----------|--------|---|---------|--------------------------------------|
| Pin                           | D         | C      | B | A       |                                      |
| P1                            | L1        |        |   |         |                                      |
| P2                            | L2        |        |   |         |                                      |
| P3                            | PEG       |        |   |         |                                      |
| 1                             | Sense-    | Sense+ |   | GND     | Shortpin                             |
| 2                             | Present-L | GND    |   | PS-ID0  | GND                                  |
| 3                             | PS-ID3    | PS-ID2 |   | GND     | 12V-AUX                              |
| 4                             | GND       | SCL    |   | PS-ID1  | GND                                  |
| 5                             | SDA       | GND    |   | GND     | I <sup>2</sup> C-En-H<br>(Comm-En-H) |
| 6                             | SMBALERT# | Ishare |   | DC-OK-L | PS-EN (Control)                      |
| P4                            |           |        |   |         | DC_N                                 |
| P5                            |           |        |   |         | DC_N                                 |
| P6                            |           |        |   |         | DC_P                                 |
| P7                            |           |        |   |         | DC_P                                 |

## Power Supply Connector



Power Connections Layout  
(Looking into Connector Side of UFE Power Supply)

# Rack Specifications



| Rack Signal Connector Pinout |                                     |         |                |
|------------------------------|-------------------------------------|---------|----------------|
| Pin No.                      | Function                            | Pin No. | Function       |
| 1                            | 48V Sense+                          | 14      | 48V Ishare     |
| 2                            | Ground                              | 15      | Unit 1 Present |
| 3                            | 48V Sense-                          | 16      | Ground         |
| 4                            | Ground                              | 17      | Unit 2 Present |
| 5                            | PS-EN (Control)                     | 18      | Ground         |
| 6                            | DC1-OK-L                            | 19      | Unit 3 Present |
| 7                            | DC2-OK-L                            | 20      | Ground         |
| 8                            | DC3-OK-L                            | 21      | SCL            |
| 9                            | I <sup>2</sup> C-En-H-1 (Comm-En-H) | 22      | Ground         |
| 10                           | I <sup>2</sup> C-En-H-2 (Comm-En-H) | 23      | SDA            |
| 11                           | I <sup>2</sup> C-En-H-3 (Comm-En-H) | 24      | Ground         |
| 12                           | Ground                              | 25      | SMBALERT#      |
| 13                           | 12V-Aux                             | 26      | N/C            |

| Signal Connector (1 per shelf) |                   |
|--------------------------------|-------------------|
| Shelf Connector                | Mating Connector  |
| Molex: 52986-2679              | Molex: 52316-2619 |
| Tyco: 2-178238-4               | Tyco: 2-5175677-4 |

| AC Input Connector (3 per shelf) |                                  |
|----------------------------------|----------------------------------|
| Shelf Connector                  | Mating Connector                 |
| IEC320 C20 Socket                | IEC320 C20 Plug (Straight Entry) |

| Shelf DIP Switch Table |            |            |
|------------------------|------------|------------|
| Shelf Number           | DIP Switch | DIP Switch |
| 1                      | Up         | Up         |
| 2                      | Up         | Down       |
| 3                      | Down       | Up         |
| 4                      | Down       | Down       |



Figure 1 - Thermal Derating Curve for UFE2000-96S48J Model  
Low Line Input Voltage



Figure 2 - Thermal Derating Curve for UFE2000-96S48J Model  
High Line Input Voltage



Figure 3 - Thermal Derating Curve for UFE1300-96S24J Model  
All Conditions

### Americas

5810 Van Allen Way  
Carlsbad, CA 92008  
USA  
Telephone: +1 760 930 4600  
Facsimile: +1 760 930 0698

### Europe (UK)

Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX  
United Kingdom  
Telephone: +44 (0) 1384 842 211  
Facsimile: +44 (0) 1384 843 355

### Asia (HK)

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
Telephone: +852 2176 3333  
Facsimile: +852 2176 3888

For global contact, visit:

[www.Emerson.com/EmbeddedPower](http://www.Emerson.com/EmbeddedPower)  
[techsupport.embeddedpower@emerson.com](mailto:techsupport.embeddedpower@emerson.com)

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

### Emerson Network Power.

The global leader in enabling  
business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

### EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.  
©2011 Emerson Electric Co.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: org@lifeelectronics.ru