



1	2	3	4	5	6	7	8																																																																											
A	 har-flexicon female connector, horizontal, screwing RoHS compliant 			Cable connection <table><tr><td>Type</td><td>har-flexicon 3.50/3.81 FSH</td><td>har-flexicon 5.00/5.08 FSH</td></tr><tr><td>Part numbers</td><td>1431xx14402xxx & 1431xx15402xxx</td><td>1431xx16402xxx & 1431xx16403xxx / 1431xx17402xxx</td></tr><tr><td>Conductor size AWG max</td><td>14 AWG</td><td>12 AWG</td></tr><tr><td>Conductor size AWG min</td><td>30 AWG</td><td>30 AWG</td></tr><tr><td>Conductor size solid max</td><td>1.5 mm²</td><td>2.5 mm²</td></tr><tr><td>Conductor size solid min</td><td>0.5mm²</td><td>0.05 mm²</td></tr><tr><td>Conductor size stranded max</td><td>1.5 mm²</td><td>2.5 mm²</td></tr><tr><td>Conductor size stranded min</td><td>0.5 mm²</td><td>0.05 mm²</td></tr><tr><td>Conductor size stranded for end sleeve</td><td></td><td></td></tr><tr><td>Stripping length max</td><td>6 mm</td><td>7,5 mm</td></tr><tr><td>Stripping length min</td><td>5 mm</td><td>6 mm</td></tr><tr><td>Screw thread</td><td>M2</td><td>M3</td></tr><tr><td>Tightening Torque max</td><td>0.25 Nm</td><td>0.6 Nm</td></tr><tr><td>Tightening Torque min</td><td>0.2 Nm</td><td>0.5 Nm</td></tr></table>				Type	har-flexicon 3.50/3.81 FSH	har-flexicon 5.00/5.08 FSH	Part numbers	1431xx14402xxx & 1431xx15402xxx	1431xx16402xxx & 1431xx16403xxx / 1431xx17402xxx	Conductor size AWG max	14 AWG	12 AWG	Conductor size AWG min	30 AWG	30 AWG	Conductor size solid max	1.5 mm ²	2.5 mm ²	Conductor size solid min	0.5mm ²	0.05 mm ²	Conductor size stranded max	1.5 mm ²	2.5 mm ²	Conductor size stranded min	0.5 mm ²	0.05 mm ²	Conductor size stranded for end sleeve			Stripping length max	6 mm	7,5 mm	Stripping length min	5 mm	6 mm	Screw thread	M2	M3	Tightening Torque max	0.25 Nm	0.6 Nm	Tightening Torque min	0.2 Nm	0.5 Nm	A																																
Type	har-flexicon 3.50/3.81 FSH	har-flexicon 5.00/5.08 FSH																																																																																
Part numbers	1431xx14402xxx & 1431xx15402xxx	1431xx16402xxx & 1431xx16403xxx / 1431xx17402xxx																																																																																
Conductor size AWG max	14 AWG	12 AWG																																																																																
Conductor size AWG min	30 AWG	30 AWG																																																																																
Conductor size solid max	1.5 mm ²	2.5 mm ²																																																																																
Conductor size solid min	0.5mm ²	0.05 mm ²																																																																																
Conductor size stranded max	1.5 mm ²	2.5 mm ²																																																																																
Conductor size stranded min	0.5 mm ²	0.05 mm ²																																																																																
Conductor size stranded for end sleeve																																																																																		
Stripping length max	6 mm	7,5 mm																																																																																
Stripping length min	5 mm	6 mm																																																																																
Screw thread	M2	M3																																																																																
Tightening Torque max	0.25 Nm	0.6 Nm																																																																																
Tightening Torque min	0.2 Nm	0.5 Nm																																																																																
B	General information <table><tr><td colspan="3">female connector</td></tr><tr><td>Type</td><td>har-flexicon 3.50/3.81 FSH</td><td>har-flexicon 5.00/5.08 FSH</td></tr><tr><td>Part numbers</td><td>1431xx14402xxx / 1431xx15402xxx</td><td>1431xx16402xxx & 1431xx16403xxx / 1431xx17402xxx</td></tr><tr><td>Contact pitch</td><td>3.50 mm / 3.81 mm</td><td>5 mm / 5.08 mm</td></tr><tr><td>No. of contacts</td><td>2-25 poles</td><td>2-25 poles</td></tr><tr><td>Rated surge voltage (II/2)</td><td>2,5 kV</td><td>4 kV (overvoltage cat. II / pollution degree 2)</td></tr><tr><td>Rated surge voltage (III/2)</td><td>2,5 kV</td><td>4 kV (overvoltage cat. III / pollution degree 2)</td></tr><tr><td>Rated surge voltage (III/3)</td><td>2,5 kV</td><td>4 kV (overvoltage cat. III / pollution degree 3)</td></tr><tr><td>Rated Voltage</td><td>300 V</td><td>300 V</td></tr><tr><td>Rated voltage (II/2)</td><td>300 V</td><td>600 V (overvoltage cat. II / pollution degree 2)</td></tr><tr><td>Rated voltage (III/2)</td><td>150 V</td><td>300 V (overvoltage cat. III / pollution degree 2)</td></tr><tr><td>Rated voltage (III/3):</td><td>150 V</td><td>250 V (overvoltage cat. III / pollution degree 3)</td></tr><tr><td>Working current</td><td>11 A</td><td>15 A</td></tr><tr><td>Usegroup B, rated voltage / current</td><td>300 V / 11 A</td><td>300 V / 15 A</td></tr><tr><td>Usegroup C, rated voltage / current</td><td>- / -</td><td>- / -</td></tr><tr><td>Usegroup D, rated voltage / current</td><td>300 V / 11 A</td><td>300 V / 15 A</td></tr><tr><td>Contact resistance</td><td colspan="2">max. 15 mOhm</td></tr><tr><td>Insulation resistance</td><td colspan="2">min. 10⁹ Ohm (500 V DC)</td></tr><tr><td>Temperature range</td><td colspan="2">-40°C ... +110°C</td></tr><tr><td>Termination technology</td><td colspan="2">screwing</td></tr><tr><td>Insertion force</td><td colspan="2">max. 3</td></tr><tr><td>Withdrawal force</td><td colspan="2">min. 1,5</td></tr><tr><td>Hot plugging</td><td colspan="2">No</td></tr><tr><td>Vibration</td><td colspan="2">10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs</td></tr><tr><td>RoHS - compliant</td><td colspan="2">Yes</td></tr><tr><td>UL file</td><td colspan="2">E314677</td></tr></table>			female connector			Type	har-flexicon 3.50/3.81 FSH	har-flexicon 5.00/5.08 FSH	Part numbers	1431xx14402xxx / 1431xx15402xxx	1431xx16402xxx & 1431xx16403xxx / 1431xx17402xxx	Contact pitch	3.50 mm / 3.81 mm	5 mm / 5.08 mm	No. of contacts	2-25 poles	2-25 poles	Rated surge voltage (II/2)	2,5 kV	4 kV (overvoltage cat. II / pollution degree 2)	Rated surge voltage (III/2)	2,5 kV	4 kV (overvoltage cat. III / pollution degree 2)	Rated surge voltage (III/3)	2,5 kV	4 kV (overvoltage cat. III / pollution degree 3)	Rated Voltage	300 V	300 V	Rated voltage (II/2)	300 V	600 V (overvoltage cat. II / pollution degree 2)	Rated voltage (III/2)	150 V	300 V (overvoltage cat. III / pollution degree 2)	Rated voltage (III/3):	150 V	250 V (overvoltage cat. III / pollution degree 3)	Working current	11 A	15 A	Usegroup B, rated voltage / current	300 V / 11 A	300 V / 15 A	Usegroup C, rated voltage / current	- / -	- / -	Usegroup D, rated voltage / current	300 V / 11 A	300 V / 15 A	Contact resistance	max. 15 mOhm		Insulation resistance	min. 10 ⁹ Ohm (500 V DC)		Temperature range	-40°C ... +110°C		Termination technology	screwing		Insertion force	max. 3		Withdrawal force	min. 1,5		Hot plugging	No		Vibration	10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs		RoHS - compliant	Yes		UL file	E314677		B
female connector																																																																																		
Type	har-flexicon 3.50/3.81 FSH	har-flexicon 5.00/5.08 FSH																																																																																
Part numbers	1431xx14402xxx / 1431xx15402xxx	1431xx16402xxx & 1431xx16403xxx / 1431xx17402xxx																																																																																
Contact pitch	3.50 mm / 3.81 mm	5 mm / 5.08 mm																																																																																
No. of contacts	2-25 poles	2-25 poles																																																																																
Rated surge voltage (II/2)	2,5 kV	4 kV (overvoltage cat. II / pollution degree 2)																																																																																
Rated surge voltage (III/2)	2,5 kV	4 kV (overvoltage cat. III / pollution degree 2)																																																																																
Rated surge voltage (III/3)	2,5 kV	4 kV (overvoltage cat. III / pollution degree 3)																																																																																
Rated Voltage	300 V	300 V																																																																																
Rated voltage (II/2)	300 V	600 V (overvoltage cat. II / pollution degree 2)																																																																																
Rated voltage (III/2)	150 V	300 V (overvoltage cat. III / pollution degree 2)																																																																																
Rated voltage (III/3):	150 V	250 V (overvoltage cat. III / pollution degree 3)																																																																																
Working current	11 A	15 A																																																																																
Usegroup B, rated voltage / current	300 V / 11 A	300 V / 15 A																																																																																
Usegroup C, rated voltage / current	- / -	- / -																																																																																
Usegroup D, rated voltage / current	300 V / 11 A	300 V / 15 A																																																																																
Contact resistance	max. 15 mOhm																																																																																	
Insulation resistance	min. 10 ⁹ Ohm (500 V DC)																																																																																	
Temperature range	-40°C ... +110°C																																																																																	
Termination technology	screwing																																																																																	
Insertion force	max. 3																																																																																	
Withdrawal force	min. 1,5																																																																																	
Hot plugging	No																																																																																	
Vibration	10-150Hz,0,35mm,5g 2h each axes -> No contact disturbance > 1µs																																																																																	
RoHS - compliant	Yes																																																																																	
UL file	E314677																																																																																	
C	Packging unit <table><tr><td>Type of packaging</td><td>No. of poles (xx)</td><td>Quantity</td><td>MOQ</td><td>Index (xxx)</td><td>Remark</td></tr><tr><td>box</td><td>2</td><td>300</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>3</td><td>200</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>4 - 5</td><td>150</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>6 - 12</td><td>100</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>13 - 20</td><td>50</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>21 - 25</td><td>25</td><td>1</td><td>000</td><td></td></tr></table> 1431xx14402xxx 1431xx16402xxx			Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark	box	2	300	1	000		box	3	200	1	000		box	4 - 5	150	1	000		box	6 - 12	100	1	000		box	13 - 20	50	1	000		box	21 - 25	25	1	000		C																																				
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark																																																																													
box	2	300	1	000																																																																														
box	3	200	1	000																																																																														
box	4 - 5	150	1	000																																																																														
box	6 - 12	100	1	000																																																																														
box	13 - 20	50	1	000																																																																														
box	21 - 25	25	1	000																																																																														
D	Isulator material <table><tr><td>Material</td><td>PA/PPA</td></tr><tr><td>Color</td><td>green</td></tr><tr><td>UL classification</td><td>UL 94-V0</td></tr><tr><td>Material group acc. to IEC 60664-1</td><td>I (CTI > 600)</td></tr></table>			Material	PA/PPA	Color	green	UL classification	UL 94-V0	Material group acc. to IEC 60664-1	I (CTI > 600)	D																																																																						
Material	PA/PPA																																																																																	
Color	green																																																																																	
UL classification	UL 94-V0																																																																																	
Material group acc. to IEC 60664-1	I (CTI > 600)																																																																																	
E	Contact material <table><tr><td>Contact material</td><td>Copper alloy</td></tr><tr><td>Plating termination zone</td><td>Ni</td></tr><tr><td>Plating contact zone</td><td>Sn</td></tr></table>			Contact material	Copper alloy	Plating termination zone	Ni	Plating contact zone	Sn	E																																																																								
Contact material	Copper alloy																																																																																	
Plating termination zone	Ni																																																																																	
Plating contact zone	Sn																																																																																	
F	Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Derating: har-flexicon 3.50/3.81 FSH:  Derating: har-flexicon 5.00/5.08 FSH: 			F																																																																														
1	2	3	4	5	6	7	8																																																																											

 All Dimensions in mm Original Size DIN A3	Scale 1:1	Free size tol.	Ref. Sub. DS 14312301201 / 500000077827 / 2014-07-31			
 All rights reserved Department EC PD - DE	Created by TADJE	Inspected by LEHNERT	Standardisation HOFFMANN	Date 2015-10-15	State Final Release	
HARTING Electronics GmbH D-32339 Espelkamp	Title har-flexicon female connector, horizontal, screwing			Doc-Key / ECM-Nr. 100579839/UGD/000/C 500000093564		
	Type DS	Number 14312301201			Rev. C	Page 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[14310214402000](#) [14310316402000](#) [14310414402000](#) [14311016402000](#) [14311214402000](#) [14310216402000](#)
[14310416402000](#) [14310616402000](#) [14310314402000](#) [14311216402000](#) [14310516402000](#) [14310614402000](#)
[14310816402000](#) [14310814402000](#) [14311014402000](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru