

# NL27WZ125

## Dual Buffer with 3-State Outputs

The NL27WZ125 is a high performance dual noninverting buffer operating from a 1.65 V to 5.5 V  $V_{CC}$  supply.

### Features

- Extremely High Speed:  $t_{PD}$  2.6 ns (typical) at  $V_{CC} = 5$  V
- Designed for 1.65 V to 5.5 V  $V_{CC}$  Operation
- Over Voltage Tolerant Inputs and Outputs
- LVTTTL Compatible – Interface Capability With 5 V TTL Logic with  $V_{CC} = 3$  V
- LVC MOS Compatible
- 24 mA Balanced Output Sink and Source Capability
- Near Zero Static Supply Current Substantially Reduces System Power Requirements
- 3-State OE Input is Active-Low
- Replacement for NC7WZ125
- Chip Complexity = 72 FETs
- These Devices are Pb-Free and are RoHS Compliant




Figure 1. Pinout (Top View)





Figure 2. Logic Symbol




ON Semiconductor®

<http://onsemi.com>



US8  
US SUFFIX  
CASE 493

### MARKING DIAGRAM



M0 = Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation may vary depending upon manufacturing location.

### PIN ASSIGNMENT

| Pin | Function          |
|-----|-------------------|
| 1   | $\overline{OE}_1$ |
| 2   | $A_1$             |
| 3   | $Y_2$             |
| 4   | GND               |
| 5   | $A_2$             |
| 6   | $Y_1$             |
| 7   | $\overline{OE}_2$ |
| 8   | $V_{CC}$          |

### FUNCTION TABLE

| Input             |       | Output |
|-------------------|-------|--------|
| $\overline{OE}_n$ | $A_n$ | $Y_n$  |
| L                 | L     | L      |
| L                 | H     | H      |
| H                 | X     | Z      |

X = Don't Care  
n = 1, 2

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

## MAXIMUM RATINGS

| Symbol        | Parameter                                                                                                     | Value                                  | Units |
|---------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------|-------|
| $V_{CC}$      | DC Supply Voltage                                                                                             | -0.5 to +7.0                           | V     |
| $V_I$         | DC Input Voltage                                                                                              | -0.5 to +7.0                           | V     |
| $V_O$         | DC Output Voltage<br>Output in High Impedance State<br>Output in HIGH or LOW State                            | -0.5 to +7.0<br>-0.5 to $V_{CC} + 0.5$ | V     |
| $I_{IK}$      | DC Input Diode Current, $V_I < GND$                                                                           | -50                                    | mA    |
| $I_{OK}$      | DC Output Diode Current, $V_O < GND$                                                                          | -50                                    | mA    |
| $I_O$         | DC Output Sink Current                                                                                        | $\pm 50$                               | mA    |
| $I_{CC}$      | DC Supply Current per Supply Pin                                                                              | $\pm 100$                              | mA    |
| $I_{GND}$     | DC Ground Current per Ground Pin                                                                              | $\pm 100$                              | mA    |
| $T_{STG}$     | Storage Temperature Range                                                                                     | -65 to +150                            | °C    |
| $T_L$         | Lead Temperature, 1 mm from Case for 10 Seconds                                                               | 260                                    | °C    |
| $T_J$         | Junction Temperature under Bias                                                                               | +150                                   | °C    |
| $\theta_{JA}$ | Thermal Resistance (Note 1)                                                                                   | 250                                    | °C/W  |
| $P_D$         | Power Dissipation in Still Air at 85°C                                                                        | 250                                    | mW    |
| MSL           | Moisture Sensitivity                                                                                          | Level 1                                |       |
| $F_R$         | Flammability Rating – Oxygen Index: 28 to 34                                                                  | UL 94 V-0 @ 0.125 in                   |       |
| $V_{ESD}$     | ESD Withstand Voltage<br>Human Body Model (Note 2)<br>Machine Model (Note 3)<br>Charged Device Model (Note 4) | > 2000<br>> 200<br>N/A                 | V     |
| $I_{LATCHUP}$ | Latchup Performance Above $V_{CC}$ and Below GND at 125°C (Note 5)                                            | $\pm 100$                              | mA    |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to JESD22-C101-A.
5. Tested to EIA/JESD78.

## RECOMMENDED OPERATING CONDITIONS

| Symbol              | Parameter                                                                                                                                                              | Min         | Max           | Units |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------------|-------|
| $V_{CC}$            | Supply Voltage<br>Operating<br>Data Retention Only                                                                                                                     | 1.65<br>1.5 | 5.5<br>5.5    | V     |
| $V_I$               | Input Voltage (Note 6)                                                                                                                                                 | 0           | 5.5           | V     |
| $V_O$               | Output Voltage (HIGH or LOW State)                                                                                                                                     | 0           | 5.5           | V     |
| $T_A$               | Operating Free-Air Temperature                                                                                                                                         | -55         | +125          | °C    |
| $\Delta t/\Delta V$ | Input Transition Rise or Fall Rate<br>$V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$<br>$V_{CC} = 3.0\text{ V} \pm 0.3\text{ V}$<br>$V_{CC} = 5.0\text{ V} \pm 0.5\text{ V}$ | 0<br>0<br>0 | 20<br>10<br>5 | ns/V  |

6. Unused inputs may not be left open. All inputs must be tied to a high- or low-logic input voltage level.

## DEVICE ORDERING INFORMATION

| Device Order Number | Package Type     | Shipping <sup>†</sup> |
|---------------------|------------------|-----------------------|
| NL27WZ125USG        | US8<br>(Pb-Free) | 3000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

DC ELECTRICAL CHARACTERISTICS

| Symbol           | Parameter                                                                         | Condition                                                                                                                                                                                      | V <sub>CC</sub><br>(V)                                 | T <sub>A</sub> = 25°C                                            |                                                            |                                                  | -55°C ≤ T <sub>A</sub> ≤ 125°C                                   |                                                  | Units |
|------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------|--------------------------------------------------|------------------------------------------------------------------|--------------------------------------------------|-------|
|                  |                                                                                   |                                                                                                                                                                                                |                                                        | Min                                                              | Typ                                                        | Max                                              | Min                                                              | Max                                              |       |
| V <sub>IH</sub>  | High-Level Input Voltage                                                          |                                                                                                                                                                                                | 1.65<br>2.3 to 5.5                                     | 0.75 V <sub>CC</sub><br>0.7 V <sub>CC</sub>                      |                                                            |                                                  | 0.75 V <sub>CC</sub><br>0.7 V <sub>CC</sub>                      |                                                  | V     |
| V <sub>IL</sub>  | Low-Level Input Voltage                                                           |                                                                                                                                                                                                | 1.65<br>2.3 to 5.5                                     |                                                                  |                                                            | 0.25 V <sub>CC</sub><br>0.3 V <sub>CC</sub>      |                                                                  | 0.25 V <sub>CC</sub><br>0.3 V <sub>CC</sub>      | V     |
| V <sub>OH</sub>  | High-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> | I <sub>OH</sub> = 100 μA<br>I <sub>OH</sub> = -3 mA<br>I <sub>OH</sub> = -8 mA<br>I <sub>OH</sub> = -12 mA<br>I <sub>OH</sub> = -16 mA<br>I <sub>OH</sub> = -24 mA<br>I <sub>OH</sub> = -32 mA | 1.65 to 5.5<br>1.65<br>2.3<br>2.7<br>3.0<br>3.0<br>4.5 | V <sub>CC</sub> - 0.1<br>1.29<br>1.9<br>2.2<br>2.4<br>2.3<br>3.8 | V <sub>CC</sub><br>1.52<br>2.1<br>2.4<br>2.7<br>2.5<br>4.0 |                                                  | V <sub>CC</sub> - 0.1<br>1.29<br>1.9<br>2.2<br>2.4<br>2.3<br>3.8 |                                                  | V     |
| V <sub>OL</sub>  | Low-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IL</sub>                     | I <sub>OL</sub> = 100 μA<br>I <sub>OL</sub> = 3 mA<br>I <sub>OL</sub> = 8 mA<br>I <sub>OL</sub> = 12 mA<br>I <sub>OL</sub> = 16 mA<br>I <sub>OL</sub> = 24 mA<br>I <sub>OL</sub> = 32 mA       | 1.65 to 5.5<br><br>2.3<br>2.7<br>3.0<br>3.0<br>4.5     |                                                                  | 0.08<br>0.20<br>0.22<br>0.28<br>0.38<br>0.42               | 0.1<br>0.24<br>0.3<br>0.4<br>0.4<br>0.55<br>0.55 |                                                                  | 0.1<br>0.24<br>0.3<br>0.4<br>0.4<br>0.55<br>0.55 | V     |
| I <sub>IN</sub>  | Input Leakage Current                                                             | V <sub>IN</sub> = 5.5V or GND                                                                                                                                                                  | 0 to 5.5                                               |                                                                  |                                                            | ±0.1                                             |                                                                  | ±1.0                                             | μA    |
| I <sub>OFF</sub> | Power Off Leakage Current                                                         | V <sub>IN</sub> = 5.5 V or<br>V <sub>OUT</sub> = 5.5 V                                                                                                                                         | 0                                                      |                                                                  |                                                            | 1.0                                              |                                                                  | 10                                               | μA    |
| I <sub>CC</sub>  | Quiescent Supply Current                                                          | V <sub>IN</sub> = 5.5V or GND                                                                                                                                                                  | 5.5                                                    |                                                                  |                                                            | 1.0                                              |                                                                  | 10                                               | μA    |
| I <sub>OZ</sub>  | 3-State Output Leakage                                                            | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>0V ≤ V <sub>OUT</sub> ≤ 5.5 V                                                                                                          | 2.3 to 5.5                                             |                                                                  |                                                            | ±0.5                                             |                                                                  | ±5                                               | μA    |

AC ELECTRICAL CHARACTERISTICS (t<sub>R</sub> = t<sub>F</sub> = 3.0 ns)

| Symbol                                 | Parameter                                          | Condition                                                                                       | V <sub>CC</sub><br>(V)  | T <sub>A</sub> = 25°C |     |            | -55°C ≤ T <sub>A</sub> ≤ 125°C |            | Units |
|----------------------------------------|----------------------------------------------------|-------------------------------------------------------------------------------------------------|-------------------------|-----------------------|-----|------------|--------------------------------|------------|-------|
|                                        |                                                    |                                                                                                 |                         | Min                   | Typ | Max        | Min                            | Max        |       |
| t <sub>PLH</sub><br>t <sub>PHL</sub>   | Propagation Delay<br>AN to YN<br>(Figures 3 and 4) | R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF                                                   | 1.8 ± 0.15<br>2.5 ± 0.2 | 2.0<br>1.0            |     | 12<br>7.5  | 2.0<br>1.0                     | 13<br>8    | ns    |
|                                        |                                                    | R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 50 pF | 3.3 ± 0.3               | 0.8<br>1.2            |     | 5.2<br>5.7 | 0.8<br>1.2                     | 5.5<br>6.0 |       |
|                                        |                                                    | R <sub>L</sub> = 1 MΩ, C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 50 pF | 5.0 ± 0.5               | 0.5<br>0.8            |     | 4.5<br>5.0 | 0.5<br>0.8                     | 4.8<br>5.3 |       |
| t <sub>OSLH</sub><br>t <sub>OSHL</sub> | Output to Output Skew<br>(Note 7)                  | R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 50 pF                                                  | 3.3 ± 0.3               |                       |     | 1.0        |                                | 1.0        | ns    |
|                                        |                                                    | R <sub>L</sub> = 500 Ω, C <sub>L</sub> = 50 pF                                                  | 5.0 ± 0.5               |                       |     | 0.8        |                                | 0.8        |       |
| t <sub>PZH</sub><br>t <sub>PZL</sub>   | Output Enable Time<br>(Figures 5, 6 and 7)         |                                                                                                 | 1.8 ± 0.15<br>2.5 ± 0.2 | 3.0<br>1.8            |     | 14<br>8.5  | 3.0<br>1.8                     | 15<br>9.0  | ns    |
|                                        |                                                    |                                                                                                 | 3.3 ± 0.3               | 1.2                   |     | 6.2        | 1.2                            | 6.5        |       |
|                                        |                                                    |                                                                                                 | 5.0 ± 0.5               | 0.8                   |     | 5.5        | 0.8                            | 5.8        |       |
| t <sub>PHZ</sub><br>t <sub>PLZ</sub>   | Output Enable Time<br>(Figures 5, 6 and 7)         |                                                                                                 | 1.8 ± 0.15<br>2.5 ± 0.2 | 2.5<br>1.5            |     | 12<br>8.0  | 2.5<br>1.5                     | 13<br>8.5  | ns    |
|                                        |                                                    |                                                                                                 | 3.3 ± 0.3               | 0.8                   |     | 5.7        | 0.8                            | 6.0        |       |
|                                        |                                                    |                                                                                                 | 5.0 ± 0.5               | 0.3                   |     | 4.7        | 0.3                            | 5.0        |       |

7. Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. This specification applies to any outputs switching in the same direction, either HIGH-to-LOW (t<sub>OSHL</sub>) or LOW-to-HIGH (t<sub>OSLH</sub>); parameter guaranteed by design.

# CAPACITIVE CHARACTERISTICS

| Symbol    | Parameter                              | Condition                                                                                                                                | Typical  | Units |
|-----------|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|----------|-------|
| $C_{IN}$  | Input Capacitance                      | $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$                                                                               | 7.0      | pF    |
| $C_{OUT}$ | Output Capacitance                     | $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$                                                                               | 7.0      | pF    |
| $C_{PD}$  | Power Dissipation Capacitance (Note 8) | 10 MHz, $V_{CC} = 3.3 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$<br>10 MHz, $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$ | 18<br>27 | pF    |

8.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:  $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}$ .  $C_{PD}$  is used to determine the no-load dynamic power consumption;  $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$ .





Figure 3. Switching Waveform



\*Includes all probe and jig capacitance.  
A 1 MHz square input wave is recommended for propagation delay tests.

Figure 4.  $T_{PLH}$  or  $T_{PHL}$






Figure 5. AC Output Enable and Disable Waveform



A 1 MHz square input wave is recommended for propagation delay tests.

Figure 6.  $T_{PZL}$  or  $T_{PL}$




A 1 MHz square input wave is recommended for propagation delay tests.

Figure 7.  $T_{PZH}$  or  $T_{PHZ}$

# NL27WZ125

## PACKAGE DIMENSIONS

US8  
CASE 493-02  
ISSUE B




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION "A" DOES NOT INCLUDE MOLD FLASH, PROTRUSION OR GATE BURR. MOLD FLASH, PROTRUSION AND GATE BURR SHALL NOT EXCEED 0.140 MM (0.0055") PER SIDE.
4. DIMENSION "B" DOES NOT INCLUDE INTER-LEAD FLASH OR PROTRUSION. INTER-LEAD FLASH AND PROTRUSION SHALL NOT EXCEED 0.140 (0.0055") PER SIDE.
5. LEAD FINISH IS SOLDER PLATING WITH THICKNESS OF 0.0076-0.0203 MM. (300-800 ").
6. ALL TOLERANCE UNLESS OTHERWISE SPECIFIED  $\pm 0.0508$  (0.002 ").

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 1.90        | 2.10 | 0.075     | 0.083 |
| B   | 2.20        | 2.40 | 0.087     | 0.094 |
| C   | 0.60        | 0.90 | 0.024     | 0.035 |
| D   | 0.17        | 0.25 | 0.007     | 0.010 |
| F   | 0.20        | 0.35 | 0.008     | 0.014 |
| G   | 0.50 BSC    |      | 0.020 BSC |       |
| H   | 0.40 REF    |      | 0.016 REF |       |
| J   | 0.10        | 0.18 | 0.004     | 0.007 |
| K   | 0.00        | 0.10 | 0.000     | 0.004 |
| L   | 3.00        | 3.20 | 0.118     | 0.126 |
| M   | 0°          | 6°   | 0°        | 6°    |
| N   | 5°          | 10°  | 5°        | 10°   |
| P   | 0.23        | 0.34 | 0.010     | 0.013 |
| R   | 0.23        | 0.33 | 0.009     | 0.013 |
| S   | 0.37        | 0.47 | 0.015     | 0.019 |
| U   | 0.60        | 0.80 | 0.024     | 0.031 |
| V   | 0.12 BSC    |      | 0.005 BSC |       |

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

NL27WZ125/D

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)