

## 200V Low Charge Injection 8-Channel High Voltage Analog Switch

### Features

- ▶ HVCMOS® technology for high performance
- ▶ Very low quiescent power dissipation ( $\sim 10\mu\text{A}$ )
- ▶ Output on-resistance typically  $11\Omega$
- ▶ Low parasitic capacitance
- ▶ DC to 50MHz small signal frequency response
- ▶ -60dB typical off-isolation at 5.0MHz
- ▶ CMOS logic circuitry for low power
- ▶ Excellent noise immunity
- ▶ Serial shift register logic control with latches
- ▶ Flexible operating supply voltages
- ▶ Surface mount packages

### Applications

- ▶ Medical ultrasound imaging
- ▶ Non-destructive evaluation


### General Description

The Supertex HV219 is a low switch resistance, low charge injection, 8-channel, 200V, analog switch integrated circuit (IC) intended primarily for medical ultrasound imaging. The device can also be used for NDE (non-destructive evaluation) applications. The HV219 is a lower switch resistance,  $11\Omega$  versus  $22\Omega$ , version of the Supertex HV20220 device. The lower switch resistance will help reduce insertion loss. It has the same pin configuration as that of the Supertex HV20220PJ and the HV20220FG.

The device is manufactured using Supertex's HVCMOS® (high voltage CMOS) technology with high voltage bilateral DMOS structures for the outputs and low voltage CMOS logic for the input control. The outputs are configured as eight independent single pole single throw  $11\Omega$  analog switches. The input logic is an 8-bit serial to parallel shift register followed by an 8-bit parallel latch. The switch states are determined by the data in the latch. Logic high will correspond to a closed switch and logic low as an opened switch.

The HV219 is designed to operate on various combinations of high voltage supplies. For example the  $V_{PP}$  and  $V_{NN}$  supplies can be: +40V/-160V, +100V/-100V, or +160V/-40V. This allows the user to maximize the signal voltage for uni-polar negative, bi-polar, or uni-polar positive.

### Block Diagram



## Ordering Information

| Part Number    | Package Option | Packing   |
|----------------|----------------|-----------|
| HV219FG-G      | 48-Lead LQFP   | 250/Tray  |
| HV219FG-G M931 |                | 1000/Reel |
| HV219PJ-G      | 28-Lead PLCC   | 38/Tube   |
| HV219PJ-G M904 |                | 500/Reel  |

-G denotes a lead (Pb)-free / RoHS compliant package

## Absolute Maximum Ratings

| Parameter                             | Value                    |
|---------------------------------------|--------------------------|
| $V_{DD}$ logic power supply voltage   | -0.5V to +15V            |
| $V_{PP} - V_{NN}$ supply voltage      | 220V                     |
| $V_{PP}$ positive high voltage supply | -0.5V to $V_{NN} + 200V$ |
| $V_{NN}$ negative high voltage supply | +0.5V to -200V           |
| Logic input voltages                  | -0.5V to $V_{DD} + 0.3V$ |
| Analog signal range                   | $V_{NN}$ to $V_{PP}$     |
| Peak analog signal current/channel    | 3.0A                     |
| Storage temperature                   | -65°C to +150°C          |
| Power dissipation:<br>28-Lead PLCC    | 1.2W                     |
| 48-Lead LQFP                          | 1.0W                     |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.


## Operating Conditions

| Sym       | Parameter                          | Value                            |
|-----------|------------------------------------|----------------------------------|
| $V_{DD}$  | Logic power supply voltage         | 4.5V to 13.2V                    |
| $V_{PP}$  | Positive high voltage supply       | 40V to $V_{NN} + 200V$           |
| $V_{NN}$  | Negative high voltage supply       | -40V to -160V                    |
| $V_{IH}$  | High level input logic voltage     | $V_{DD} - 1.5V$ to $V_{DD}$      |
| $V_{IL}$  | Low-level input logic voltage      | 0V to 1.5V                       |
| $V_{SIG}$ | Analog signal voltage peak-to-peak | $V_{NN} + 10V$ to $V_{PP} - 10V$ |
| $T_A$     | Operating free air temperature     | 0°C to 70°C                      |


## Power Up/Down Sequence

1. Power up/down sequence is arbitrary except GND must be powered up first and powered down last. This applies for applications powering GND of the IC with different voltages.
2.  $V_{SIG}$  must always be at or in between  $V_{PP}$  and  $V_{NN}$  or floating during power up/down transition.
3. Rise and fall times of the power supplies  $V_{DD}$ ,  $V_{PP}$  and  $V_{NN}$  should not be less than 1.0ms.

## Pin Configuration



**48-Lead LQFP**  
(top view)



**28-Lead PLCC**  
(top view)

## Product Marking

Top Marking



YY = Year Sealed  
WW = Week Sealed  
L = Lot Number  
C = Country of Origin\*  
A = Assembler ID\*  
— = "Green" Packaging  
\*May be part of top marking

Bottom Marking



Package may or may not include the following marks: Si or

**48-Lead LQFP**

Top Marking



YY = Year Sealed  
WW = Week Sealed  
L = Lot Number  
C = Country of Origin\*  
A = Assembler ID\*  
— = "Green" Packaging  
\*May be part of top marking

Bottom Marking



Package may or may not include the following marks: Si or

**28-Lead PLCC**

## Typical Thermal Resistance

| Package      | $\theta_{ja}$ |
|--------------|---------------|
| 48-Lead LQFP | 52°C/W        |
| 28-Lead PLCC | 48°C/W        |

# DC Electrical Characteristics (over recommended operating conditions unless otherwise noted)

| Sym               | Parameter                                  | 0°C  |     | +25°C |      |     | +70°C |     | Units | Conditions                                                                 |                                                                  |
|-------------------|--------------------------------------------|------|-----|-------|------|-----|-------|-----|-------|----------------------------------------------------------------------------|------------------------------------------------------------------|
|                   |                                            | Min  | Max | Min   | Typ  | Max | Min   | Max |       |                                                                            |                                                                  |
| R <sub>ONS</sub>  | Small signal switch on-resistance          | -    | 15  | -     | 13   | 19  | -     | 24  | Ω     | I <sub>SIG</sub> = 5.0mA                                                   | V <sub>PP</sub> = +40V                                           |
|                   |                                            | -    | 13  | -     | 11   | 14  | -     | 16  |       | I <sub>SIG</sub> = 200mA                                                   | V <sub>NN</sub> = -160V                                          |
|                   |                                            | -    | 13  | -     | 11   | 14  | -     | 15  |       | I <sub>SIG</sub> = 5.0mA                                                   | V <sub>PP</sub> = +100V                                          |
|                   |                                            | -    | 9.0 | -     | 9.0  | 12  | -     | 14  |       | I <sub>SIG</sub> = 200mA                                                   | V <sub>NN</sub> = -100V                                          |
|                   |                                            | -    | 12  | -     | 10   | 13  | -     | 15  |       | I <sub>SIG</sub> = 5.0mA                                                   | V <sub>PP</sub> = +160V                                          |
|                   |                                            | -    | 11  | -     | 8    | 13  | -     | 14  |       | I <sub>SIG</sub> = 200mA                                                   | V <sub>NN</sub> = -40V                                           |
| ΔR <sub>ONS</sub> | Small signal switch on-resistance matching | -    | 20  | -     | 5.0  | 20  | -     | 20  | %     | I <sub>SIG</sub> = 5.0mA, V <sub>PP</sub> = +100V, V <sub>NN</sub> = -100V |                                                                  |
| R <sub>ONL</sub>  | Large signal switch on-resistance          | -    | -   | -     | 8.0  | -   | -     | -   | Ω     | V <sub>SIG</sub> = V <sub>PP</sub> -10V, I <sub>SIG</sub> = 1.0A           |                                                                  |
| I <sub>SOL</sub>  | Switch off leakage per switch              | -    | 5.0 | -     | 1.0  | 10  | -     | 15  | μA    | V <sub>SIG</sub> = V <sub>PP</sub> -10V & V <sub>NN</sub> +10V             |                                                                  |
| V <sub>OS</sub>   | DC offset switch off                       | -    | 300 | -     | 100  | 300 | -     | 300 | mV    | R <sub>LOAD</sub> = 100kΩ                                                  |                                                                  |
|                   | DC offset switch on                        | -    | 500 | -     | 100  | 500 | -     | 500 | mV    | R <sub>LOAD</sub> = 100kΩ                                                  |                                                                  |
| I <sub>PPQ</sub>  | Quiescent V <sub>PP</sub> supply current   | -    | -   | -     | 10   | 50  | -     | -   | μA    | All switches off                                                           |                                                                  |
| I <sub>NNQ</sub>  | Quiescent V <sub>NN</sub> supply current   | -    | -   | -     | -10  | -50 | -     | -   | μA    | All switches off                                                           |                                                                  |
| I <sub>PPQ</sub>  | Quiescent V <sub>PP</sub> supply current   | -    | -   | -     | 10   | 50  | -     | -   | μA    | All switches on, I <sub>SW</sub> = 5.0mA                                   |                                                                  |
| I <sub>NNQ</sub>  | Quiescent V <sub>NN</sub> supply current   | -    | -   | -     | -10  | -50 | -     | -   | μA    | All switches on, I <sub>SW</sub> = 5.0mA                                   |                                                                  |
| I <sub>SW</sub>   | Switch output peak current                 | -    | 3.0 | -     | 3.0  | 2.0 | -     | 2.0 | A     | V <sub>SIG</sub> duty cycle < 0.1%                                         |                                                                  |
| f <sub>SW</sub>   | Output switch frequency                    | -    | -   | -     | -    | 50  | -     | -   | kHz   | Duty cycle = 50%                                                           |                                                                  |
| I <sub>PP</sub>   | Average V <sub>PP</sub> supply current     | -    | 6.5 | -     | -    | 7.0 | -     | 8.0 | mA    | V <sub>PP</sub> = +40V<br>V <sub>NN</sub> = -160V                          | All output switches are turning on and off at 50kHz with no load |
|                   |                                            | -    | 4.0 | -     | -    | 5.0 | -     | 5.5 |       | V <sub>PP</sub> = +100V<br>V <sub>NN</sub> = -100V                         |                                                                  |
|                   |                                            | -    | 4.0 | -     | -    | 5.0 | -     | 5.5 |       | V <sub>PP</sub> = +160V<br>V <sub>NN</sub> = -40V                          |                                                                  |
| I <sub>NN</sub>   | Average V <sub>NN</sub> supply current     | -    | 6.5 | -     | -    | 7.0 | -     | 8.0 | mA    | V <sub>PP</sub> = +40V<br>V <sub>NN</sub> = -160V                          | All output switches are turning on and off at 50kHz with no load |
|                   |                                            | -    | 4.0 | -     | -    | 5.0 | -     | 5.5 |       | V <sub>PP</sub> = +100V<br>V <sub>NN</sub> = -100V                         |                                                                  |
|                   |                                            | -    | 4.0 | -     | -    | 5.0 | -     | 5.5 |       | V <sub>PP</sub> = +160V<br>V <sub>NN</sub> = -40V                          |                                                                  |
| I <sub>DD</sub>   | Average V <sub>DD</sub> supply current     | -    | 4.0 | -     | -    | 4.0 | -     | 4.0 | mA    | f <sub>CLK</sub> = 5.0MHz, V <sub>DD</sub> = 5.0V                          |                                                                  |
| I <sub>DDQ</sub>  | Quiescent V <sub>DD</sub> supply current   | -    | 10  | -     | -    | 10  | -     | 10  | μA    | All logic inputs are static                                                |                                                                  |
| I <sub>SOR</sub>  | Data out source current                    | 0.45 | -   | 0.45  | 0.70 | -   | 0.40  | -   | mA    | V <sub>OUT</sub> = V <sub>DD</sub> -0.7V                                   |                                                                  |
| I <sub>SINK</sub> | Data out sink current                      | 0.45 | -   | 0.45  | 0.70 | -   | 0.40  | -   | mA    | V <sub>OUT</sub> = 0.7V                                                    |                                                                  |
| C <sub>IN</sub>   | Large input capacitance                    | -    | 10  | -     | -    | 10  | -     | 10  | pF    | ---                                                                        |                                                                  |

# AC Electrical Characteristics (over recommended operating conditions, $V_{DD} = 5.0V$ , unless otherwise noted)

| Sym           | Parameter                                | 0°C |     | +25°C |      |     | +70°C |     | Units   | Conditions                                                  |
|---------------|------------------------------------------|-----|-----|-------|------|-----|-------|-----|---------|-------------------------------------------------------------|
|               |                                          | Min | Max | Min   | Typ  | Max | Min   | Max |         |                                                             |
| $t_{SD}$      | Set-up time before $\overline{LE}$ rises | 150 | -   | 150   | -    | -   | 150   | -   | ns      | ---                                                         |
| $t_{WLE}$     | Time width of $\overline{LE}$            | 150 | -   | 150   | -    | -   | 150   | -   | ns      | ---                                                         |
| $t_{DO}$      | Clock delay time to data out             | -   | 150 | -     | -    | 150 | -     | 150 | ns      | ---                                                         |
| $t_{WCL}$     | Time width of CL                         | 150 | -   | 150   | -    | -   | 150   | -   | ns      | ---                                                         |
| $t_{SU}$      | Set-up time data to clock                | 15  | -   | 15    | 8.0  | -   | 20    | -   | ns      | ---                                                         |
| $t_H$         | Hold time data from clock                | 35  | -   | 35    | -    | -   | 35    | -   | ns      | ---                                                         |
| $f_{CLK}$     | Clock frequency                          | -   | 5.0 | -     | -    | 5.0 | -     | 5.0 | MHz     | 50% duty cycle,<br>$f_{DATA} = f_{CLK}/2$                   |
| $t_r, t_f$    | Clock rise and fall times                | -   | 50  | -     | -    | 50  | -     | 50  | ns      | ---                                                         |
| $T_{ON}$      | Turn-on time                             | -   | 5.0 | -     | -    | 5.0 | -     | 5.0 | $\mu s$ | $V_{SIG} = V_{PP} - 10V$ ,<br>$R_{LOAD} = 10k\Omega$        |
| $T_{OFF}$     | Turn-off time                            | -   | 5.0 | -     | -    | 5.0 | -     | 5.0 | $\mu s$ |                                                             |
| dv/dt         | Maximum $V_{SIG}$ slew rate              | -   | 20  | -     | -    | 20  | -     | 20  | V/ns    | $V_{PP} = +40V, V_{NN} = -160V$                             |
|               |                                          | -   | 20  | -     | -    | 20  | -     | 20  |         | $V_{PP} = +100V, V_{NN} = -100V$                            |
|               |                                          | -   | 20  | -     | -    | 20  | -     | 20  |         | $V_{PP} = +160V, V_{NN} = -40V$                             |
| $K_O$         | Off isolation                            | -30 | -   | -30   | -33  | -   | -     | -   | dB      | $f = 5.0MHz$ ,<br>1.0K $\Omega$ //15pF load                 |
|               |                                          | -58 | -   | -58   | -    | -   | -     | -   |         | $f = 5.0MHz$ , 50 $\Omega$ load                             |
| $K_{CR}$      | Switch crosstalk                         | -   | -   | -60   | -    | -   | -     | -   | dB      | $f = 5.0MHz$ , 50 $\Omega$ load                             |
| $I_{ID}$      | Output switch isolation diode current    | -   | 300 | -     | -    | 300 | -     | 300 | mA      | 300ns pulse width,<br>2% duty cycle                         |
| $C_{SG(OFF)}$ | Off capacitance SW to GND                | 14  | 25  | 14    | 20   | 25  | 14    | 25  | pF      | 0V, $f = 1.0MHz$                                            |
| $C_{SG(ON)}$  | On capacitance SW to GND                 | 40  | 60  | 40    | 50   | 60  | 40    | 60  | pF      | 0V, $f = 1.0MHz$                                            |
| $+V_{SPK}$    | Output voltage spike                     | -   | -   | -     | -    | 150 | -     | -   | mV      | $V_{PP} = +40V$ ,<br>$V_{NN} = -160V, R_{LOAD} = 50\Omega$  |
| $-V_{SPK}$    |                                          | -   | -   | -     | -    | 200 | -     | -   |         |                                                             |
| $+V_{SPK}$    |                                          | -   | -   | -     | -    | 150 | -     | -   |         | $V_{PP} = +100V$ ,<br>$V_{NN} = -100V, R_{LOAD} = 50\Omega$ |
| $-V_{SPK}$    |                                          | -   | -   | -     | -    | 200 | -     | -   |         |                                                             |
| $+V_{SPK}$    |                                          | -   | -   | -     | -    | 150 | -     | -   |         | $V_{PP} = +160V$ ,<br>$V_{NN} = -40V, R_{LOAD} = 50\Omega$  |
| $-V_{SPK}$    |                                          | -   | -   | -     | -    | 200 | -     | -   |         |                                                             |
| QC            | Charge injection                         | -   | -   | -     | 1450 | -   | -     | -   | pC      | $V_{PP} = +40V$ ,<br>$V_{NN} = -160V, V_{SIG} = 0V$         |
|               |                                          | -   | -   | -     | 1050 | -   | -     | -   |         | $V_{PP} = +100V$ ,<br>$V_{NN} = -100V, V_{SIG} = 0V$        |
|               |                                          | -   | -   | -     | 550  | -   | -     | -   |         | $V_{PP} = +160V$ ,<br>$V_{NN} = -40V, V_{SIG} = 0V$         |


## Truth Table

| Data in 8-Bit Shift Register |    |    |    |    |    |    |    | $\overline{LE}$ | CL | Output Switch State |     |     |     |     |     |     |     |
|------------------------------|----|----|----|----|----|----|----|-----------------|----|---------------------|-----|-----|-----|-----|-----|-----|-----|
| D0                           | D1 | D2 | D3 | D4 | D5 | D6 | D7 |                 |    | SW0                 | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 |
| L                            |    |    |    |    |    |    |    | L               | L  | OFF                 |     |     |     |     |     |     |     |
| H                            |    |    |    |    |    |    |    | L               | L  | ON                  |     |     |     |     |     |     |     |
|                              | L  |    |    |    |    |    |    | L               | L  |                     | OFF |     |     |     |     |     |     |
|                              | H  |    |    |    |    |    |    | L               | L  |                     | ON  |     |     |     |     |     |     |
|                              |    | L  |    |    |    |    |    | L               | L  |                     |     | OFF |     |     |     |     |     |
|                              |    | H  |    |    |    |    |    | L               | L  |                     |     | ON  |     |     |     |     |     |
|                              |    |    | L  |    |    |    |    | L               | L  |                     |     |     | OFF |     |     |     |     |
|                              |    |    | H  |    |    |    |    | L               | L  |                     |     |     | ON  |     |     |     |     |
|                              |    |    |    | L  |    |    |    | L               | L  |                     |     |     |     | OFF |     |     |     |
|                              |    |    |    | H  |    |    |    | L               | L  |                     |     |     |     | ON  |     |     |     |
|                              |    |    |    |    | L  |    |    | L               | L  |                     |     |     |     |     | OFF |     |     |
|                              |    |    |    |    | H  |    |    | L               | L  |                     |     |     |     |     | ON  |     |     |
|                              |    |    |    |    |    | L  |    | L               | L  |                     |     |     |     |     |     | OFF |     |
|                              |    |    |    |    |    | H  |    | L               | L  |                     |     |     |     |     |     | ON  |     |
|                              |    |    |    |    |    |    | L  | L               | L  |                     |     |     |     |     |     |     | OFF |
|                              |    |    |    |    |    |    | H  | L               | L  |                     |     |     |     |     |     |     | ON  |
| X                            | X  | X  | X  | X  | X  | X  | X  | H               | L  | Hold Previous State |     |     |     |     |     |     |     |
| X                            | X  | X  | X  | X  | X  | X  | X  | X               | H  | OFF                 | OFF | OFF | OFF | OFF | OFF | OFF | OFF |


### Notes:

1. The eight switches operate independently.
2. Serial data is clocked in on the L to H transition clock.
3. The switches go to a state retaining their present condition at the rising edge of the  $\overline{LE}$ .
4. When  $\overline{LE}$  is low, the shift register data flows through the latch.
5. Shift register clocking has no effect on the switch states if  $\overline{LE}$  is high.
6. The clear input overrides all other inputs.


## Logic Timing Waveforms





## Test Circuits



Switch OFF Leakage




DC Offset ON/OFF


 $T_{ON}/T_{OFF}$  Test Circuit

$$K_o = 20 \log \frac{V_{OUT}}{V_{IN}}$$

OFF Isolation




Isolation Diode Current




$$K_{CR} = 20 \log \frac{V_{OUT}}{V_{IN}}$$

Crosstalk



$$Q = 1000pF \times V_{OUT}$$

Charge Injection



Output Voltage Spike

## Pin Description

### 48-Lead LQFP

| Pin | Name |
|-----|------|
| 1   | SW5  |
| 2   | NC   |
| 3   | SW4  |
| 4   | NC   |
| 5   | SW4  |
| 6   | NC   |
| 7   | NC   |
| 8   | SW3  |
| 9   | NC   |
| 10  | SW3  |
| 11  | NC   |
| 12  | SW2  |

| Pin | Name |
|-----|------|
| 13  | NC   |
| 14  | SW2  |
| 15  | NC   |
| 16  | SW1  |
| 17  | NC   |
| 18  | SW1  |
| 19  | NC   |
| 20  | SW0  |
| 21  | NC   |
| 22  | SW0  |
| 23  | NC   |
| 24  | VPP  |

| Pin | Name            |
|-----|-----------------|
| 25  | VNN             |
| 26  | NC              |
| 27  | NC              |
| 28  | GND             |
| 29  | VDD             |
| 30  | NC              |
| 31  | NC              |
| 32  | NC              |
| 33  | DIN             |
| 34  | CLK             |
| 35  | $\overline{LE}$ |
| 36  | CLR             |

| Pin | Name |
|-----|------|
| 37  | DOUT |
| 38  | NC   |
| 39  | SW7  |
| 40  | NC   |
| 41  | SW7  |
| 42  | NC   |
| 43  | SW6  |
| 44  | NC   |
| 45  | SW6  |
| 46  | NC   |
| 47  | SW5  |
| 48  | NC   |

## Pin Description

### 28-Lead PLCC

| Pin | Name |
|-----|------|
| 1   | SW3  |
| 2   | SW3  |
| 3   | SW2  |
| 4   | SW2  |
| 5   | SW1  |
| 6   | SW1  |
| 7   | SW0  |


| Pin | Name |
|-----|------|
| 8   | SW0  |
| 9   | NC   |
| 10  | VPP  |
| 11  | NC   |
| 12  | VNN  |
| 13  | GND  |
| 14  | VDD  |

| Pin | Name            |
|-----|-----------------|
| 15  | NC              |
| 16  | DIN             |
| 17  | CLK             |
| 18  | $\overline{LE}$ |
| 19  | CL              |
| 20  | DOUT            |
| 21  | SW7             |


| Pin | Name |
|-----|------|
| 22  | SW7  |
| 23  | SW6  |
| 24  | SW6  |
| 25  | SW5  |
| 26  | SW5  |
| 27  | SW4  |
| 28  | SW4  |

# 48-Lead LQFP Package Outline (FG)


7.00x7.00mm body, 1.60mm height (max), 0.50mm pitch



**Top View**



**Side View**



**View B**

**Note:**

1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.

| Symbol            |     | A     | A1   | A2   | b    | D     | D1    | E     | E1    | e           | L    | L1          | L2          | θ    |
|-------------------|-----|-------|------|------|------|-------|-------|-------|-------|-------------|------|-------------|-------------|------|
| Dimension<br>(mm) | MIN | 1.40* | 0.05 | 1.35 | 0.17 | 8.80* | 6.80* | 8.80* | 6.80* | 0.50<br>BSC | 0.45 | 1.00<br>REF | 0.25<br>BSC | 0°   |
|                   | NOM | -     | -    | 1.40 | 0.22 | 9.00  | 7.00  | 9.00  | 7.00  |             | 0.60 |             |             | 3.5° |
|                   | MAX | 1.60  | 0.15 | 1.45 | 0.27 | 9.20* | 7.20* | 9.20* | 7.20* |             | 0.75 |             |             | 7°   |

JEDEC Registration MS-026, Variation BBC, Issue D, Jan. 2001.





\* This dimension is not specified in the JEDEC drawing.

**Drawings are not to scale.**

**Supertex Doc. #: DSPD-48LQFPFG Version, D041309.**

## 28-Lead PLCC Package Outline (PJ)

.453x.453in. body, .180in. height (max), .050in. pitch



### Notes:

1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.
2. Actual shape of this feature may vary.

| Symbol             |     | A    | A1   | A2   | b    | b1   | D    | D1   | E    | E1   | e        | R    |
|--------------------|-----|------|------|------|------|------|------|------|------|------|----------|------|
| Dimension (inches) | MIN | .165 | .090 | .062 | .013 | .026 | .485 | .450 | .485 | .450 | .050 BSC | .025 |
|                    | NOM | .172 | .105 | -    | -    | -    | .490 | .453 | .490 | .453 |          | .035 |
|                    | MAX | .180 | .120 | .083 | .021 | .032 | .495 | .456 | .495 | .456 |          | .045 |

JEDEC Registration MS-018, Variation AB, Issue A, June, 1993.

Drawings not to scale.

Supertex Doc. #: DSPD-28PLCCPJ, Version B031111.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

**Supertex inc.** does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: <http://www.supertex.com>)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)