

## Standard Metal Film Leaded Resistors



A homogeneous film of metal alloy is deposited on a high grade ceramic body. After a helical groove has been cut in the resistive layer, tinned connecting leads of electrolytic copper are welded to the end-caps.

The resistors are coated with a colored lacquer (light-blue for type SFR16S; light-green for type SFR25 and red-brown for type SFR25H) which provides electrical, mechanical and climatic protection. The encapsulation is resistant to all cleaning solvents in accordance with IEC 60068-2-45.

### FEATURES

- Low cost
- Low noise (max. 1.5  $\mu\text{V/V}$  for  $R > 1 \text{ M}\Omega$ )
- Small size (SFR16S: 0204, SFR25/25H: 0207)
- Lead (Pb)-free solder contacts
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS  
COMPLIANT**

### APPLICATIONS

- General purpose resistors

| TECHNICAL SPECIFICATIONS   |                 |  |  |   |
|--|-----------------|--|--|---|
| DESCRIPTION  | UNIT            | SFR16S   | SFR25  | SFR25H  |
| Resistance Range   | $\Omega$        | $\pm 5 \%$ ; 1 to 3M<br>$\pm 1 \%$ ; 4.99 to 3M<br>Jumper (0 $\Omega$ )                      | $\pm 5 \%$ ; 0.22 to 10M<br>$\pm 1 \%$ ; 1 to 10M<br>Jumper (0 $\Omega$ )                    |   |
| Resistance Tolerance   | %               | $\pm 1$ , E24/E96 series; $\pm 5$ , E24 series   |  |   |
| Temperature Coefficient:<br>$R \leq 4.7 \Omega$<br>$4.7 \Omega < R \leq 100 \text{ k}\Omega$<br>$100 \text{ k}\Omega < R \leq 1 \text{ M}\Omega$<br>$R > 1 \text{ M}\Omega$  | ppm/K           | $\leq \pm 250$<br>$\leq \pm 100$<br>$\leq \pm 250$<br>$\leq \pm 250$                         | $\leq \pm 100$<br>$\leq \pm 100$<br>$\leq \pm 100$<br>$\leq \pm 250$                         | $\leq \pm 100$<br>$\leq \pm 100$<br>$\leq \pm 100$<br>$\leq \pm 250$                        |
| Rated Dissipation, $P_{70}$  | W               | 0.5  | 0.4  | 0.5   |
| Thermal Resistance, $R_{th}$   | K/W             | 170  | 200  | 150   |
| Maximum Permissible Voltage, ( $U_{max}$ . AC/DC)  | V               | 200  | 250  | 350   |
| Noise:<br>$R < 68 \text{ k}\Omega$<br>$68 \text{ k}\Omega \leq R \leq 100 \text{ k}\Omega$<br>$100 \text{ k}\Omega \leq R \leq 1 \text{ M}\Omega$<br>$R > 1 \text{ M}\Omega$ | $\mu\text{V/V}$ | max. 0.1<br>max. 0.5<br>max. 1.5<br>max. 1.5   | max. 0.1<br>max. 0.1<br>max. 0.1<br>max. 1.5   | max. 0.1<br>max. 0.1<br>max. 0.1<br>max. 1.5  |
| Basic Specifications   |                 | IEC 60115-1  |  |   |
| Climatic Category (IEC 60068-1)  |                 | 55/155/56  |  |   |
| Stability, $\Delta R$ max., after:<br>Load (1000 h, $P_{70}$ ):<br>$R$ Range<br>Long Term Damp Heat Test (56 Days):<br>$R \leq 1 \text{ M}\Omega$<br>$R > 1 \text{ M}\Omega$ |                 | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (1 \% R + 0.05 \Omega)$<br>$\pm (1 \% R + 0.05 \Omega)$ | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (1 \% R + 0.05 \Omega)$<br>$\pm (1 \% R + 0.05 \Omega)$ | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (1 \% R + 0.05 \Omega)$<br>$\pm (2 \% R + 0.1 \Omega)$ |
| Soldering (10 s, 260 °C)   |                 | $\pm (0.25 \% R + 0.05 \Omega)$  | $\pm (0.25 \% R + 0.05 \Omega)$  | $\pm (0.25 \% R + 0.05 \Omega)$   |
| Short Time Overload  |                 | $\pm (0.25 \% R + 0.05 \Omega)$  | $\pm (0.25 \% R + 0.05 \Omega)$  | $\pm (1 \% R + 0.05 \Omega)$  |

### Note

- $R$  value is measured with probe distance of 24 mm  $\pm$  1 mm using 4-terminal method

| PART NUMBER AND PRODUCT DESCRIPTION  |   |                            |   |                                      |                          |   |
|--|---|----------------------------|---|--------------------------------------|--------------------------|---|
| PART NUMBER: SFR2500001001FA500  |   |                            |   |                                      |                          |   |
| <div style="display: flex; justify-content: space-around; font-weight: bold; font-size: 1.2em;"> <span>S</span><span>F</span><span>R</span><span>2</span><span>5</span><span>0</span><span>0</span><span>0</span><span>0</span><span>1</span><span>0</span><span>0</span><span>1</span><span>F</span><span>A</span><span>5</span><span>0</span><span>0</span> </div> |   |                            |   |                                      |                          |   |
| MODEL/SIZE   | VARIANT                                     | TCR/MATERIAL               | VALUE   | TOLERANCE                            | PACKAGING <sup>(1)</sup> | SPECIAL   |
| SFR16S0<br>SFR2500<br>SFR25H0  | 0 = Neutral<br>Z = Value overflow (special) | 0 = Standard<br>Z = Jumper | 3 digit value<br>1 digit multiplier<br>MULTIPLIER<br><br>7 = *10 <sup>-3</sup> 2 = *10 <sup>2</sup><br>8 = *10 <sup>-2</sup> 3 = *10 <sup>3</sup><br>9 = *10 <sup>-1</sup> 4 = *10 <sup>4</sup><br>0 = *10 <sup>0</sup> 5 = *10 <sup>5</sup><br>1 = *10 <sup>1</sup> Z = 0000 | F = ± 1 %<br>J = ± 5 %<br>Z = Jumper | N4<br>A5<br>A1<br>R5     | The 2 digits are used for all special parts.<br>00 = Standard |
| PRODUCT DESCRIPTION: SFR25 1 % A5 1K0  |   |                            |   |                                      |                          |   |
| SFR25  | 1 %   | A5                         | 1K0   |                                      |                          |   |
| MODEL/SIZE   | TOLERANCE                                   | PACKAGING <sup>(1)</sup>   | RESISTANCE VALUE  |                                      |                          |   |
| SFR16S<br>SFR25<br>SFR25H  | ± 1 %<br>± 5 %                              | N4<br>A5<br>A1<br>R5       | 47K = 47 kΩ<br>51R1 = 51.1 Ω  |                                      |                          |   |

**Notes**

<sup>(1)</sup> Please refer to table PACKAGING

- The jumper has a maximum resistance  $R_{max.} = 30 \text{ m}\Omega$  at 3 A (SFR16S)
- The jumper has a maximum resistance  $R_{max.} = 30 \text{ m}\Omega$  at 5 A (SFR25)
- The PART NUMBER is shown to facilitate the introduction of a unified part numbering system for ordering products

| PACKAGING     |           |              |           |      |        |      |
|---------------|-----------|--------------|-----------|------|--------|------|
| MODEL         | TOLERANCE | TAPING       | AMMO PACK |      | REEL   |      |
|               |           |              | PIECES    | CODE | PIECES | CODE |
| SFR16S        | 1 %       | Axial, 52 mm | 5000      | A5   | 5000   | R5   |
| SFR16S        | 5 %       | Axial, 52 mm | 5000      | A5   | 5000   | R5   |
|               |           |              | 1000      | A1   |        |      |
| SFR25, SFR25H | 1 %       | Axial, 52 mm | 5000      | A5   | 5000   | R5   |
| SFR25, SFR25H | 5 %       | Axial, 52 mm | 5000      | A5   | 5000   | R5   |
|               |           |              | 1000      | A1   |        |      |
| SFR25, SFR25H | 1 %       | Radial       | 4000      | N4   | -      | -    |
| SFR25, SFR25H | 5 %       | Radial       | 4000      | N4   | -      | -    |

**DIMENSIONS**


| DIMENSIONS - Resistor types and relevant physical dimensions in millimeters |                     |                     |                     |             |
|---|---------------------|---------------------|---------------------|-------------|
| TYPE  | Ø D <sub>max.</sub> | L <sub>1 max.</sub> | L <sub>2 max.</sub> | Ø d         |
| SFR16S  | 1.9                 | 3.5                 | 4.1                 | 0.45 ± 0.05 |
| SFR25   | 2.5                 | 6.5                 | 7.5                 | 0.58 ± 0.05 |
| SFR25H  | 2.5                 | 6.5                 | 7.5                 | 0.58 ± 0.05 |

| MASS PER UNIT |           |
|---------------|-----------|
| TYPE          | MASS (mg) |
| SFR16S        | 102       |
| SFR25         | 205       |
| SFR25H        | 205       |

**OUTLINES**

The length of the body ( $L_1$ ) is measured by inserting the leads into holes of two identical gauge plates and moving these plates parallel to each other until the resistor body is clamped without deformation (IEC 60294).

**MARKING**

The nominal resistance and tolerance are marked on the resistor using four or five colored bands in accordance with IEC 60062, marking codes for resistors and capacitors.

**PRODUCTS WITH RADIAL LEADS (SFR25, SFR25H)**


| DIMENSIONS - Radial taping |   |       |           |      |
|----------------------------|---|-------|-----------|------|
| SYMBOL                     | PARAMETER                                       | VALUE | TOLERANCE | UNIT |
| P                          | Pitch of components                             | 12.7  | $\pm 1.0$ | mm   |
| $P_0$                      | Feed-hole pitch                                 | 12.7  | $\pm 0.2$ | mm   |
| $P_1$                      | Feed-hole centre to lead at topside at the tape | 3.85  | $\pm 0.5$ | mm   |
| $P_2$                      | Feed-hole center to body center                 | 6.35  | $\pm 1.0$ | mm   |
| F                          | Lead-to-lead distance                           | 4.8   | + 0.7/- 0 | mm   |
| W                          | Tape width                                      | 18.0  | $\pm 0.5$ | mm   |
| $W_0$                      | Minimum hold down tape width                    | 5.5   | -         | mm   |
| H1                         | Component height                                | 29    | Max.      | mm   |
| $H_0$                      | Lead wire clinch height                         | 16.5  | $\pm 0.5$ | mm   |
| $H_0$                      | Height of component from tape center            | 19.5  | $\pm 1$   | mm   |
| $D_0$                      | Feed-hole diameter                              | 4.0   | $\pm 0.2$ | mm   |
| L                          | Maximum length of snapped lead                  | 11.0  | -         | mm   |
| $L_1$                      | Minimum lead wire (tape portion) shortest lead  | 2.5   | -         | mm   |

**Note**

- Please refer to document "Packaging" for more detail ([www.vishay.com/doc?28721](http://www.vishay.com/doc?28721)).



**FUNCTIONAL PERFORMANCE  
PRODUCT CHARACTERIZATION**

Standard values of nominal resistance are taken from the E96/E24 series for resistors with a tolerance of  $\pm 1\%$  or  $\pm 5\%$ . The values of the E96/E24 series are in accordance with IEC 60063.

The power that the resistor can dissipate depends on the operating temperature



Maximum dissipation ( $P_{max}$ ) in percentage of rated power as a function of the ambient temperature ( $T_{amb}$ )



SFR16S Pulse on a regular basis; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration ( $t_i$ )



SFR16S Pulse on a regular basis; maximum permissible peak pulse voltage ( $\hat{U}_{max}$ ) as a function of pulse duration ( $t_i$ )



SFR25 Pulse on a regular basis; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration ( $t_i$ )



SFR25 Pulse on a regular basis; maximum permissible peak pulse voltage ( $\hat{U}_{max}$ ) as a function of pulse duration ( $t_i$ )



SFR25H Pulse on a regular basis; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration ( $t_i$ )



SFR25H Pulse on a regular basis; maximum permissible peak pulse voltage ( $\hat{U}_{max}$ ) as a function of pulse duration ( $t_i$ )



SFR16S Hot-spot temperature rise ( $\Delta T$ ) as a function of dissipated power



SFR25/SFR25H Hot-spot temperature rise ( $\Delta T$ ) as a function of dissipated power

**Note**

- The maximum permissible hot-spot temperature is 155 °C.

**Application Information**



**TESTS AND REQUIREMENTS**

Essentially all tests are carried out in accordance with IEC 60115-1 specification, category LCT/UCT/56 (rated temperature range: Lower Category Temperature, Upper Category temperature; damp heat, steady state, test duration: 56 days).

The tests are carried out in accordance with IEC 60068-2-xx test method under standard atmospheric conditions according to IEC 60068-1, 5.3.

In the Test Procedures and Requirements table, tests and requirements are listed with reference to the relevant clauses of IEC 60115-1 and IEC 60068-2-xx test methods. A short description of the test procedure is also given. In some instances deviations from the IEC recommendations were necessary for our method of specifying. All soldering tests are performed with mildly activated flux.

| TEST PROCEDURES AND REQUIREMENTS |                         |   |  |                            |  |       |   |
|----------------------------------|-------------------------|---|--|----------------------------|--|-------|---|
| IEC 60115-1 CLAUSE               | IEC 60068-2 TEST METHOD | TEST  | PROCEDURE  | RESISTANCE RANGE           | REQUIREMENTS   |       |   |
|                                  |                         |   |  |                            | SFR16S   | SFR25 | SFR25H  |
| 4.16                             |                         | Robustness of terminations:                   |  |                            | Number of failures <math> < 10 \times 10^{-6}</math><br><br>Number of failures <math> < 10 \times 10^{-6}</math><br><br>No damage<br>$\Delta R \text{ max.: } \pm (0.25 \% R + 0.05 \Omega)$ |       |   |
| 4.16.2                           | 21 (Ua1)                | Tensile all samples                           | $\varnothing$ 0.45 mm, load 5 N; 10 s<br>$\varnothing$ 0.58 mm, load 10 N; 10 s  |                            |  |       |   |
| 4.16.3                           | 21 (Ub)                 | Bending half number of samples                | $\varnothing$ 0.45 mm, load 2.5 N; 4 x 90°<br>$\varnothing$ 0.58 mm, load 5 N; 4 x 90°   |                            |  |       |   |
| 4.16.4                           | 21 (Uc)                 | Torsion other half of samples                 | 3 x 360° in opposite directions  |                            |  |       |   |
| 4.17                             | 20 (Ta)                 | Solderability                                 | 2 s; 235 °C: Solder bath method; SnPb40<br>3 s; 245 °C: Solder bath method; SnAg3Cu0.5   |                            | Good tinning ( $\geq 95 \%$ covered); no damage  |       |   |
|                                  |                         | Solderability (after aging)                   | 8 h steam or 16 h 155 °C; leads immersed 6 mm; for 2 s at 235 °C: Solder bath (SnPb40) for 3 s at 245 °C: Solder bath (SnAgCu0.5) method |                            | Good tinning ( $\geq 95 \%$ covered); no damage  |       |   |
| 4.18                             | 20 (Tb)                 | Resistance to soldering heat                  | Thermal shock: 10 s; 260 °C; 3 mm from body  |                            | $\Delta R \text{ max.: } \pm (0.25 \% R + 0.05 \Omega)$  |       |   |
| 4.19                             | 14 (Na)                 | Rapid change of temperature                   | 30 min at - 55 °C and 30 min at + 155 °C; 5 cycles   |                            | $\Delta R \text{ max.: } \pm (0.25 \% R + 0.05 \Omega)$  |       |   |
| 4.20                             | 29 (Eb)                 | Bump  | 3 x 1500 bumps in 3 directions; 40 g   |                            | No damage<br>$\Delta R \text{ max.: } \pm (0.25 \% R + 0.05 \Omega)$   |       |   |
| 4.22                             | 6 (Fc)                  | Vibration                                     | Frequency 10 Hz to 500 Hz; displacement 1.5 mm or acceleration 10 g; 3 directions; total 6 h (3 x 2 h)                                   |                            | No damage<br>$\Delta R \text{ max.: } \pm (0.25 \% R + 0.05 \Omega)$   |       |   |
| 4.23                             | 2 (Ba)                  | Climatic sequence: Dry heat                   | 16 h; 155 °C   |                            | $R_{\text{ins min.:}} 1000 \text{ M}\Omega$<br><br>$\Delta R \text{ max.: } \pm (1 \% R + 0.05 \Omega)$  |       |   |
| 4.23.2                           |                         | Damp heat (accelerated) 1 <sup>st</sup> cycle | 24 h; 55 °C; 90 % to 100 % RH  |                            |  |       |   |
| 4.23.3                           | 30 (Db)                 |   |  |                            |  |       |   |
| 4.23.4                           | 1 (Aa)                  | Cold  | 2 h; - 55 °C   |                            |  |       |   |
| 4.23.5                           | 13 (M)                  | Low air pressure                              | 2 h; 8.5 kPa; 15 °C to 35 °C   |                            |  |       |   |
| 4.23.6                           | 30 (Db)                 | Damp heat (accelerated) remaining cycles      | 5 days; 55 °C; 95 % to 100 % RH  |                            |  |       |   |
|                                  |                         |   |  | $R \leq 1 \text{ M}\Omega$ | $\Delta R \text{ max.: } \pm (1 \% R + 0.05 \Omega)$   |       |   |
|                                  |                         |   |  | $R > 1 \text{ M}\Omega$    | $\Delta R \text{ max.: } \pm (1 \% R + 0.05 \Omega)$   |       | $\Delta R \text{ max.: } \pm (2 \% R + 0.1 \Omega)$ |





| TEST PROCEDURES AND REQUIREMENTS |                         |                             |  |   |  |  |  |
|----------------------------------|-------------------------|-----------------------------|--|---|--|--|--|
| IEC 60115-1 CLAUSE               | IEC 60068-2 TEST METHOD | TEST                        | PROCEDURE  | RESISTANCE RANGE  | REQUIREMENTS   |  |  |
|                                  |                         |                             |  |   | SFR16S   | SFR25  | SFR25H   |
| 4.24                             | 78 (Cab)                | Damp heat (steady state)    | 56 days; 40 °C; 90 % to 95 % RH; loaded with 0.01 $P_{70}$ (steps: 0 V to 100 V)   |   | $R_{ins}$ min.: 1000 M $\Omega$<br>$\Delta R$ max.: $\pm (2 \% R + 0.05 \Omega)$   |  |  |
| 4.25.1                           |                         | Endurance (at 70 °C)        | 1000 h; loaded with $P_{70}$ or $U_{max}$ ; 1.5 h ON and 0.5 h OFF   |   | $\Delta R$ max.: $\pm (2 \% R + 0.05 \Omega)$  |  |  |
| 4.8                              |                         | Temperature coefficient     | Between - 55 °C and + 155 °C   | $R < 4.7 \Omega$<br>$R \leq 100 \text{ k}\Omega$<br>$R \leq 1 \text{ M}\Omega$<br>$R > 1 \text{ M}\Omega$         | $\leq \pm 250 \text{ ppm/K}$<br>$\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 250 \text{ ppm/K}$<br>$\leq \pm 250 \text{ ppm/K}$ | $\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 250 \text{ ppm/K}$ | $\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 100 \text{ ppm/K}$<br>$\leq \pm 250 \text{ ppm/K}$ |
| 4.7                              |                         | Voltage proof on insulation | $U_{RMS} = 400 \text{ V}$ (SFR16S) or $U_{RMS} = 600 \text{ V}$ (SFR25 and SFR25H); during 1 min; V-block method   |   | No breakdown   |  |  |
| 4.12                             |                         | Noise                       | IEC 60195  | $R < 68 \text{ k}\Omega$<br>$R \leq 100 \text{ k}\Omega$<br>$R \leq 1 \text{ M}\Omega$<br>$R > 1 \text{ M}\Omega$ | max. 0.1 $\mu\text{V/V}$<br>max. 0.5 $\mu\text{V/V}$<br>max. 1.5 $\mu\text{V/V}$<br>max. 1.5 $\mu\text{V/V}$                 | max. 0.1 $\mu\text{V/V}$<br>max. 0.1 $\mu\text{V/V}$<br>max. 0.1 $\mu\text{V/V}$<br>max. 1.5 $\mu\text{V/V}$                 | max. 0.1 $\mu\text{V/V}$<br>max. 0.1 $\mu\text{V/V}$<br>max. 0.1 $\mu\text{V/V}$<br>max. 1.5 $\mu\text{V/V}$                 |
| 4.6.1.1                          |                         | Insulation resistance       | $U_{max}$ , DC = 500 V during 1 min; V-block method  |   | $R_{ins}$ min.: 1000 M $\Omega$  |  |  |
| 4.13                             |                         | Short time overload         | Room temperature; $P = 6.25 \times P_n$ (SFR25, SFR25H) or $6.25 \times 0.25 \text{ W}$ (SFR16S); (voltage not more than 2 x limiting voltage); 10 cycles; 5 s ON and 45 s OFF |   | $\Delta R$ max.: $\pm (0.25 \% R + 0.05 \Omega)$   |  | $\Delta R$ max.: $\pm 1 \% R + 0.05 \Omega$  |

**HISTORICAL 12NC INFORMATION**

- The resistors had a 12-digit numeric code starting with 23.
- The subsequent 6 digits for 1 % or 7 digits for 5 % indicated the resistor type and packaging.
- The remaining digits indicated the resistance value:
  - The first 3 digits for 1 % or 2 digits for 5 % indicated the resistance value.
  - The last digit indicated the resistance decade.

**Resistance Decade for  $\pm 5 \%$  Tolerance**

| RESISTANCE DECADE                | LAST DIGIT |
|----------------------------------|------------|
| 0.10 $\Omega$ to 0.91 $\Omega$   | 7          |
| 1 $\Omega$ to 9.1 $\Omega$       | 8          |
| 10 $\Omega$ to 91 $\Omega$       | 9          |
| 100 $\Omega$ to 910 $\Omega$     | 1          |
| 1 k $\Omega$ to 9.1 k $\Omega$   | 2          |
| 10 k $\Omega$ to 91 k $\Omega$   | 3          |
| 100 k $\Omega$ to 910 k $\Omega$ | 4          |
| 1 M $\Omega$ to 9.1 M $\Omega$   | 5          |
| = 10 M $\Omega$                  | 6          |

**Resistance Decade for  $\pm 1 \%$  Tolerance**

| RESISTANCE DECADE                | LAST DIGIT |
|----------------------------------|------------|
| 1 $\Omega$ to 9.76 $\Omega$      | 8          |
| 10 $\Omega$ to 97.6 $\Omega$     | 9          |
| 100 $\Omega$ to 976 $\Omega$     | 1          |
| 1 k $\Omega$ to 9.76 k $\Omega$  | 2          |
| 10 k $\Omega$ to 97.6 k $\Omega$ | 3          |
| 100 k $\Omega$ to 976 k $\Omega$ | 4          |
| 1 M $\Omega$ to 9.76 M $\Omega$  | 5          |
| = 10 M $\Omega$                  | 6          |

**12NC Example**

The 12NC of a SFR25 resistor, value 5600  $\Omega \pm 5 \%$ , taped on a bandolier of 5000 units in ammpack was: 2322 181 43562.



| <b>HISTORICAL 12NC - Resistor type and packaging</b> |        |                          |                |                |                      |
|--|--------|--------------------------|----------------|----------------|----------------------|
| TYPE   | TOL.   | 23.. ... ..              |                |                |                      |
|  |        | BANDOLIER<br>IN AMMOPACK |                |                | BANDOLIER<br>ON REEL |
|  |        | RADIAL TAPED             | STRAIGHT LEADS |                | STRAIGHT LEADS       |
|  |        | 4000 UNITS               | 1000 UNITS     | 5000 UNITS     | 5000 UNITS           |
| SFR16S   | ± 5 %  | -                        | ..22 187 73... | ..22 187 53... | ..06 187 23...       |
|  | ± 1 %  | -                        | -              | ..06 187 3...  | ..06 187 1....       |
|  | Jumper | -                        | -              | ..06 187 90013 | ..22 187 90346       |
| SFR25  | ± 5 %  | ..06 184 03...           | ..22 181 53... | ..22 181 43... | ..22 181 63...       |
|  | ± 1 %  | -                        | -              | ..22 188 2...  | ..06 181 8....       |
|  | Jumper | -                        | ..22 181 90018 | ..22 181 90019 | ..06 181 90011       |
| SFR25H   | ± 5 %  | ..06 186 03...           | ..22 186 16... | ..22 186 76... | ..06 186 63...       |
|  | ± 1 %  | -                        | -              | ..22 186 3.... | ..06 186 8....       |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)