



# Multilayer Diplexer

For 2400-2500MHz / 5150-5850MHz

# DPX205850DT-9043B1BR

---

**2.0x1.25mm [EIA 0805]\***

\* Dimensions Code JIS[EIA]

---

# Multilayer Diplexer


Conformity to RoHS Directive

For 2400-2500MHz / 5150-5850MHz


## DPX205850DT-9043B1BR

### SHAPES AND DIMENSIONS

[Top view]



[Bottom view]




Dimensions in mm

#### Terminal functions

|   |           |
|---|-----------|
| 1 | GND       |
| 2 | Common    |
| 3 | GND       |
| 4 | High-Band |
| 5 | GND       |
| 6 | Low-Band  |

### RECOMMENDED LAND PATTERN



Dimensions in mm

○ RoHS Directive Compliant Product: See the following for more details. <https://product.tdk.com/info/en/environment/rohs/index.html>

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

# DPX205850DT-9043B1BR

## ELECTRICAL CHARACTERISTICS

### LOW-BAND

| Item                                  | Frequency Range (MHz) | Min. | Typ. | Max. |
|---------------------------------------|-----------------------|------|------|------|
| Insertion Loss (dB)                   | 2400 to 2500          | —    | 0.27 | 0.45 |
| Attenuation (dB)                      | 4800 to 5000          | 23   | 29.6 | —    |
|                                       | 7200 to 7500          | 20   | 39.1 | —    |
| Characteristic Impedance ( $\Omega$ ) | 50 (Nominal)          |      |      |      |

· Ta: +25±5°C

### HIGH-BAND

| Item                                  | Frequency Range (MHz) | Min. | Typ. | Max. |
|---------------------------------------|-----------------------|------|------|------|
| Insertion Loss (dB)                   | 5150 to 5850          | —    | 0.31 | 0.50 |
| Attenuation (dB)                      | 2400 to 2500          | 25   | 31.8 | —    |
|                                       | 10300 to 11700        | 20   | 28.0 | —    |
|                                       | 15450 to 17550        | 18   | 31.2 | —    |
| Characteristic Impedance ( $\Omega$ ) | 50 (Nominal)          |      |      |      |

· Ta: +25±5°C

### COMMON

| Item                                  | Frequency Range (MHz) | Min. | Typ. | Max. |
|---------------------------------------|-----------------------|------|------|------|
| Isolation (dB)                        | 2400 to 2500          | 20   | 32.4 | —    |
|                                       | 5150 to 5850          | 20   | 26.5 | —    |
| Return Loss (dB)                      | 2400 to 2500          | 10   | 20.8 | —    |
|                                       | 5150 to 5850          | 10   | 23.1 | —    |
| Characteristic Impedance ( $\Omega$ ) | 50 (Nominal)          |      |      |      |

· Ta: +25±5°C

## TEMPERATURE RANGE

| Operating temperature (°C) | Storage temperature (°C) |
|----------------------------|--------------------------|
| −40 to +85                 | −40 to +85               |


- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

# DPX205850DT-9043B1BR


## FREQUENCY CHARACTERISTICS

### LOW-BAND


#### Insertion Loss



#### Return Loss




#### Attenuation




### HIGH-BAND


#### Insertion Loss



#### Return Loss



#### Attenuation




- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

## DPX205850DT-9043B1BR


## FREQUENCY CHARACTERISTICS

## COMMON

## Return Loss




## Isolation



- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

# DPX205850DT-9043B1BR

## RECOMMENDED REFLOW PROFILE



| Soaking |    |            | Working |               | Soldering Peak |            |            |
|---------|----|------------|---------|---------------|----------------|------------|------------|
| Temp.   | T1 | T2         | Temp.   | T3            | Temp.          | T4         | T5         |
| 150°C   |    | 180°C      | 230°C   |               | 247 to 253°C   |            | 260°C max. |
|         |    | 60 to 120s |         | more than 30s |                | within 10s |            |

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

#### REMINDERS

The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this catalog.

- |                                                                   |                                                                              |
|-------------------------------------------------------------------|------------------------------------------------------------------------------|
| (1) Aerospace/Aviation equipment                                  | (8) Public information-processing equipment                                  |
| (2) Transportation equipment (cars, electric trains, ships, etc.) | (9) Military equipment                                                       |
| (3) Medical equipment                                             | (10) Electric heating apparatus, burning equipment                           |
| (4) Power-generation control equipment                            | (11) Disaster prevention/crime prevention equipment                          |
| (5) Atomic energy-related equipment                               | (12) Safety equipment                                                        |
| (6) Seabed equipment                                              | (13) Other applications that are not considered general-purpose applications |
| (7) Transportation control equipment                              |                                                                              |

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc., to ensure higher safety.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)