


## ELVR - Analog and Digital Low Pressure Sensors Series



### Table of Contents

|                                                          |       |
|----------------------------------------------------------|-------|
| <a href="#">Features &amp; Applications</a> .....        | 2     |
| <a href="#">Standard Pressure Ranges</a> .....           | 2     |
| <a href="#">Pressure Sensor Maximum Ratings</a> .....    | 2     |
| <a href="#">Environmental Specifications</a> .....       | 2     |
| <a href="#">Analog Output (5V) Specifications</a> .....  | 3     |
| <a href="#">Analog Output (3V) Specifications</a> .....  | 4     |
| <a href="#">Digital Output (5V) Specifications</a> ..... | 5     |
| <a href="#">Digital Output (3V) Specifications</a> ..... | 6     |
| <a href="#">Device Option Descriptions</a> .....         | 7     |
| <a href="#">I<sup>2</sup>C Interface</a> .....           | 8-9   |
| <a href="#">SPI Interface</a> .....                      | 10-11 |
| <a href="#">How to Order Guide</a> .....                 | 12    |
| <a href="#">Dimensional Package Drawings</a>             |       |
| <a href="#">Non-Barbed SIL, DIP and SMT</a> ....         | 13-16 |
| <a href="#">Barbed SIL, DIP and SMT</a> .....            | 17-20 |
| <a href="#">Product Labeling</a> .....                   | 21    |
| <a href="#">Suggested Pad Layouts</a> .....              | 21    |

### Introduction

The ELVR Series Mini Analog and Digital Output Sensor is based on All Sensors' CoBeam<sup>2</sup>™ Technology. This reduces package stress susceptibility, resulting in improved overall long term stability. The superior dual-die technology also vastly improves position sensitivity compared to single die devices. This technology breakthrough advances the state of the art for piezoresistive pressure sensors beyond what has been achieved for low pressure sensing using silicon based strain technology.

The ELVR sensors can communicate directly with microcontrollers, eliminating the need for additional A/D converters. ELVR series pressure sensors are available at 3V and 5V supply voltage. The ELVR series provides a rapid update rate at multiple resolutions. A wide range of miniature SIP and DIP package options allows for flexible and space-saving PCB-mounting. These calibrated and compensated sensors provide accurate, stable output over a wide temperature range. This series is intended for use with non-corrosive, non-ionic working fluids such as air and dry gases. A protective parylene coating is optionally available for moisture/harsh media protection for pressure ranges 10 inH<sub>2</sub>O and above.

The ELVR Series is a direct replacement to First Sensors' HCLA product line. Refer to the product web page for a cross reference table:

<https://www.allsensors.com/products/elvr-series>



# ELVR SERIES ANALOG & DIGITAL PRESSURE SENSORS

## Features

- Pressure Ranges from 2.5 mbar to 75 mbar (1 to 30 inH2O)
- Precision ASIC Conditioning
- Analog Output with Digital I2C and SPI Interface
- 3V and 5V Supply Voltage



## Applications

- Medical
- Industrial

## Standard Pressure Ranges

| Device    | Operating Range <sup>A</sup> |       | Differential Proof Pressure |       | Differential Burst Pressure |       |
|-----------|------------------------------|-------|-----------------------------|-------|-----------------------------|-------|
|           | mbar                         | inH2O | mbar                        | inH2O | mbar                        | inH2O |
| ELVR-L01D | ± 2.5                        | ± 1   | 250                         | 100   | 750                         | 301   |
| ELVR-L05D | ± 12.5                       | ± 5   | 500                         | 201   | 750                         | 301   |
| ELVR-L10D | ± 25                         | ± 10  | 500                         | 201   | 750                         | 301   |
| ELVR-L20D | ± 50                         | ± 20  | 500                         | 201   | 1250                        | 502   |
| ELVR-L30D | ± 75                         | ± 30  | 500                         | 201   | 2000                        | 803   |
| ELVR-L01G | 2.5                          | 1     | 250                         | 100   | 750                         | 301   |
| ELVR-L05G | 12.5                         | 5     | 500                         | 201   | 750                         | 301   |
| ELVR-L10G | 25                           | 10    | 500                         | 201   | 750                         | 301   |
| ELVR-L20G | 50                           | 20    | 500                         | 201   | 1250                        | 502   |
| ELVR-L30G | 75                           | 30    | 500                         | 201   | 2000                        | 803   |

Note A: Operating range in inH2O is expressed as an approximate value. ELVR series is calibrated to mbar pressure units.

| Pressure Sensor Maximum Ratings                |                       | Environmental Specifications                                                         |                                                                                       |
|------------------------------------------------|-----------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Supply Voltage (Vs)</b>                     | 2.7 to 5.5 Vdc        | <b>Temperature Ranges</b>                                                            |                                                                                       |
| <b>Analog-Output Current</b>                   |                       | Compensated:                                                                         | Commercial 0°C to 70°C<br>Industrial -20°C to 85°C                                    |
| Sink                                           | 1 mA                  | Operating                                                                            | -25°C to 85°C                                                                         |
| Source                                         | 1 mA                  | Storage                                                                              | -40°C to 125°C                                                                        |
| <b>Common Mode Pressure</b>                    | 2000 mbar / 803 inH2O | <b>Humidity Limits (non condensing)</b>                                              | 0 to 95% RH                                                                           |
| SMT Assembly Specifications                    |                       | Equivalent Circuit                                                                   |                                                                                       |
| <b>Average preheating temperature gradient</b> | 2.5 K/s               | <b>I2C</b>                                                                           | <b>SPI</b>                                                                            |
| <b>Soak Time</b>                               | ca. 3 min             |  |  |
| <b>Time above 217°C</b>                        | 50 s                  | See package drawings for pinouts.                                                    |                                                                                       |
| <b>Time above 230°C</b>                        | 40 s                  |                                                                                      |                                                                                       |
| <b>Time above 250°C</b>                        | 15 s                  |                                                                                      |                                                                                       |
| <b>Peak Temperature</b>                        | 260°C                 |                                                                                      |                                                                                       |
| <b>Cooling Temperature Gradient</b>            | -3.5 K/s              |                                                                                      |                                                                                       |



## Performance Characteristics for ELVR Series Amplified Low Pressure Sensors

All parameters are measured at **5.0 volt** excitation and 25°C unless otherwise specified. Pressure measurements are with positive pressure applied to PORT B

| Analog Performance Characteristics          |                   |         |         |         |       |                     |
|---------------------------------------------|-------------------|---------|---------|---------|-------|---------------------|
| Parameter                                   |                   | Minimum | Nominal | Maximum | Units | Specification Notes |
| Full Scale Span (FSS)                       |                   | 3.9     | 4.0     | 4.1     | V     | 5                   |
| Full Scale Output (FSO)                     |                   |         |         |         |       | -                   |
|                                             | Min Pressure      |         | 0.25    |         | V     |                     |
|                                             | Max Pressure      |         | 4.25    |         | V     |                     |
| Span Temperature Shift                      |                   |         |         |         |       |                     |
|                                             | L01x              | -       | -       | ±2      | %FSS  | 2                   |
|                                             | L05x through L30x | -       | -       | ±1      | %FSS  | 2                   |
| Offset Voltage @ zero differential pressure |                   |         |         |         |       |                     |
|                                             | LxxD              | 2.15    | 2.25    | 2.35    | V     | -                   |
|                                             | LxxG              | 0.15    | 0.25    | 0.35    | V     | -                   |
| Offset Temperature Shift                    |                   |         |         |         |       |                     |
|                                             | L01x              | -       | -       | ±1.5    | %FSS  | 2                   |
|                                             | L05x              | -       | -       | ±1      | %FSS  | 2                   |
|                                             | L10x through L30x | -       | -       | ±0.5    | %FSS  | 2                   |
| Offset Warm-up Shift                        |                   |         |         |         |       |                     |
|                                             | L01x              | -       | ±10     | -       | mV    | 3                   |
|                                             | L05x through L30x | -       | ±5      | -       | mV    | 3                   |
| Offset Long Term Drift (one year)           |                   |         |         |         |       |                     |
|                                             | L01x              | -       | ±15     | -       | mV    | -                   |
|                                             | L05x through L30x | -       | ±5      | -       | mV    | -                   |
| Linearity, Hysteresis error (all products)  |                   | -       | ±0.05   | ±0.25   | %FSS  | 4                   |
| Response Delay                              |                   | -       | 0.5     | -       | ms    | 1                   |
| D/A Resolution                              |                   | -       | -       | 11      | bit   | -                   |
| Current Consumption (no load)               |                   | -       | 5.0     | -       | mA    | 6                   |

### Specification Notes

**Note 1:** For any pressure applied the output response time to reach 90% of pressure applied.

**Note 2:** Shift is relative to 25°C between standard or industrial compensated temperature range endpoints.

**Note 3:** Shift is within the first hour of excitation applied to the device.

**Note 4:** Measured at one-half full scale rated pressure using best straight line curve fit.

**Note 5:** The span is the algebraic difference between full scale output voltage and the offset voltage.

**Note 6:** Parameter is characterized and not 100% tested.

## Performance Characteristics for ELVR Series Amplified Low Pressure Sensors

All parameters are measured at **3.0 volt** excitation and 25°C unless otherwise specified. Pressure measurements are with positive pressure applied to PORT B

| Analog Performance Characteristics          |                    |         |         |         |       |                     |
|---------------------------------------------|--------------------|---------|---------|---------|-------|---------------------|
| Parameter                                   |                    | Minimum | Nominal | Maximum | Units | Specification Notes |
| Full Scale Span (FSS)                       |                    | 1.9     | 2.0     | 2.10    | V     | 5                   |
| Full Scale Output (FSO)                     |                    |         |         |         |       | -                   |
|                                             | Min Pressure       |         | 0.25    |         | V     |                     |
|                                             | Max Pressure       |         | 2.25    |         | V     |                     |
| Span Temperature Shift                      |                    |         |         |         |       |                     |
|                                             | L01x               | -       | -       | ±2      | %FSS  | 2                   |
|                                             | L05x though L30x   | -       | -       | ±1      | %FSS  | 2                   |
| Offset Voltage @ zero differential pressure |                    |         |         |         |       |                     |
|                                             | LxxD               | 1.15    | 1.25    | 1.35    | V     | -                   |
|                                             | LxxG               | 0.15    | 0.25    | 0.35    | V     | -                   |
| Offset Temperature Shift                    |                    |         |         |         |       |                     |
|                                             | L01x               | -       | -       | ±1.5    | %FSS  | 2                   |
|                                             | L05x               | -       | -       | ±1      | %FSS  | 2                   |
|                                             | L10x through L30x  | -       | -       | ±0.5    | %FSS  | 2                   |
| Offset Warm-up Shift                        |                    |         |         |         |       |                     |
|                                             | L01x               | -       | ±10     | -       | mV    | 3                   |
|                                             | L05x thorough L30x | -       | ±5      | -       | mV    | 3                   |
| Offset Long Term Drift (one year)           |                    |         |         |         |       |                     |
|                                             | L01x               | -       | ±5      | -       | mV    | -                   |
|                                             | L05x thorough L30x | -       | ±5      | -       | mV    | -                   |
| Linearity, Hysteresis error (all products)  |                    | -       | ±0.05   | ±0.25   | %FSS  | 4                   |
| Response Delay                              |                    | -       | 0.5     | -       | ms    | 1                   |
| D/A Resolution                              |                    | -       | -       | 11      | bit   | -                   |
| Current Consumption                         |                    | -       | 5       | -       | mA    | 6                   |



## Performance Characteristics for ELVR Series Amplified Low Pressure Sensors

All parameters are measured at **5.0 volt** excitation and 25°C unless otherwise specified. Pressure measurements are with positive pressure applied to PORT B

| Digital Performance Characteristics in Decimal |                   |         |         |         |         |                     |
|------------------------------------------------|-------------------|---------|---------|---------|---------|---------------------|
| Parameter                                      |                   | Minimum | Nominal | Maximum | Units   | Specification Notes |
| Full Scale Span (FSS)                          |                   | -       | 26214   | -       | Decimal | 2                   |
| Full Scale Output (FSO)                        |                   |         |         |         |         |                     |
|                                                | Min Pressure      |         | 1638    |         | Decimal | 5                   |
|                                                | Max Pressure      |         | 27852   |         | Decimal | 5                   |
| Span Temperature Shift                         |                   |         |         |         |         |                     |
|                                                | L01x              | -       | -       | ±2      | %FSS    | 2                   |
|                                                | L05x through L30x | -       | -       | ±1      | %FSS    | 2                   |
| Offset Voltage @ zero differential pressure    |                   |         |         |         |         |                     |
|                                                | LxxD              | 14090   | 14745   | 15400   | Decimal | -                   |
|                                                | LxxG              | 983     | 1638    | 2294    | Decimal | -                   |
| Offset Temperature Shift                       |                   |         |         |         |         |                     |
|                                                | L01x              | -       | -       | ±1.5    | %FSS    | 2                   |
|                                                | L05x              | -       | -       | ±1      | %FSS    | 2                   |
|                                                | L10x through L30x | -       | -       | ±0.5    | %FSS    | 2                   |
| Offset Warm-up Shift                           |                   |         |         |         |         |                     |
|                                                | L01x              | -       | 66      | -       | Decimal | 3                   |
|                                                | L05x through L30x | -       | 33      | -       | Decimal | 3                   |
| Offset Position Sensitivity (±1 g)             |                   |         |         |         |         |                     |
|                                                | L01x              | -       | 99      | -       | Decimal | -                   |
|                                                | L05x through L30x | -       | 33      | -       | Decimal | -                   |
| Offset Long Term Drift (one year)              |                   |         |         |         |         |                     |
|                                                | L01x              | -       | 66      | -       | Decimal | -                   |
|                                                | L05x through L30x | -       | 33      | -       | Decimal | -                   |
| Linearity, Hysteresis error (all products)     |                   | -       | ±0.05   | ±0.25   | %FSS    | 4                   |
| Response Delay                                 |                   |         | 0.5     |         | ms      | 1                   |
| A/D Resolution                                 |                   | -       | 12      | -       | bit     | -                   |
| Current Consumption                            |                   | -       | 5       | -       | mA      | 6                   |

## Performance Characteristics for ELVR Series Amplified Low Pressure Sensors

All parameters are measured at **3.0 volt** excitation and 25°C unless otherwise specified. Pressure measurements are with positive pressure applied to PORT B

| Digital Performance Characteristics in Decimal |                   |         |          |         |                              |
|------------------------------------------------|-------------------|---------|----------|---------|------------------------------|
| Parameter                                      |                   | Minimum | Nominal  | Maximum | Units<br>Specification Notes |
| Full Scale Span (FSS)                          |                   | 21299   | 21845    | 22391   | Decimal 2                    |
| Full Scale Output (FSO)                        |                   |         |          |         |                              |
|                                                | Min Pressure      | -       | 2731     | -       | Decimal 5                    |
|                                                | Max Pressure      | -       | 24576    | -       | Decimal 5                    |
| Span Temperature Shift                         |                   |         |          |         |                              |
|                                                | L01x              | -       | -        | ±2      | %FSS 2                       |
|                                                | L05x through L30x | -       | -        | ±1      | %FSS 2                       |
| Offset Voltage @ zero differential pressure    |                   |         |          |         |                              |
|                                                | LxxD              | 12561   | 13653    | 14745   | Decimal -                    |
|                                                | LxxG              | 1638    | 2731     | 3823    | Decimal -                    |
| Offset Temperature Shift                       |                   |         |          |         |                              |
|                                                | L01x              | -       | -        | ±1.5    | %FSS 2                       |
|                                                | L05x              | -       | -        | ±1      | %FSS 2                       |
|                                                | L10x through L30x | -       | -        | ±0.5    | %FSS 2                       |
| Offset Warm-up Shift                           |                   |         |          |         |                              |
|                                                | L01x              | -       | 66       | -       | Decimal 3                    |
|                                                | L05x through L30x | -       | 33       | -       | Decimal 3                    |
| Offset Position Sensitivity (±1 g)             |                   |         |          |         |                              |
|                                                | L01x              | -       | 99       | -       | Decimal -                    |
|                                                | L05x through L30x | -       | 33       | -       | Decimal -                    |
| Offset Long Term Drift (one year)              |                   |         |          |         |                              |
|                                                | L01x              | -       | 66       | -       | Decimal -                    |
|                                                | L05x through L30x | -       | 33       | -       | Decimal -                    |
| Linearity, Hysteresis error (all products)     |                   | -       | ±0.05    | ±0.25   | %FSS 4                       |
| Response Delay                                 |                   | -       | 0.5      | -       | ms 1                         |
| A/D Resolution                                 |                   | -       | 12 or 14 | -       | bit -                        |
| Current Consumption                            |                   | -       | 5        | -       | mA 6                         |



---

## Device Options

---

The following is a list of factory programmable options. Consult the factory to learn more about the options.

### Interface

I2C and SPI interfaces are available with eight (8) lead packages only.

### Supply Voltage

Devices are characterized at either 3.0V or 5.0V depending on the options selected. It is suggested to select the option that most closely matches the application supply voltage for best possible performance.

### Speed/Power

There are two options of Speed/Power. These are Fast(F) and High Resolution(H).

Fast Mode(F) Is the fastest operating mode where the device operates with continuous sampling at the fastest internal speed 12 bit resolution, 0.5ms update rate.

High Resolution(H): Also operates with continuous samples however the ADC is set for longer duration for higher resolution. The conversion times are resultantly longer than the Fast(F) mode with 1 ms update rate.

### Coating

Parylene Coating: Parylene coating provides a moisture barrier and protection form some harsh media. Consult factory for applicability of Parylene for the target application and sensor type. This option is not available for pressure ranges below 10 inH2O.

# I2C Interface

## Introduction

The ELVR is capable of producing a digital output signal. The device runs a cyclic program, which will store a corrected pressure value with 12 or 13 bit resolution about every 250µs within the output registers of the internal ASIC. In order to use the sensor for digital signal readout, it should be connected to a bidirectional I2C-bus.

According to the I2C-bus specification, the bus is controlled by a master device, which generates the clock signal, controls the bus access and generates START and STOP conditions. The ELVR is designed to work as a slave, hence it will only respond to requests from a master device.

## Digital I2C interface

The ELVR complies with the following protocol in Figure 1.

**Bus not busy** : During idle periods both data line (SDA) and clock line (SCL) remain HIGH.

**START condition (S)** : HIGH to LOW transition of SDA line while clock (SCL) is HIGH is interpreted as START condition. START conditions are always generated by the master. Each initial request for a pressure value has to begin with a START condition.

**STOP condition (P)** : LOW to HIGH transition of SDA line while clock (SCL) is HIGH determines STOP condition. STOP conditions are always generated by the master. More than one request for the current pressure value can be transmitted without generation of intermediate STOP condition.

**DATA valid (D)**: State of data line represents valid data when, after START condition, data line is stable for duration of HIGH period of clock signal. Data on line must be changed during LOW period of clock signal. There is one clock pulse per bit of data.

**Acknowledge (A)**: Data is transferred in pieces of 8 bits (1 byte) on serial bus, MSB first. After each byte the receiving device – whether master or slave – is obliged to pull data line LOW as acknowledge for reception of data. Master must generate an extra clock pulse for this purpose. When acknowledge is missed, slave transmitter becomes inactive. Master must then either send last command again or generate STOP condition in that case.

**Slave address**: The I2C-bus master-slave concept requires a unique address for each device. The ELVR has a preconfigured slave address, see table 2. The sensor will then listen to both slave addresses. After generating a START condition the master sends the address byte containing a 7 bit address followed by a data direction bit (R/W). A "0" indicates a transmission from master to slave (WRITE), a "1" indicates a data request (READ).

**DATA operation** : The sensor starts to send 2 data bytes containing the current pressure value as a 15 bit value placed in the output registers.




Figure 1: I<sup>2</sup>C bus protocol



## I<sup>2</sup>C BUS INTERFACE (Cont'd)

### I<sup>2</sup>C Interface Parameters

| Parameter                                                  | Symbol              | Minimum | Nominal | Maximum | Unit                |
|------------------------------------------------------------|---------------------|---------|---------|---------|---------------------|
| Input High Level                                           | -                   | 90      | -       | 100     | % of V <sub>S</sub> |
| Input Low Level                                            | -                   | 0       | -       | 10      | % of V <sub>S</sub> |
| Output Low Level                                           | -                   | -       | -       | 10      | % of V <sub>S</sub> |
| Pull-Up Resistor                                           | -                   | 500     | -       | -       | Ω                   |
| Load Capacitance @ SDA                                     | C <sub>SDA</sub>    | -       | -       | 400     | pF                  |
| Input Capacitance @ SDA/SCL                                | C <sub>I2C_IN</sub> | -       | -       | 10      | pF                  |
| Signal Clock Frequency                                     | F <sub>SCL</sub>    | 100*    | -       | 400     | kHZ                 |
| Bus Free Time Between STOP and START Condition             | t <sub>BUF</sub>    | 1.3     | -       | -       | μs                  |
| Hold Time (Repeated) START Condition, to First Clock Pulse | t <sub>HD,STA</sub> | 0.8     | -       | -       | μs                  |
| Low Period of SCL                                          | t <sub>Low</sub>    | 1.3     | -       | -       | μs                  |
| High Period of SCL                                         | t <sub>High</sub>   | 0.6     | -       | -       | μs                  |
| Setup Time Repeated START Condition                        | t <sub>SU,STA</sub> | 1       | -       | -       | μs                  |

**Note:** All Sensors recommends communication speeds of at least 100 kHz (max. 640 kHz). Please contact your nearest All Sensors sales office for further information.




Figure 2. Timing Characteristics

# SPI - SERIAL PERIPHERAL INTERFACE

## Introduction

The ELVR series is capable of producing a digital output signal. The device runs a cyclic program, which will store a corrected sensor value with 12 or 13 bit resolution about every 9 ms within the output registers of the internal ASIC. This cyclic program runs independent from the bus communication. In order to use the pressure sensor for digital signal readout, it should be connected to a SPI Master device.

SPI specifies four signals: The clock (CLK) is generated by the master and input to all slaves. MOSI carries data from master to slave. MISO carries data from slave back to master. A slave select line (SS) allows individual selection of a slave device.

## SPI Modes

A pair of parameters called clock polarity (CPOL) and clock phase (CPHA) determine the edges of the clock signal on which the data are driven and sampled. Each of the two parameters has two possible states, which allows for four possible combinations, all of which are incompatible with one another.

The ELVR series supports all clock phase (CPHA)=0 and polarity (CPOL)=0. CPOL which means that data transmission starts with the rising first clock edge (see Figure 3).

## Slave select

The falling edge of the SS line indicates the beginning of the transfer. Additionally the SS line must not be negated and reasserted between the three bytes to be transmitted.

## Data operation

The MOSI line should always be set to high level. So there is no data transmission from master to slave. Because of internal configuration the slave will answer the first byte with an FFxh. The second and third byte contain the 15 bit pressure information (see Figure 4).




Figure 3: Example of a standard 1 byte SPI data transfer for CPHA=0 and CPOL=0




Figure 4: 3 byte data stream between ELVR sensor and master containing the pressure value as a 15 bit value.



## SPI - SERIAL PERIPHERAL INTERFACE (Cont'd)

### Interface Parameters

| Parameter                               | Symbol              | Minimum     | Nominal | Maximum | Unit       |
|-----------------------------------------|---------------------|-------------|---------|---------|------------|
| Input High Level                        | -                   | 90          | -       | 100     | % of $V_s$ |
| Input Low Level                         | -                   | 0           | -       | 10      | % of $V_s$ |
| Output Low Level                        | -                   | -           | -       | 10      | % of $V_s$ |
| Pull-Up Resistor                        | -                   | 500         | -       | -       | $\Omega$   |
| Load Capacitance @ MISO                 | $C_{MISO}$          | -           | -       | 400     | pF         |
| Input Capacitance @ Each Pin            | $C_{SPL\_IN}$       | -           | -       | 10      | pF         |
| Signal Clock Frequency                  | $f_{SCK}$           | 100*        | -       | 640     | KHZ        |
| MISO Hold Time after SCK Sample Slope   | $t_{SPL\_HD\_MISO}$ | 200         | -       | -       | ns         |
| MOSI Setup Time Before SCK Sample Slope | $t_{SPL\_SU\_MOSI}$ | $2/f_{CLK}$ | -       | -       | -          |
| /SS Setup Time Before SCK Sample Slope  | $t_{SPL\_SU\_SS}$   | 10          | -       | -       | ns         |
| /SS Hold Time After SCK Sample Slope    | $t_{SPL\_HD\_SS}$   | $1/f_{CLK}$ | -       | -       | -          |

**Note:** All Sensors recommends communication speeds of at least 100 kHz (max. 640 kHz). Please contact your nearest All Sensors sales office for further information.




Figure 5: Timing characteristics

## How to Order

Refer to Table 1 for configuring a standard base part number which includes the pressure range, package and temperature range. Table 2 shows the available configuring options. The option identifier is required to complete the device part number. Refer to Table 3 for the available device package options.

Example P/N with options: ELVR-L01D-F1RS-C-NI3F






Table 1 - How to configure a base part number

| ORDERING INFORMATION | SERIES | PRESSURE RANGE |               | PACKAGE |                  |              |                 | TEMPERATURE RANGE |                  |
|----------------------|--------|----------------|---------------|---------|------------------|--------------|-----------------|-------------------|------------------|
|                      | ID     | ID             | Description   | Base ID | Port Orientation | Lid Style ID | Description     | Lead Type ID      | Description      |
|                      | ELVR   | L01D           | ±1 inH2O      | F       | 1                | R            | Long Non-Barbed | T                 | SIL (see note 7) |
|                      |        | L05D           | ±5 inH2O      |         | N                | S            | Long Barbed     | D                 | DIP              |
|                      |        | L10D           | ±10 inH2O     |         |                  |              |                 | J                 | J-Lead SMT       |
|                      |        | L20D           | ±20 inH2O     |         |                  |              |                 | L                 | L-Lead SMT       |
|                      |        | L30D           | ±30 inH2O     |         |                  |              |                 |                   |                  |
|                      |        | L01G           | 0 to 1 inH2O  |         |                  |              |                 |                   |                  |
|                      |        | L05G           | 0 to 5 inH2O  |         |                  |              |                 |                   |                  |
|                      |        | L10G           | 0 to 10 inH2O |         |                  |              |                 |                   |                  |
|                      |        | L20G           | 0 to 20 inH2O |         |                  |              |                 |                   |                  |
|                      |        | L30G           | 0 to 30 inH2O |         |                  |              |                 |                   |                  |
| Example              | ELVR   | L01D           |               | F       | 1                | R            |                 | S                 | C                |
|                      |        |                |               |         |                  |              |                 |                   | I                |

Table 2 - How to configure an option identifier

| ORDERING INFORMATION | COATING |                               | INTERFACE |                          |         | SUPPLY VOLTAGE |             | DIGITAL RESOLUTION, UPDATE RATE |                              |
|----------------------|---------|-------------------------------|-----------|--------------------------|---------|----------------|-------------|---------------------------------|------------------------------|
|                      | ID      | Description                   | ID        | Description              | Address | ID             | Description | ID                              | Description                  |
|                      | N       | No Coating                    | A         | Analog Only (see note 7) | N/A     | 3              | 3.0V        | F                               | Fast Mode (12bit, 0.5ms)     |
|                      | P       | Parylene Coating (see note 8) | I         | I2C & Analog             | 0x78    | 5              | 5.0V        | H                               | High Resolution (14bit, 1ms) |
|                      |         |                               | S         | Option- SPI & Analog     | N/A     |                |             |                                 |                              |
|                      |         |                               | 2         | Option- I2C & Analog     | 0x28    |                |             |                                 |                              |
|                      |         |                               | 3         | Option- I2C & Analog     | 0x38    |                |             |                                 |                              |
|                      |         |                               | 4         | Option- I2C & Analog     | 0x48    |                |             |                                 |                              |
|                      |         |                               | 5         | Option- I2C & Analog     | 0x58    |                |             |                                 |                              |
|                      |         |                               | 6         | Option- I2C & Analog     | 0x68    |                |             |                                 |                              |
| Example              | N       |                               | I         |                          |         | 3              |             | F                               |                              |

TABLE 3: Available F-Series Package Configurations

| Port Orientation    | Non-Barbed Lid                                                                      |                                                                                     |                                                                                     |                                                                                     | Barbed Lid                                                                          |                                                                                       |                                                                                       |                                                                                       |
|---------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                     | Lead Style                                                                          |                                                                                     |                                                                                     |                                                                                     | Lead Style                                                                          |                                                                                       |                                                                                       |                                                                                       |
|                     | SIL                                                                                 | DIP                                                                                 | SMT-J                                                                               | SMT-L                                                                               | SIL                                                                                 | DIP                                                                                   | SMT-J                                                                                 | SMT-L                                                                                 |
| Dual Port Same Side |  |  |  |  |  |  | NOT OFFERED                                                                           |  |
|                     | F1RT                                                                                | F1RD                                                                                | F1RJ                                                                                | F1RL                                                                                | F1ST                                                                                | F1SD                                                                                  | NOT OFFERED                                                                           | F1SL                                                                                  |
| Single Port         |  |  |  |  |  |  |  |  |
|                     | FNRT                                                                                | FNRD                                                                                | FNRJ                                                                                | FNRL                                                                                | FNST                                                                                | FNSD                                                                                  | FNSJ                                                                                  | FNSL                                                                                  |



### Specification Notes (Cont.)

**NOTE 7: LEADFRAME "T" HAS ONLY ANALOG OUTPUT CAPABILITY. ALL LEAD TYPES EXCEPT FOR "T" HAVE SIMULTANEOUS DIGITAL AND ANALOG OUTPUT CAPABILITY.**



**NOTE 8: PARYLENE COATING NOT OFFERED IN J-LEAD SMT CONFIGURATION. PARYLENE COATING IS NOT OFFERED FOR PRESSURE RANGES BELOW 10 inH2O.**





## Package Drawings



Package Drawings (Cont'd)



## Package Drawings (Cont'd)



### NOTES



- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-28.

|     | I2C            | SPI            |
|-----|----------------|----------------|
| Pin | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |

## All Sensors

TITLE: F-Series Package

SIZE: FILE NAME: A FIRJ Package



### NOTES

- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-28.



|     | I2C            | SPI            |
|-----|----------------|----------------|
| Pin | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |

## All Sensors

TITLE: F-Series Package

SIZE: FILE NAME: A FNRJ Package

## Package Drawings (Cont'd)



### NOTES



- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-29.

|     | I2C            | SPI            |
|-----|----------------|----------------|
| Pin | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |

## All Sensors

TITLE: F-Series Package

SIZE: A FILE NAME: F1RL Package



### NOTES

- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-29.

|     | I2C            | SPI            |
|-----|----------------|----------------|
| Pin | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |



## All Sensors

TITLE: F-Series Package



SIZE: A FILE NAME: FNRL Package





Package Drawings (Cont'd)



## Package Drawings (Cont'd)



## Package Drawings (Cont'd)



### NOTES



- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-29.

|     | I2C            | SPI            |
|-----|----------------|----------------|
| Pin | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |

## All Sensors

TITLE: F-Series Package

SIZE FILE NAME  
A F1SL Package



### NOTES

- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-29.



|     | I2C            | SPI            |
|-----|----------------|----------------|
| Pin | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |

## All Sensors

TITLE: F-Series Package

SIZE FILE NAME  
A F1SL Package

## Package Drawings (Cont'd)



### NOTES

- 1) Dimensions are in inches [mm].
- 2) For suggested pad layout, see drawing: PAD-28.

| Pin | I2C            | SPI            |
|-----|----------------|----------------|
|     | Definition     | Definition     |
| 1   | Vs             | Vs             |
| 2   | Gnd            | Gnd            |
| 3   | Vout           | Vout           |
| 4   | Do not Connect | MISO           |
| 5   | SCL            | CLK            |
| 6   | Do not Connect | SS             |
| 7   | Do not Connect | Do not Connect |
| 8   | SDA            | MOSI           |


## All Sensors

TITLE: F-Series Package

SIZE: **A** FILE NAME: FNSJ Package




## Product Labeling




Example Device Label


## Suggested Pad Layouts




PAD-01



PAD-27



PAD-28



PAD-29

All Sensors reserves the right to make changes to any products herein. All Sensors does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)