



**UNIDIRECTIONAL P-GATE THYRISTOR  
OVERVOLTAGE AND OVERCURRENT PROTECTOR**

**TISP8250D Overvoltage and Overcurrent Protector**

Telecommunication System 30 A 10/1000 Protector

**Ion-Implanted Breakdown Region  
- Precise and Stable Voltage**

Device Name	V <sub>DRM</sub> V	V <sub>(BO)</sub> V
TISP8250D	250	340


**Rated for International Surge Wave Shapes**

Wave Shape	Standard	I <sub>PPSM</sub> A
2/10	GR-1089-CORE	75
0.5/700	CNET I 31-24	40
10/700	ITU-T K.20/21	40
10/1000	GR-1089-CORE	30


**Functional Replacement for TPP25011**

 ..... **UL Recognized Component**

**8-SOIC Package (Top View)**



**Device Symbol**



**Description**

The TISP8250D is a P-gate reverse-blocking thyristor (SCR) designed for the protection of telecommunications equipment against overvoltages and overcurrents on the telephone line caused by lightning, a.c. power contact and induction. The fixed voltage and current triggered modes make the TISP8250D particularly suitable for the protection of ungrounded customer premise equipment. Connected across the d.c. side of a telephone set polarity bridge, in fixed voltage mode these devices can protect the ringer in the on-hook condition. In an off-hook condition, either the fixed voltage or current triggered modes can protect the following telephone electronics.

Without external gate activation, the TISP8250D is a fixed voltage protector. The maximum working voltage without clipping is 250 V and the protection voltage is 340 V. Lower values of protection voltage may be set by connecting an avalanche breakdown diode of less than 250 V between the TISP8250D gate and anode (see Figure 2.)

By connecting a small value resistor in series with the line conductor and connecting the TISP8250D gate cathode terminals in parallel with the resistor, conductor overcurrents can gate trigger the TISP8250D into conduction.

Overvoltages are initially clipped by breakdown clamping until the voltage rises to the breakover level, which causes the device to crowbar into a low-voltage on state. Overcurrents develop sufficient voltage across the external gate-cathode resistor to trigger the device into a low-voltage on state. This low-voltage on state causes the current resulting from the overstress to be safely diverted through the device. The high crowbar holding current prevents d.c. latchup as the diverted current subsides.

**How To Order**

Device	Package	Carrier	For Standard Termination Finish Order As	For Lead Free Termination Finish Order As	Marking Code	Standard Quantity
TISP8250D	8-SOIC	Embossed Tape Reeled	TISP8250DR	TISP8250DR-S	8250	2500
		Tube	TISP8250D	TISP8250D-S		1500

\*RoHS Directive 2002/95/EC Jan 27 2003 including Annex  
JULY 2000 - REVISED MARCH 2005  
Specifications are subject to change without notice.  
Customers should verify actual device performance in their specific applications.

# TISP8250D Overvoltage and Overcurrent Protector

# BOURNS®

## Absolute Maximum Ratings, $T_A = 25\text{ }^\circ\text{C}$ (Unless Otherwise Noted)

Rating	Symbol	Value	Unit
Repetitive peak off-state voltage (see Note 1)	$V_{\text{DRM}}$	250	V
Non-repetitive peak impulse current (see Notes 2, 3 and 4) 2/10 $\mu\text{s}$ (Telcordia GR-1089-CORE, 2/10 $\mu\text{s}$ waveshape) 0.2/310 (CNET I 31-24, 0.5/700 $\mu\text{s}$ waveshape) 5/310 $\mu\text{s}$ (ITU-T K.20/21, 10/700 $\mu\text{s}$ voltage waveshape) 5/310 $\mu\text{s}$ (FTZ R12, 10/700 $\mu\text{s}$ voltage waveshape) 10/1000 $\mu\text{s}$ (Telcordia GR-1089-CORE, 10/1000 $\mu\text{s}$ voltage waveshape)	$I_{\text{PPSM}}$	75 40 40 40 30	A
Non-repetitive peak on-state current, 50 Hz (see Notes 2, 3 and 4) 10 ms half sine wave 1 s rectified sine wave 1000 s rectified sine wave	$I_{\text{TSM}}$	5 3.5 0.7	A
Junction temperature	$T_J$	-40 to +150	$^\circ\text{C}$
Storage temperature range	$T_{\text{stg}}$	-65 to +150	$^\circ\text{C}$

- NOTES: 1. For voltage values at lower temperatures, derate at 0.13 %/ $^\circ\text{C}$ .  
 2. Initially the device must be in thermal equilibrium, with  $T_J = 25\text{ }^\circ\text{C}$ .  
 3. The surge may be repeated after the device returns to its initial conditions.  
 4. EIA/JESD51-2 environment and EIA/JESD51-3 PCB with standard footprint dimensions connected with 5 A printed wiring track widths. Derate current values at -0.61 %/ $^\circ\text{C}$  for ambient temperatures above  $25\text{ }^\circ\text{C}$ .

## Electrical Characteristics, $T_A = 25\text{ }^\circ\text{C}$ (Unless Otherwise Noted)

Parameter	Test Conditions	Min	Typ	Max	Unit
$I_{\text{DRM}}$ Repetitive peak off-state current	$V_D = V_{\text{DRM}}$ $T_A = 25\text{ }^\circ\text{C}$ $T_A = 85\text{ }^\circ\text{C}$			5 10	$\mu\text{A}$
$V_{(\text{BO})}$ Breakover voltage	$dv/dt = 250\text{ V/ms}$ , $R_{\text{SOURCE}} = 300\ \Omega$			340	V
$I_{(\text{BO})}$ Breakover current	$dv/dt = 250\text{ V/ms}$ , $R_{\text{SOURCE}} = 300\ \Omega$	15		200	mA
$I_H$ Holding current	$I_T = 5\text{ A}$ , $di/dt = -30\text{ mA/ms}$	180			mA
$V_{\text{GK}}$ Gate-cathode voltage	$I_G = 30\text{ mA}$	0.6		1.2	V
$I_{\text{GT}}$ Gate trigger current	$V_{\text{AK}} = 100\text{ V}$			40	mA
$I_D$ Off-state current	$V_D = 60\text{ V}$			5	$\mu\text{A}$
$C_O$ Off-state capacitance	$f = 1\text{ MHz}$ , $V_d = 1\text{ V rms}$ , $V_D = 5\text{ V}$			100	pF

## Thermal Characteristics, $T_A = 25\text{ }^\circ\text{C}$ (Unless Otherwise Noted)

Parameter	Test Conditions	Min	Typ	Max	Unit
$R_{\theta\text{JA}}$ Junction to ambient thermal resistance	EIA/JESD51-3 PCB, $I_T = I_{\text{TSM}(1000)}$ (see Note 5)			170	$^\circ\text{C/W}$

- NOTE 5. EIA/JESD51-2 environment and PCB has standard footprint dimensions connected with 5A rated printed wiring track widths.

## Parameter Measurement Information




Figure 1. Voltage-Current Characteristic for A and K Terminals  
All Measurements are Referenced to the K Terminal




Figure 2. Overvoltage Protection Circuit

### **Bourns Sales Offices**

Region	Phone	Fax
The Americas:	+1-951-781-5500	+1-951-781-5700
Europe:	+41-41-7685555	+41-41-7685510
Asia-Pacific:	+886-2-25624117	+886-2-25624116

### **Technical Assistance**

Region	Phone	Fax
The Americas:	+1-951-781-5500	+1-951-781-5700
Europe:	+41-41-7685555	+41-41-7685510
Asia-Pacific:	+886-2-25624117	+886-2-25624116

**[www.bourns.com](http://www.bourns.com)**

Bourns® products are available through an extensive network of manufacturer's representatives, agents and distributors. To obtain technical applications assistance, a quotation, or to place an order, contact a Bourns representative in your area.



*Reliable Electronic Solutions*

"TISP" is a trademark of Bourns, Ltd., a Bourns Company, and is Registered in U.S. Patent and Trademark Office.  
"Bourns" is a registered trademark of Bourns, Inc. in the U.S. and other countries.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)