

VE Series

Features

- 3 ϕ ~ 18 ϕ , 85°C, 2,000 hours assured
- Chip type large capacitance capacitors
- Designed for surface mounting on high density PC board
- RoHS Compliance



Marking color: Black

Specifications

| Items | Performance | | | | | | | | | | | | | |
|--|---|---|--|------|------|--------|----|----|----|----|----|-----|-----------|-----------|
| Category Temperature Range | -40°C ~ +85°C | | | | | | | | | | | | | |
| Capacitance Tolerance | ±20% (at 120Hz, 20°C) | | | | | | | | | | | | | |
| Leakage Current (at 20°C) | Rated Voltage | 6.3 ~ 100V | | | | | | | | | | | | |
| | Time | after 2 minutes | | | | | | | | | | | | |
| | Case size | 3 ~ 10 ϕ | | | | | | | | | | | | |
| | Leakage Current | I = 0.01CV or 3 μ A, whichever is greater | | | | | | | | | | | | |
| Tan δ (at 120Hz, 20°C) | Rated Voltage | 4 6.3 10 16 25 35 50 63 100 160 ~ 250 400 ~ 450 | | | | | | | | | | | | |
| | 3 ~ 10 ϕ | 0.42 0.28 0.24 0.20 0.14 0.12 0.10 0.10 0.10 - - | | | | | | | | | | | | |
| | 12.5 ~ 18 ϕ | - 0.38 0.34 0.30 0.26 0.22 0.18 0.14 0.10 0.20 0.25 | | | | | | | | | | | | |
| | When the capacitance exceeds 1,000 μ F, 0.02 shall be added every 1,000 μ F increase. | | | | | | | | | | | | | |
| Low Temperature Characteristics (at 120Hz) | Impedance ratio shall not exceed the values given in the table below. | | | | | | | | | | | | | |
| | Impedance Ratio | Rated Voltage | | 4.0 | 6.3 | 10 | 16 | 25 | 35 | 50 | 63 | 100 | 160 ~ 250 | 400 ~ 450 |
| | | Z(-25°C) | ϕ D < 12.5 | 7 | 4 | 4 | 3 | 2 | 2 | 2 | 2 | 2 | - | - |
| | | /Z(+20°C) | ϕ D \geq 12.5 | - | 5 | 5 | 4 | 2 | 2 | 2 | 2 | 2 | 3 | 6 |
| Z(-40°C) | | ϕ D < 12.5 | 15 | 8 | 5 | 4 | 3 | 3 | 3 | 3 | 3 | - | - | |
| Endurance | Test Time | 2,000 Hrs | | | | | | | | | | | | |
| | Capacitance Change | Within ±20% of initial value (4V: ±30%) | | | | | | | | | | | | |
| | Tan δ | Less than 200% of specified value (4V: ±300%) | | | | | | | | | | | | |
| | Leakage Current | Within specified value | | | | | | | | | | | | |
| Shelf Life Test | * The above Specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied for 2,000 hours at 85°C. | | | | | | | | | | | | | |
| Ripple Current & Frequency Multipliers | Test time: 1,000 hours; other items are the same as those for the Endurance. | | The rated voltage shall be applied to the capacitors before the measurements for 160 ~ 450V (Refer to JIS C 5101-4 4.1). | | | | | | | | | | | |
| | Freq. (Hz) | | 50 | 120 | 1k | 10k up | | | | | | | | |
| Cap. (μ F) | | Under 1,000 | 0.80 | 1.00 | 1.25 | 1.40 | | | | | | | | |
| | | 1,000 < C \leq 10,000 | 0.85 | 1.00 | 1.15 | 1.25 | | | | | | | | |

Diagram of Dimensions

Fig. 1



Fig. 2



Lead Spacing and Diameter

Unit: mm

| ϕ D | L | A | B | C | W | P ± 0.2 | Fig. No. |
|----------|------------|------|------|------|-------------|---------|----------|
| 3 | 5.3 ± 0.2 | 3.3 | 3.3 | 4.1 | 0.45 ~ 0.75 | 0.8 | 1 |
| 4 | 5.3 ± 0.2 | 4.3 | 4.3 | 5.1 | 0.5 ~ 0.8 | 1.0 | 1 |
| 5 | 5.3 ± 0.2 | 5.3 | 5.3 | 5.9 | 0.5 ~ 0.8 | 1.5 | 1 |
| 6.3 | 5.3 ± 0.2 | 6.6 | 6.6 | 7.2 | 0.5 ~ 0.8 | 2.0 | 1 |
| 6.3 | 7.7 ± 0.3 | 6.6 | 6.6 | 7.2 | 0.5 ~ 0.8 | 2.0 | 1 |
| 8 | 6.5 ± 0.3 | 8.4 | 8.4 | 9.0 | 0.5 ~ 0.8 | 2.3 | 1 |
| 8 | 10 ± 0.5 | 8.4 | 8.4 | 9.0 | 0.7 ~ 1.1 | 3.1 | 1 |
| 10 | 7.7 ± 0.3 | 10.4 | 10.4 | 11.0 | 0.7 ~ 1.3 | 4.7 | 1 |
| 10 | 10 ± 0.5 | 10.4 | 10.4 | 11.0 | 0.7 ~ 1.3 | 4.7 | 1 |
| 12.5 | 13.5 ± 0.5 | 13.0 | 13.0 | 13.7 | 1.1 ~ 1.4 | 4.4 | 2 |
| 12.5 | 16 ± 0.5 | 13.0 | 13.0 | 13.7 | 1.1 ~ 1.4 | 4.4 | 2 |
| 16 | 16.5 ± 0.5 | 17.0 | 17.0 | 18.0 | 1.1 ~ 1.4 | 6.4 | 2 |
| 16 | 21.5 ± 0.5 | 17.0 | 17.0 | 18.0 | 1.1 ~ 1.4 | 6.4 | 2 |
| 18 | 16.5 ± 0.5 | 19.0 | 19.0 | 20.0 | 1.1 ~ 1.4 | 6.4 | 2 |
| 18 | 21.5 ± 0.5 | 19.0 | 19.0 | 20.0 | 1.1 ~ 1.4 | 6.4 | 2 |

Marking

$\phi D = 3 \text{ mm}$



$\phi D = 4 \sim 6.3 \text{ mm}$



$\phi D = 8 \sim 10 \text{ mm}$



$\phi D \geq 12.5 \text{ mm}$



Dimension: $\phi D \times L(\text{mm})$

Ripple Current: mA/rms at 120 Hz, 85°C

Dimension & Permissible Ripple Current

| μF | V. DC Contents | 4V (0G) | | 6.3V (0J) | | 10V (1A) | | 16V (1C) | | 25V (1E) | | 35V (1V) | | 50V (1H) | | 63 (1J) | | | |
|---------------|----------------|--------------------|-----------|--------------------|----------------|--------------------------|-------------------|-----------------------------|------------------|--------------------|----------------|--------------------|----------------|--------------------|----------------|-------------------|----------|-------|-----|
| | | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | | |
| 1 | 010 | | | | | | | | | | | | | 4×5.3 | 10 | 4×5.3 | 8 | | |
| 2.2 | 2R2 | | | | | | | | | | | | | 4×5.3 | 14 | 4×5.3 | 12 | | |
| 3.3 | 3R3 | | | | | | | | | 3×5.3 | 14 | 3×5.3 | 14 | 4×5.3 | 17 | 5×5.3 | 22 | | |
| 4.7 | 4R7 | | | | | 3×5.3 | 14 | 3×5.3 | 14 | 4×5.3 | 26 | 4×5.3 | 26 | 4×5.3 | 20 | 5×5.3 | 25 | | |
| 10 | 100 | | | 3×5.3 | 16 | 4×5.3 | 26 | 4×5.3 | 26 | 5×5.3 | 44 | 5×5.3 | 44 | 5×5.3 | 35 | 6.3×5.3 8×6.5 | 40 46 | | |
| 22 | 220 | 3×5.3 | 16 | 4×5.3 | 26 | 5×5.3 | 44 | 4×5.3 5×5.3 | 30 44 | 5×5.3 6.3×5.3 | 47 59 | 5×5.3 6.3×5.3 | 47 59 | 6.3×5.3 6.3×7.7 | 50 65 | 8×10 | 139 | | |
| 33 | 330 | 4×5.3 | 31 | 4×5.3 | 31 | 4×5.3 5×5.3 | 31 55 | 5×5.3 | 55 | 5×5.3 6.3×5.3 | 55 67 | 6.3×5.3 6.3×7.7 | 67 85 | 6.3×7.7 8×6.5 | 75 95 | 8×10 | 139 | | |
| 47 | 470 | 4×5.3 | 34 | 4×5.3 5×5.3 | 34 55 | 6.3×5.3 | 75 | 5×5.3 6.3×5.3 | 55 75 | 6.3×5.3 6.3×7.7 | 75 98 | 6.3×5.3 8×6.5 | 75 105 | 6.3×7.7 8×10 | 75 190 | 10×10 | 200 | | |
| 68 | 680 | 5×5.3 | 58 | 5×5.3 6.3×5.3 | 58 89 | 5×5.3 6.3×5.3 | 58 89 | 6.3×5.3 | 89 | 6.3×7.7 | 109 | 6.3×7.7 | 109 | 8×10 | 190 | 10×10 | 226 | | |
| 100 | 101 | 5×5.3 6.3×5.3 | 58 89 | 6.3×5.3 | 89 | 6.3×5.3 6.3×7.7 | 89 109 | 6.3×5.3 6.3×7.7 8×6.5 | 89 109 125 | 6.3×7.7 | 109 | 8×6.5 | 145 | 8×10 | 252 | 8×10 | 190 | 10×10 | 226 |
| 150 | 151 | | | | | | | | | | | | 10×7.7 | 252 | | | | | |
| 220 | 221 | 6.3×5.3 6.3×7.7 | 89 124 | 6.3×5.3 6.3×7.7 | 89 124 | 6.3×7.7 8×6.5 8×10 | 124 175 270 | 6.3×7.7 8×10 | 124 270 | 8×10 10×7.7 | 270 270 | 8×10 10×10 | 270 370 | 10×10 | 320 | 12.5×13.5 | 500 | | |
| 330 | 331 | 6.3×7.7 | 124 | 6.3×7.7 8×6.5 | 124 190 | 8×10 | 290 | 8×10 10×7.7 | 290 290 | 10×10 | 400 | 10×10 | 400 | 12.5×13.5 | 600 | 12.5×16 | 600 | | |
| 470 | 471 | 8×10 | 290 | 8×10 | 290 | 10×7.7 10×10 | 290 400 | 10×10 | 400 | 10×10 | 400 | 12.5×13.5 | 680 | 12.5×16 | 740 | 16×16.5 | 850 | | |
| 680 | 681 | | | 10×7.7 | 290 | 10×10 | 410 | 10×10 | 410 | 12.5×13.5 | 680 | 12.5×13.5 | 680 | 16×16.5 | 1,000 | 18×16.5 | 1,100 | | |
| 1,000 | 102 | | | 10×10 | 430 | 10×10 | 430 | 12.5×13.5 | 750 | 12.5×13.5 | 750 | 16×16.5 | 1,100 | 18×16.5 16×21.5 | 1,350 1,400 | | | | |
| 2,200 | 222 | | | 12.5×13.5 | 890 | 12.5×13.5 | 890 | 16×16.5 | 1,100 | 16×16.5 | 1,100 | 18×16.5 16×21.5 | 1,450 1,500 | | | | | | |
| 3,300 | 332 | | | 12.5×16 | 1,000 | 16×16.5 | 1,300 | 16×16.5 | 1,300 | 18×16.5 16×21.5 | 1,450 1,500 | 18×21.5 | 1,750 | | | | | | |
| 4,700 | 472 | | | 16×16.5 | 1,400 | 16×16.5 | 1,400 | 18×16.5 16×21.5 | 1,600 1,650 | 18×21.5 | 1,750 | | | | | | | | |
| 6,800 | 682 | | | 18×16.5 16×21.5 | 1,700 1,750 | 18×16.5 16×21.5 | 1,700 1,750 | 18×21.5 | 2,000 | | | | | | | | | | |
| 10,000 | 103 | | | 18×21.5 | 2,000 | 18×21.5 | 2,000 | | | | | | | | | | | | |

| μF | V. DC Contents | 100V (2A) | | 160V (2C) | | 200V (2D) | | 250V (2E) | | 400V (2G) | | 450V (2W) | |
|---------------|----------------|--------------------|------------|--------------------|------------|--------------------|------------|--------------------|------------|-------------------|-----|-------------------|-----|
| | | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA | $\phi D \times L$ | mA |
| 4.7 | 4R7 | | | | | | | | | 12.5×13.5 | 120 | 12.5×13.5 | 120 |
| 10 | 100 | 8×10 | 90 | | | | | 12.5×13.5 | 150 | 12.5×13.5 | 120 | 12.5×16 | 130 |
| 22 | 220 | 8×10 | 90 | | | 12.5×13.5 | 240 | 12.5×13.5 | 150 | 16×16.5 | 140 | 16×16.5 | 140 |
| 33 | 330 | 10×10 | 120 | 12.5×13.5 | 290 | 12.5×16 | 310 | 12.5×16 | 240 | 16×16.5 | 140 | 18×16.5 | 180 |
| 47 | 470 | 10×10 | 120 | 12.5×16 | 370 | 16×16.5 | 420 | 16×16.5 | 340 | 18×16.5 | 280 | 18×21.5 | 250 |
| 68 | 680 | 12.5×13.5 | 380 | 16×16.5 | 500 | 16×16.5 | 420 | 18×16.5 16×21.5 | 440 450 | 18×21.5 | 350 | | |
| 100 | 101 | 12.5×13.5 | 440 | 18×16.5 16×21.5 | 650 690 | 18×16.5 16×21.5 | 550 590 | 18×21.5 | 490 | | | | |
| 220 | 221 | 16×16.5 | 600 | | | | | | | | | | |
| 330 | 331 | 18×16.5 16×21.5 | 780 850 | | | | | | | | | | |

Part Numbering System

VE series 470 μF $\pm 20\%$ 6.3V Carrier Tape 8 ϕ × 10L Pb-free and PET coating case

VE- **471** **M** **OJ** **TR** - **0810**

Series name Capacitance Capacitance Tolerance Rated Voltage Package Type Terminal Type Case size Lead Wire and Coating Type

Note: For more details, please refer to "Part Numbering System (SMD Type)" on page 12.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru