



SSRM series

45-65A DIN Mount Solid State Relay With Paired SCR Output, Integral Heatsink

File E29244

Users should thoroughly review the technical data before selecting a product part number. It is recommended that users also seek out the pertinent approvals files of the agencies/laboratories and review them to confirm the product meets the requirements for a given application.

Features

- DIN mount design with integral heatsink.
- Choice of 45, 55 or 65A rms inverse-parallel connected SCR output.
- 48 - 660VAC output.
- 4 -32VDC or 90 - 140Vrms input control.
- 4,000V rms optical isolation.
- Green LED input status indicator.
- Finger-safe (IP20) screw clamp terminals for load and control.
- Ground terminal.

Engineering Data

Form: 1 Form A (SPST-NO).

Duty: Continuous.

Isolation: 4,000V rms input-to-output-to-ground.

Insulation Resistance: 10⁹ Ohms, minimum, at 500VDC.

Capacitance: 8.0 pf maximum (input to output).

Temperature Range:

Storage: -40°C to +125°C

Operating: -40°C to + 80°C

Case and Mounting: Refer to outline dimension drawing.

Termination:

Control: Finger safe (IP20) screw clamps accepting wire size up to #12 AWG (2.5 mm).

Load: Finger safe (IP20) screw clamps accepting wire size up to #8 AWG (3.8 mm).

Ground: #10 screw with 5/16 in. hex/slotted head.

Installation Spacing: Minimum 0.8 in (20 mm) space between units.

Approximate Weight: 16.9 oz. (479 g).

Ordering Information

Sample Part Number ▶

SSRM

-600

A

55

1. Basic Series: SSRM = Solid State Relay with Integral Heatsink for DIN Rail Mounting

2. Line Voltage: 600 = 48 - 660 VAC

3. Input Type & Voltage: A = 90 - 140VAC
D = 4 - 32VDC

4. Maximum Switching Rating/Output: 45 = 45.0A rms
55 = 55.0A rms
65 = 65.0A rms

Our authorized distributors are more likely to maintain the following items in stock for immediate delivery.

SSRM-600A45
SSRM-600D45

SSRM-600A55
SSRM-600D55

SSRM-600A65
SSRM-600D65

Input Specifications


Parameter	Conditions	AC Control Units	DC Control Units
Control Voltage Range V _{IN}	@ 25°C	90 - 140 Vrms	4.0 - 32 VDC
Reverse Voltage V _{IN(Max.)}	@ 25°C	—	32 VDC
Must Operate Voltage V _{IN(OP)} (Min.)	@ 25°C	90 Vrms	4.0 VDC
Must Release Voltage V _{IN(REL)} (Min.)	@ 25°C	10 Vrms	1.0 VDC
Input Current (Typ.)	@ 25°C	15 mA @ 120 Vrms	14 mA @ 5 VDC
Input Current (Max.)	@ 25°C	—	30 mA

Output Specifications (@ 25° C, unless otherwise specified)

Parameter	Conditions	Units	45A Rated Units	55A Rated Units	65A Rated Units
Load Voltage Range V_L	$f = 47 - 63 \text{ Hz.}$	V rms	48 - 660	48 - 660	48 - 660
Repetitive Blocking Voltage (Min.)		V peak	± 1200	± 1200	± 1200
Load Current Range I_L^*		A rms	0.15 - 45.0	0.25 - 55.0	0.25 - 65.0
Single Cycle Surge Current (Min.)		A peak	625	1,000	1,200
Leakage Current (Off-State) (Max.)	$f = 60 \text{ Hz. } V_L = 600\text{Vrms}$	mA rms	1.0	1.0	1.0
Thermal Resistance Junction to Case $R_{\theta J-C}$ (Max.)		°C/W	0.63	0.31	0.28
On-State Voltage Drop (Max.)	$I_L = \text{Max.}$	V peak	1.7	1.7	1.7
Static dv/dt (Off-State) (Min.)	$V_L = \text{Max.}$	V/ μs	500	500	500
Turn-On Time (Max.)	$f = 60 \text{ Hz.}$	ms	8.3 for DC Input Models, 10.0 for AC Input Models		
Turn-Off Time (Max.)	$f = 60 \text{ Hz.}$	ms	8.3 for DC Input Models, 40.0 for AC Input Models		
$I^2 t$ Rating (Max.)	$t = 8.3 \text{ ms}$	A ² Sec.	1,620	4,150	6,000
Load Power Factor Rating (Min.)	$I_L = \text{Max.}$		0.5	0.5	0.5

*See Thermal Derating Curves.

Electrical Characteristics (Thermal Derating Curves)




Disclaimer

While Tyco Electronics has made every reasonable effort to ensure the accuracy of the information in this document, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current.

Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose.

The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult Tyco Electronics for the latest dimensions and design specifications.

Outline Dimensions



Recommended Torque Range for Terminal Screws:
 Control: 5 - 6 in lb (0.6 - 0.7 Nm).
 Output: 10 - 15 in lb (1.1 - 1.7 Nm).

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru