



# Micro-D Metal Shell MWDM Back-To-Back Unshielded Cable Assemblies

B



**Save Time and Money With Back-To-Back Cables**– These Micro-D connectors feature crimp wire terminations and epoxy encapsulation. The installed cost is lower than terminating solder cup connectors.

**100% Certified**– all back-to-back assemblies are 100% checked for continuity, resistance, voltage and insulation resistance.

**Hardware Note**– if jackposts are required on one end and jackscrews on the other, use hardware designator “B” (no hardware installed), and order hardware kits separately.

## HOW TO ORDER BACK-TO-BACK UNSHIELDED CABLES

| Series                    | Shell Material and Finish  | Insulator Material                                 | Contact Layout | Connect or Type  | Wire Gage (AWG) | Wire Type   | Wire Color   | Total Length Inches   | Hardware   |
|---------------------------|--|--|----------------|--|-----------------|---|--|---|--|
| MWDM                      | <b>Aluminum Shell</b><br>1 – Cadmium<br>2 – Nickel<br>4 – Black Anodize<br>5 – Gold<br>6 – Chem Film | L – LCP<br>30% Glass-Filled Liquid Crystal Polymer | 9              | <b>GP</b> – Pin (Plug) Connector Both Ends<br><b>GS</b> – Socket (Receptacle) Connector Both Ends<br><b>CS</b> – Pin Connector to Socket Connector | 4 – #24         | <b>K</b> – M22759/11 600 Vrms Teflon (TFE)<br><b>J</b> – M22759/33 600 Vrms Modified Cross-Linked Tefzel® (ETFE)<br><b>E</b> – NEMA HP3-EB 600 Vrms Type E M16878/4 (TFE) (replaced by M22759/11 for mil spec applications) | 1 – White  | 18<br>Total Length In Inches. “18” Specifies 18 Inches<br>(2” Min. for 2 row, 3” Min. for 3 row, 4” Min. for 4 row) | <b>B</b><br><b>P</b><br><b>M</b><br><b>M1</b><br><b>S</b><br><b>S1</b><br><b>L</b><br><b>K</b> |
|                           |  |  | 15             |  | 6 – #26         |   | 2 – Yellow   |   |  |
|                           |  |  | 21             |  | 8 – #28         |   | 7 – Ten Color Repeating  |   |  |
|                           |  |  | 25             |  | 0 – #30         |   | 5 – Color-Coded Stripes Per MIL-STD-681  |   |  |
|                           |  |  | 31             |  |                 |   | (Striped wire not available on 67, 69 or 100 pin connectors or for #28, #30 AWG) |   |  |
|                           |  |  | 37             |  |                 |   | 7 – Ten Color Repeating  |   |  |
|                           | 51   |  |                |  |                 |   |  |   |  |
|                           | 51-2   |  |                |  |                 |   |  |   |  |
|                           | 67   |  |                |  |                 |   |  |   |  |
|                           | 69   |  |                |  |                 |   |  |   |  |
| 100                       |  |  |                |  |                 |   |  |   |  |
|                           | <b>Stainless Steel Shell</b><br>3 – Passivated   |  |                |  |                 |   |  |   |  |
| <b>Sample Part Number</b> |  |  |                |  |                 |   |  |   |  |
| MWDM                      | 1  | L –  | 25             | GP –   | 6               | K   | 7 –  | 18  | B  |

## MICRO-D MOUNTING HARDWARE

| B   | P   | M   | M1  | S  | S1   | L  | K  |
|---|---|---|---|--|--|--|--|
|   |   |   |   |  |  |  |  |
| <b>Thru-Hole</b><br>Order Hardware Separately | <b>Jackpost</b><br>Removable<br>Includes Nut and Washer | <b>Jackscrew</b><br>Hex Head<br>Removable<br>E-ring | <b>Jackscrew</b><br>Hex Head<br>Removable<br>E-ring<br>Extended | <b>Jackscrew</b><br>Slot Head<br>Removable<br>E-ring | <b>Jackscrew</b><br>Slot Head<br>Removable<br>E-ring<br>Extended | <b>Jackscrew</b><br>Hex Head<br>Non- Removable | <b>Jackscrew</b><br>Slot Head<br>Non-<br>Removable<br>Extended |

# Micro-D Metal Shell MWDM Back-To-Back Unshielded Cable Assemblies



## PERFORMANCE SPECIFICATIONS

|                           |                               |
|---------------------------|-------------------------------|
| Current Rating            | 3 AMP                         |
| DWV                       | 600 VAC Sea level             |
| Insulation Resistance     | 5000 Megohms Minimum          |
| Contact Resistance        | 8 Milliohms Maximum           |
| Low Level Contact Resist. | 32 Milliohms Maximum          |
| Magnetic Permeability     | 2 μ Maximum                   |
| Operating Temperature     | -55° C. to +150° C.           |
| Shock, Vibration          | 50 g., 20g.                   |
| Mating Force              | (10 Ounces) X (# of Contacts) |

## MATERIALS AND FINISHES

|                  |   |
|------------------|---|
| Connector Shell  | Aluminum Alloy 6061 or Stainless Steel, 300 Series, passivated. See Ordering Info for Plating Options |
| Insulator        | Liquid Crystal Polymer (LCP)  |
| Interfacial Seal | Fluorosilicone Rubber, Blue   |
| Pin Contact      | Beryllium Copper Gold over Nickel Plating   |
| Socket Contact   | Copper Alloy Gold Over Nickel Plating   |
| Hardware         | 300 Series Stainless Steel  |
| Encapsulant      | Epoxy Resin Hysol EE4215  |



## DIMENSIONS

| Layout | A Max. |       | B         |           | C Max. |       | D Max. |      | E Max. |       | F         |           | G Max. |       | H Max. |       | J Max. |      |
|--------|--------|-------|-----------|-----------|--------|-------|--------|------|--------|-------|-----------|-----------|--------|-------|--------|-------|--------|------|
|        | In.    | mm.   | In. ±.003 | mm. ±0.08 | In.    | mm.   | In.    | mm.  | In.    | mm.   | In. ±.003 | mm. ±0.08 | In.    | mm.   | In.    | mm.   | In.    | mm.  |
| 9P     | .785   | 19.94 | .565      | 14.35     | .333   | 8.46  | .184   | 4.67 | .308   | 7.82  | .183      | 4.65      | .416   | 10.57 | .400   | 10.16 | .270   | 6.86 |
| 9S     | .785   | 19.94 | .565      | 14.35     | .400   | 10.16 | .250   | 6.35 | .308   | 7.82  | .195      | 4.95      | .429   | 10.90 | .400   | 10.16 | .270   | 6.86 |
| 15P    | .935   | 23.75 | .715      | 18.16     | .483   | 12.27 | .184   | 4.67 | .308   | 7.82  | .183      | 4.65      | .416   | 10.57 | .550   | 13.97 | .270   | 6.86 |
| 15S    | .935   | 23.75 | .715      | 18.16     | .551   | 14.00 | .250   | 6.35 | .308   | 7.82  | .195      | 4.95      | .429   | 10.90 | .550   | 13.97 | .270   | 6.86 |
| 21P    | 1.085  | 27.56 | .865      | 21.97     | .633   | 16.08 | .184   | 4.67 | .308   | 7.82  | .183      | 4.65      | .416   | 10.57 | .700   | 17.78 | .270   | 6.86 |
| 21S    | 1.085  | 27.56 | .865      | 21.97     | .701   | 17.81 | .250   | 6.35 | .308   | 7.82  | .195      | 4.95      | .429   | 10.90 | .700   | 17.78 | .270   | 6.86 |
| 25P    | 1.185  | 30.01 | .965      | 24.51     | .733   | 18.62 | .184   | 4.67 | .308   | 7.82  | .183      | 4.65      | .416   | 10.57 | .800   | 20.32 | .270   | 6.86 |
| 25S    | 1.185  | 30.01 | .965      | 24.51     | .801   | 20.35 | .250   | 6.35 | .308   | 7.82  | .195      | 4.95      | .429   | 10.90 | .800   | 20.32 | .270   | 6.86 |
| 31P    | 1.335  | 33.91 | 1.115     | 28.32     | .883   | 22.43 | .184   | 4.67 | .308   | 7.82  | .183      | 4.65      | .416   | 10.57 | .950   | 24.13 | .270   | 6.86 |
| 31S    | 1.335  | 33.91 | 1.115     | 28.32     | .951   | 24.16 | .250   | 6.35 | .308   | 7.82  | .195      | 4.95      | .429   | 10.90 | .950   | 24.13 | .270   | 6.86 |
| 37P    | 1.485  | 37.72 | 1.265     | 32.13     | 1.033  | 26.24 | .184   | 4.67 | .308   | 7.82  | .183      | 4.65      | .416   | 10.57 | 1.100  | 27.94 | .270   | 6.86 |
| 37S    | 1.485  | 37.72 | 1.265     | 32.13     | 1.101  | 27.96 | .250   | 6.35 | .308   | 7.82  | .195      | 4.95      | .429   | 10.90 | 1.100  | 27.94 | .270   | 6.86 |
| 51P    | 1.435  | 36.45 | 1.215     | 30.86     | .983   | 24.97 | .228   | 5.79 | .351   | 8.92  | .183      | 4.65      | .416   | 10.57 | 1.050  | 26.67 | .310   | 7.87 |
| 51S    | 1.435  | 36.45 | 1.215     | 30.86     | 1.051  | 26.70 | .296   | 7.52 | .351   | 8.92  | .195      | 4.95      | .429   | 10.90 | 1.050  | 26.67 | .310   | 7.87 |
| 51-2P  | 1.835  | 46.61 | 1.615     | 41.02     | 1.384  | 35.15 | .184   | 4.67 | .310   | 7.87  | .183      | 4.65      | .416   | 10.57 | 1.450  | 36.83 | .270   | 6.86 |
| 51-2S  | 1.835  | 46.61 | 1.615     | 41.02     | 1.450  | 36.83 | .250   | 6.35 | .310   | 7.87  | .195      | 4.95      | .429   | 10.90 | 1.450  | 36.83 | .270   | 6.86 |
| 67P    | 2.235  | 56.77 | 2.015     | 51.18     | 1.784  | 45.31 | .184   | 4.67 | .310   | 7.87  | .183      | 4.65      | .416   | 10.57 | 1.850  | 36.83 | .270   | 6.86 |
| 67S    | 2.235  | 56.77 | 2.015     | 51.18     | 1.850  | 46.99 | .250   | 6.35 | .310   | 7.87  | .195      | 4.95      | .429   | 10.90 | 1.850  | 36.83 | .270   | 6.86 |
| 69P    | 1.735  | 44.07 | 1.515     | 38.48     | 1.284  | 32.61 | .228   | 5.79 | .351   | 8.92  | .183      | 4.65      | .416   | 10.57 | 1.350  | 34.29 | .310   | 7.87 |
| 69S    | 1.735  | 44.07 | 1.515     | 38.48     | 1.350  | 34.29 | .296   | 7.52 | .351   | 8.92  | .195      | 4.95      | .429   | 10.90 | 1.350  | 34.29 | .310   | 7.87 |
| 100P   | 2.170  | 55.12 | 1.800     | 45.72     | 1.383  | 35.13 | .270   | 6.86 | .394   | 10.01 | .183      | 4.65      | .416   | 10.57 | 1.442  | 36.63 | .360   | 9.14 |
| 100S   | 2.170  | 55.12 | 1.800     | 45.72     | 1.451  | 36.86 | .333   | 8.46 | .394   | 10.01 | .195      | 4.95      | .429   | 10.90 | 1.442  | 36.63 | .360   | 9.14 |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)