




# Ultra Low Capacitance Bidirectional Symmetrical (BiSy) Single Line ESD-Protection Diode in Silicon Package



## FEATURES

- Ultra compact CLP0603 package
- Low package height < 0.3 mm
- 1-line ESD-protection
- Working range  $\pm 5.5$  V
- Low leakage current < 0.1  $\mu$ A
- Ultra low load capacitance  $C_D = 0.29$  pF typ.
- ESD-protection acc. IEC 61000-4-2  $\pm 16$  kV contact discharge  $\pm 16$  kV air discharge
- Lead plating: Au (e4)
- Lead material: Ni
- Backside coating
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



## MARKING (example only)



1 = year code  
 Open circle = month code and pin 1  
 XY = type code

ORDERING INFORMATION			
DEVICE NAME	ORDERING CODE	TAPED UNITS PER REEL (8 mm TAPE ON 7" REEL)	MINIMUM ORDER QUANTITY
VBUS05B1-SD0	VBUS05B1-SD0-G4-08	15 000	15 000

PACKAGE DATA				
DEVICE NAME	PACKAGE NAME	TYPE CODE	WEIGHT	SOLDERING CONDITIONS
VBUS05B1-SD0	CLP0603	5A	0.12 mg	260 °C/10 s at terminals Reflow soldering according JEDEC® STD-020

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	acc. IEC 61000-4-5, 8/20 $\mu$ s/single shot	$I_{PPM}$	2.5	A
Peak pulse power	Pin 1 to pin 2 acc. IEC 61000-4-5; $t_p = 8/20$ $\mu$ s; single shot	$P_{PP}$	45	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	$V_{ESD}$	$\pm 16$	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		$\pm 16$	
Operating temperature	Junction temperature	$T_J$	-55 to +150	°C
Storage temperature		$T_{stg}$	-55 to +150	°C

**ESD-PROTECTION FOR HIGH-SPEED SIGNAL OR DATA LINES**

The VBUS05B1-SD0 is a Bidirectional and Symmetrical (BiSy) ESD-protection device which clamps positive and negative overvoltage transients to ground. Connected between the signal or data line and the ground the VBUS05B1-SD0 offers a high isolation (low leakage current, low capacitance) within the specified working range. Due to the short leads and small package size of the tiny CLP0603 package the line inductance is very low, so that fast transients like and ESD-strike can be clamped with minimal over- or undershoots. Due to the very low capacitance the VBUS05B1-SD0 can be used for high speed data ports like HDMI, USB 3.0 or Thunderbolt.

<b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)						
PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	$N_{channel}$	-	-	1	lines
Reverse stand-off voltage	Max. reverse working voltage	$V_{RWM}$	-	-	5.5	V
Reverse voltage	at $I_R = 0.1\text{ }\mu\text{A}$	$V_R$	5.5	-	-	V
Reverse current	at $V_{RWM} = 5.5\text{ V}$	$I_R$	-	-	0.1	$\mu\text{A}$
Reverse breakdown voltage	at $I_R = 1\text{ mA}$	$V_{BR}$	6.0	8.5	10	V
Reverse clamping voltage	at $I_{PP} = 1\text{ A}$	$V_C$	-	12	14	V
	at $I_{PP} = I_{PPM} = 2.5\text{ A}$	$V_C$	-	15	18	V
Capacitance	at $V_R = 0\text{ V}$ ; $f = 1\text{ MHz}$	$C_D$	-	0.29	0.4	pF
	at $V_R = 3.3\text{ V}$ ; $f = 1\text{ MHz}$	$C_D$	-	0.29	-	pF
Clamping voltage	Transmission Line Pulse (TLP); $t_p = 100\text{ ns}$ $I_{TLP} = 8\text{ A}$	$V_{C-TLP}$	-	20	-	V
	Transmission Line Pulse (TLP); $t_p = 100\text{ ns}$ $I_{TLP} = 16\text{ A}$		-	29	-	
Dynamic resistance	Transmission Line Pulse (TLP); $t_p = 100\text{ ns}$	$R_{DYN}$	-	1.14	-	$\Omega$

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - ESD Discharge Current Wave Form acc. IEC 61000-4-2 (330  $\Omega$ /150 pF)




Fig. 4 - Typical Peak Clamping Voltage  $V_C$  vs. Peak Pulse Current  $I_{PP}$




Fig. 2 - 8/20  $\mu\text{s}$  Peak Pulse Current Wave Form acc. IEC 61000-4-5




Fig. 5 - Typical Peak Clamping Voltage  $V_C$  vs. Peak Pulse Current  $I_{PP}$







Fig. 3 - Typical Reverse Voltage  $V_R$  vs. Reverse Current  $I_R$




**PACKAGE DIMENSIONS** in millimeters (mils): **CLP0603-2L**

Package = chip dimensions in mm




	Millimeters			mils		
	min.	nom.	max.	min.	nom.	max.
A	0.24	0.27	0.30	9.44	10.63	11.81
A1			0.02			0.79
b	0.22	0.25	0.28	8.66	9.84	11.02
D	0.27	0.30	0.33	10.62	11.81	12.99
E	0.57	0.60	0.63	22.44	23.62	24.80
e		0.40			15.75	
e1		0.25			9.84	
L	0.12	0.15	0.18	4.72	5.91	7.09

footprint recommendation:



footprint recommendation 2:



22740

2 terminal leadless package (CLP0603-2L LLP)


Document no.: S8-V-3906.04-023 (4)

Created - Date: 22. Nov. 2010

Rev.4 - Date: 07. May 2014




CARRIER TAPE in millimeters: CLP0603



Cummulative tolerances of 10 sprocket holes is +/-0.2mm

22591  
Document no. S8-V-3906.04-0025 (4)  
Created - Date: 22. Nov. 2010

ORIENTATION IN CARRIER CLP0603



22607  
Orientation in Carrier Tape (CLP0603)  
S8-V-3906.04-026 (4)  
22.10.2010

**APPLICATION NOTE**

**1. PCB FOOTPRINT DESIGN**

Verified by internal tests, Vishay recommends the soldering pad and solder mask opening design as shown in fig. 1. We recommend using a non-solder mask defined (NSMD) design, as shown below. The reason is that with a NSMD design, the size of the actual solder pad is more accurate (tolerances for copper etchings are smaller compared to a solder mask defined process).




Fig. 1 - Recommended Soldering Pad Design

**2. PCB SOLDERING PAD METALLIZATION**

There are several common pad metallization/finishes, including OSP (Organic Solderability Protectant), HASL (Hot Air Solder Level), and ENiAu. Because of the CLP0603's extremely small size, Vishay only recommends using the electroless Ni/immersion gold over copper pad plating.

**3. SCREEN PRINT PROCESS**

The solder paste is applied to the PCB by using a screen print process.

**3.1 STANDARD RECOMMENDATION FOR PC BOARD FOOTPRINT AND STENCIL:**

The recommended stencil thickness for the CLP0603 package is 80 µm (the absolute maximum is 100 µm). The recommended dimensions for the stencil openings are 12 mil (300 µm) by 8 mil (200 µm) for both pads. The side wall of the stencil openings should be tapered approximately 5 degrees. An electro-polished finish will support a better release of the paste.




Fig. 2 - Maximum Stencil Openings - for a Stencil Thickness of 80 µm


**Note**

- A wider stencil opening will result in a better solder paste release from the stencil. So the best quality can be obtained by using the optimum between the stencil quality, thickness, and opening.

If a tilting of the package is observed, the amount of solder paste should be reduced slightly. Please also take into consideration the direct relation between the amount of solder paste and the package shear strength.

**3.2 ALTERNATIVE RECOMMENDATION FOR PC BOARD FOOTPRINT AND STENCIL:**

footprint recommendation 2:



Footprint (solder land): 0.22 mm x 0.12 mm (2 x)  
 Stencil thickness: 125 µm (5 mil) usable  
 Stencil opening: 0.2 mm (round)


**4. SOLDER PASTE TYPE**

Type 4 solder pastes (or smaller powder sizes) are recommended. In our evaluation we used the Cookson Electronics' Alpha OM-338 CSP (96.5 % Sn/3 % Ag/0.5 % Cu) solder paste.

**5. REFLOW SOLDERING PROCESS**

A standard surface-mount reflow soldering process can be used (reference: JPC/JEDEC® J-STD-020D).

However, for an optimum process, recommendations from the solder paste supplier should be considered. Variations in chemistry and viscosity of the fluxer may require small adjustments to the soldering profile.


**TABLE 1 - CLASSIFICATION REFLOW PROFILES**

PROFILE FEATURE	SnPb EUTECTIC ASSEMBLY	LEAD (Pb)-FREE ASSEMBLY
<b>PREHEAT AND SOAK</b>		
Temperature min. ( $T_{Smin.}$ )	100 °C	150 °C
Temperature max. ( $T_{Smax.}$ )	150 °C	200 °C
Time ( $T_{Smin.}$ to $T_{Smax.}$ ) ( $t_s$ )	60 s to 120 s	60 s to 120 s
Average ramp-up rate ( $T_{Smax.}$ to $T_P$ )	3 °C/s maximum	
Liquidous temperature ( $T_L$ )	183 °C	217 °C
Time to liquidous ( $t_L$ )	60 s to 150 s	60 s to 150 s
Peak package temperature ( $T_P$ ) <sup>(1)</sup>	See classification temperature in table 3	See classification temperature in table 4
Time ( $t_p$ ) <sup>(2)</sup> with 5 °C of the specified classification temperature ( $T_C$ )	20 s <sup>(2)</sup>	30 s <sup>(2)</sup>
Average ramp-down rate ( $T_P$ to $T_{Smax.}$ )	6 °C/s maximum	
Time 25 °C to peak temperature	6 min maximum	8 min maximum

**Notes**

- (1) Tolerance for peak profile temperature ( $T_P$ ) is defined as a supplier minimum and user maximum  
 (2) Tolerance for time at peak profile temperature ( $T_P$ ) is defined as a supplier minimum and user maximum

**Notes**

- All temperatures refer to the center of the package, measured on the package body surface that is facing up during assembly reflow (e.g. live-bug). If parts are reflowed in other than the normal live-bug assembly reflow orientation (i.e. dead-bug),  $T_P$  shall be within  $\pm 2$  °C of the live-bug  $T_P$  and still meet the  $T_C$  requirements, otherwise, the profile shall be adjusted to achieve the latter. To accurately measure actual peak package body temperatures refer to JEP140 for the recommended thermocouple use.
- Reflow profiles in this document are for classification/preconditioning and are not meant to specify board assembly profiles. Actual board assembly profiles should be developed based on specific process needs and board designs and should not exceed the parameters in table 1. For example, if  $T_C$  is 260 °C and time  $t_p$  is 30 s, this means the following for the supplier and the user:
  - For a supplier: The peak temperature must be at least 260 °C. The time above 255 °C must be at least 30 s.
  - For a user: The peak temperature must not exceed 260 °C. The time above 255 °C must not exceed 30 s.
- All components in the test load shall meet the classification profile requirements.
- SMD packages classified to a given moisture sensitivity level by using procedures or criteria defined within any previous version of J-STD-020, JESD22-A112 (rescinded), IPC-SM-786 (rescinded) do not need to be reclassified to the current revision unless a change in classification level or a higher peak classification temperature is desired.

**TABLE 2 - SnPb EUTECTIC PROCESS - CLASSIFICATION TEMPERATURES (T<sub>c</sub>)**

PACKAGE THICKNESS	VOLUME mm <sup>3</sup> < 350	VOLUME mm <sup>3</sup> ≥ 350
< 2.5 mm	235 °C	220 °C
≥ 2.5 mm	220 °C	220 °C

**TABLE 3 - LEAD (Pb)-FREE PROCESS - CLASSIFICATION TEMPERATURES (T<sub>c</sub>)**



PACKAGE THICKNESS	VOLUME mm <sup>3</sup> < 350	VOLUME mm <sup>3</sup> 350 to 2000	VOLUME mm <sup>3</sup> > 2000
< 1.6 mm	260 °C	260 °C	260 °C
1.6 mm to 2.5 mm	260 °C	250 °C	245 °C
> 2.5 mm	250 °C	245 °C	245 °C

**Notes**

- At the direction of the device manufacturer, but not the board assembler/user, the maximum peak package body temperature (T<sub>p</sub>) can exceed the values specified in tables 2 and 3. The use of a higher T<sub>p</sub> does not change the classification temperature (T<sub>c</sub>).
- Package volume excludes external terminals (e.g., balls, bumps, lands, leads) and/or nonintegral heat sinks.
- The maximum component temperature reached during reflow depends on package thickness and volume. The use on convection reflow processes reduces the thermal gradients between packages. However thermal gradients due to differences in thermal mass of SMD packages may still exist.
- Moisture sensitivity levels of components intended for use in a lead (Pb)-free assembly process shall be evaluated using the lead (Pb)-free classification temperatures and profiles defined in table 1 and 3, whether or not lead (Pb)-free.
- SMD packages classified to a given moisture sensitivity level by using procedures or criteria defined within any previous version of J-STD-020, JESD22-A112 (rescinded), IPC-SM-786 (rescinded) do not need to be reclassified to the current revision unless a change in classification level or a higher peak classification temperature is desired.

**6. SOLDERING QUALITY INSPECTION**

An X-ray inspection system is required to find defects such as shorts between pads, open contacts, and voids within the solder. In addition, a visual inspection by microscope or camera (of appropriate magnification) can be used to inspect the sides of the solder joints for acceptable shape and molten solder.


**7. SHEAR TEST COMPARISON**

The data below shows a comparison of shear strength after a reflow soldering process.

	VISHAY	COMPETITOR 1	COMPETITOR 2	COMPETITOR 3
Typical shear strength	500 g	350 g	600 g	440 g

**8. REWORK PROCEDURE**

For rework, the CLP0603 package must be removed from the PCB if there is any issue with the solder joints. Standard SMT rework systems are recommended for this. Due to the small size of the package, the rework system should be equipped with a proper magnification aid.

**9. INTERCHANGEABILITY OF THE CLP WITH A PLASTIC PACKAGE OF THE SAME SIZE**

Based on our studies, the CLP is 100 % compatible with plastic packages of the same size.





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)